

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: EIGA108

Issue date: 16/01/2013 Revision date: 18/09/2025 Supersedes version of: 01/08/2019 Version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

 Product form
 : Substance

 Name
 : Silicon tetrafluoride

 EC-No.
 : 232-015-5

 CAS-No.
 : 7783-61-1

 REACH registration No.
 : 01-2120762243-59

Product code : 000010021730

Formula : SiF4

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Electronic component manufacture.

Use of the substance/mixture : Using gas alone or in mixtures for the calibration of analysis equipment.

1.2.2. Uses advised against

Uses advised against : Consumer use.

Uses other than those listed above are not supported, contact your supplier for more

information on other uses.

1.3. Details of the supplier of the safety data sheet

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura
Austria
T +43 50 4273
office@at.linde-gas.com

1.4. Emergency telephone number

Emergency number : UMCO/NCEC: +44 1865 407333 (English); +49 89 220 61012 (German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure: Liquefied gas H280
Health hazards Acute toxicity (inhalation:gas) Category 2 H330
Skin corrosion/irritation, Category 1, Sub-Category 1A H314
Serious eye damage/eye irritation, Category 1 H318

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

AT - en 1/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

H314 - Causes severe skin burns and eye damage.

H330 - Fatal if inhaled.

EUH-statements : EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention : P260 - Do not breathe gas, vapours.

P280 - Wear eye protection, face protection, protective clothing, protective gloves.

- Response : P303+P361+P353+P315 - IF ON SKIN : (or hair) Take off immediately all contaminated

clothing. Rinse skin with water or shower. Get immediate medical advice.

P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for

breathing. Get immediate medical advice.

P305+P351+P338+P315 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice.

- Storage : P403 - Store in a well-ventilated place.

P405 - Store locked up.

2.3. Other hazards

Other hazards : Not classified as PBT or vPvB. Not classified as PMT or vPvM . The substance/mixture has

no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Silicon tetrafluoride	CAS-No.: 7783-61-1 EC-No.: 232-015-5 REACH-no: 01-2120762243- 59	100	Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 EUH071

Specific concentration limits:			
Name	Product identifier	Specific concentration limits	
Silicon tetrafluoride	CAS-No.: 7783-61-1 EC-No.: 232-015-5 REACH-no: 01-2120762243- 59	(1 ≤ C ≤ 100) STOT SE 3; H335	

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable

AT - en 2/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

First-aid measures after skin contact

In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Remove contaminated clothing. Drench affected area with water for at least 15 minutes.

First-aid measures after eye contact First-aid measures after ingestion

: Immediately flush eyes thoroughly with water for at least 15 minutes.

: Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed

Prolonged exposure to small concentrations may result in pulmonary oedema.

Delayed adverse effects possible.

May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.

Material is destructive to tissue of the mucuous membranes and upper respiratory tract.

Cough, shortness of breath, headache, nausea.

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance. Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Water spray or fog. Product does not burn, use fire control measures appropriate for the

surrounding fire.

Unsuitable extinguishing media

: Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire

: No reactivity hazard other than the effects described in sub-sections below.

Specific hazards

: Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products

: Hydrogen fluoride.

5.3. Advice for firefighters

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

Wear gas tight chemically protective clothing in combination with self contained breathing

Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

AT - en 3/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.

6.1.2. For emergency responders

Emergency procedures

: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use chemically protective clothing. Monitor concentration of released product. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Reduce vapour with fog or fine water spray. Try to stop release.

6.3. Methods and material for containment and cleaning up

Methods and material for containment and cleaning

up

: Hose down area with water.

Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Avoid contact with aluminium.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid exposure, obtain special instructions before use.

Do not smoke while handling product.

Avoid suck back of water, acid and alkalis.

Only experienced and properly instructed persons should handle gases under pressure.

Ensure the complete gas system was (or is regularily) checked for leaks before use. Installation of a cross purge assembly between the container and the regulator is

recommended.

Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.

The product must be handled in accordance with good industrial hygiene and safety procedures.

Consider pressure relief device(s) in gas installations.

Do not breathe gas.

Avoid release of product into work area.

Use only lubricants and sealings approved for the specific gas service.

AT - en 4/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Safe handling of the gas receptacle

: Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatibilities

: Store locked up.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps, when provided, should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Silicon tetrafluoride (7783-61-1)		
DNEL/DMEL (additional information)		
Additional information None established.		
PNEC (additional information)		
Additional information None established.		

8.1.5. Control banding

No additional information available

AT - en 5/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Product to be handled in a closed system and under strictly controlled conditions. Preferably use permanent leak-tight installations (e.g. welded pipes). Gas detectors should be used when toxic gases may be released. Consider the use of a work permit system e.g. for maintenance activities. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available).

Personal protection equipment

Personal protective equipment:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Wear goggles and a face shield when transfilling or breaking transfer connections. Provide readily accessible eye wash stations and safety showers. Standard EN 166 - Personal eye-protection - specifications

Skin protection

Hand protection:

Wear working gloves when handling gas containers. Wear chemically resistant protective gloves. Standard EN 374 - Protective gloves against chemicals. Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms. Consult glove manufacturer's product information on material suitability and material thickness. The breakthrough time of the selected gloves must be greater than the intended use period.

Respiratory protection

Respiratory protection:

Recommended: Filter B (grey). Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Gas filters do not protect against oxygen deficiency. Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks . Keep self contained breathing apparatus readily available for emergency use.

Thermal hazards

Thermal hazard protection:

None in addition to the above sections.

Environmental exposure controls

Environmental exposure controls:

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Other information:

Keep suitable chemically resistant protective clothing readily available for emergency use. Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state : G

Colour : Gives off white fumes in moist air. Colourless.

Form : Liquefied gas

AT - en 6/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Odour : Pungent.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

Melting point : -86.8 °C
Freezing point : Not applicable
Boiling point : -95.2 °C
Flammability : Non flammable.
Oxidising properties : No oxidising properties.

Explosive limits : Not available
Lower explosion limit : Not applicable.
Upper explosion limit : Not applicable.

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable. Decomposition temperature : Not applicable.

pH : If dissolved in water pH-value will be affected.

Viscosity, kinematic : No reliable data available.
Viscosity, dynamic : No reliable data available.
Solubility in water : Completely soluble.

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic products. Partition coefficient n-octanol/water (Log Pow) : Not applicable for gas mixtures.

Vapour pressure : Not applicable.

Vapour pressure at 50°C : Not applicable.

Critical pressure : 3720 kPa

Density : 37.2 g/cm³ 20.0 °C

Relative density : Not known.

Relative vapour density at 20°C : Not applicable. Relative gas density : 3.6

Particle characteristics : Not applicable

Not applicable for gases and gas mixtures.

Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Critical temperature : -14.1 °C

9.2.2. Other safety characteristics

Molecular mass : 104 g/mol
Gas group : Press. Gas (Liq.)

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

May react violently with alkalis. Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas. With water causes rapid corrosion of some metals. Reacts with water to form corrosive acids. Moisture. For additional information on compatibility refer to ISO 11114.

AT - en 7/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Fatal if inhaled.

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Inhalation:gas: Fatal if inhaled.

LC50 Inhalation - Rat [ppm] 922 ppm/1h (ADR) 461 ppm/4h (CLP)

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: If dissolved in water pH-value will be affected.

Serious eye damage/irritation : Causes serious eye damage.

pH: If dissolved in water pH-value will be affected.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Reproductive toxicity : Not classified

Toxic for reproduction: Fertility : No known effects from this product.

Toxic for reproduction: unborn child : No known effects from this product.

STOT-single exposure : May cause nausea and irritation of the respiratory tract. Hydrolysis of silanes in the body

forms silicic acid or hydrated silica. Severe corrosion to the respiratory tract at high

concentrations.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

Silicon tetrafluoride (7783-61-1)

Viscosity, kinematic No reliable data available.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information

: Absorption of excessive fluorides can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys), Delayed fatal pulmonary oedema possible, The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

Not rapidly degradable

Silicon	tetrafluo	ride (7783-	61_1)
SIIICUII	tetraniuo	iiue i	1103-	0 I - I I

LC50 96 h - Fish [mg/l] No data available.

AT - en 8/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Silicon tetrafluoride (7783-61-1)		
EC50 48h - Daphnia magna [mg/l] No data available.		
EC50 72h - Algae [mg/l]	No data available.	

12.2. Persistence and degradability

Silicon tetrafluoride (7783-61-1)	
Assessment	Not applicable for inorganic products.

12.3. Bioaccumulative potential

Silicon tetrafluoride (7783-61-1)		
Partition coefficient n-octanol/water (Log Pow) Not applicable for gas mixtures.		
Partition coefficient n-octanol/water (Log Kow)	Not applicable for inorganic products.	

12.4. Mobility in soil

Silicon tetrafluoride (7783-61-1)	
	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

: Not classified as PBT or vPvB. Assessment

12.6. Endocrine disrupting properties

Other adverse effects	: May cause pH changes in aqueous ecological systems. Not classified as PMT or vPvM.	
Assessment	: The substance/mixture has no endocrine disrupting properties.	

12.7. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems. Not classified as PMT or vPvM.

Effect on the ozone layer : No effect on the ozone layer. Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Gases formed by combustion should be washed with water to remove silica. Contact supplier if guidance is required. Must not be discharged to atmosphere. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
HP Code	: HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal

administration, or inhalation exposure.

HP8 - "Corrosive:" waste which on application can cause skin corrosion.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

> AT - en 9/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	umber			
UN 1859	UN 1859	UN 1859	UN 1859	UN 1859
14.2. UN proper shippin	g name			
SILICON TETRAFLUORIDE	SILICON TETRAFLUORIDE	Silicon tetrafluoride	SILICON TETRAFLUORIDE	SILICON TETRAFLUORIDE
Transport document descr	iption			
UN 1859 SILICON TETRAFLUORIDE, 2.3 (8), (C/D)	UN 1859 SILICON TETRAFLUORIDE, 2.3 (8)	UN 1859 Silicon tetrafluoride, 2.3 (8)	UN 1859 SILICON TETRAFLUORIDE, 2.3 (8)	UN 1859 SILICON TETRAFLUORIDE, 2.3 (8)
14.3. Transport hazard o	class(es)			
2.3 (8)	2.3 (8)	2.3 (8)	2.3 (8)	2.3 (8)
2 8	2 8	Not applicable	2 8	2 8
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is correctly fitted.

Overland transport

Classification code (ADR) : 2TC Limited quantities (ADR) : 0 Excepted quantities (ADR) : E0 : P200 Packing instructions (ADR) : MP9 Mixed packing provisions (ADR) Portable tank and bulk container instructions (ADR) : (M) Tank code (ADR) : PxBH(M) Tank special provisions (ADR) : TA4, TT9 Vehicle for tank carriage : AT Transport category (ADR)

Special provisions for carriage - Loading, unloading : CV9, CV10, CV36

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S14 Hazard identification number (Kemler No.) : 268

AT - en 10/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates : 200

268 1859

Tunnel restriction code (ADR) : C/D

Transport by sea

Limited quantities (IMDG) : 0

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P200

EmS-No. (Fire) : F-C

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : D

Stowage and handling (IMDG) : SW2

Properties and observations (IMDG) : Non-flammable, toxic and corrosive gas with a pungent odour. Corrosive to metals.In moist

air produces hydrogen fluoride. Much heavier than air (3.6). Highly irritating to skin, eyes

and mucous membranes.

Air transport

PCA Limited quantities (IATA) : FORBIDDEN
PCA limited quantity max net quantity (IATA) : FORBIDDEN
PCA packing instructions (IATA) : FORBIDDEN
PCA max net quantity (IATA) : FORBIDDEN
CAO packing instructions (IATA) : FORBIDDEN
CAO max net quantity (IATA) : FORBIDDEN
Special provisions (IATA) : A2

Special provisions (IATA) : A2 ERG code (IATA) : 2CP

Inland waterway transport

Classification code (ADN) : 2TC
Limited quantities (ADN) : 0
Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EP, TOX, A

Ventilation (ADN) : VE02 Number of blue cones/lights (ADN) : 2

Rail transport

Classification code (RID) : 2TC
Limited quantities (RID) : 0
Excepted quantities (RID) : E0
Packing instructions (RID) : P200
Mixed packing provisions (RID) : MP9
Portable tank and bulk container instructions (RID) : (M)
Tank codes for RID tanks (RID) : PxBH(M)

Special provisions for RID tanks (RID) : TU38, TE22, TE25, TA4, TT9, TM6

Transport category (RID) : 1

Special provisions for carriage - Loading, unloading : CW9, CW10, CW36

and handling (RID)

Hazard identification number (RID) : 268

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

AT - en 11/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

VOC Directive (2004/42)

Restrictions on use : None.

Seveso Directive (Disaster Risk Reduction)

Seveso Directive: 2012/18/EU (Seveso III) : Covered.

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
H2 ACUTE TOXIC — Category 2, all exposure routes — Category 3, inhalation exposure route	50	200

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Ensure all national/local regulations are observed.

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 2016/425/EEC on personal protective equipment

Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX)

Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2. Chemical safety assessment

A CSA has not yet been carried out.

SECTION 16: Other information

Indication of changes:

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	ADR - Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	ATE - Acute Toxicity Estimate	
BLV	Biological limit value	

AT - en 12/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
BOD	Biochemical oxygen demand (BOD)	
CAO	Cargo Aircraft only / Cargo Aircraft only	
CAS-No.	Chemical Abstract Service number	
CLP	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
COD	Chemical oxygen demand (COD)	
CSA	CSA - Chemical Safety Assessment	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Median effective concentration	
EC	European Inventory of Existing Commercial Chemical Substances	
ED	Endocrine disruptor	
EINECS	EINECS - European Inventory of Existing Commercial Chemical Substances	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
IOELV	Indicative Occupational Exposure Limit Value	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
N.O.S.	Not Otherwise Specified	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PCA	Passenger and Cargo Aircraft / Passenger and Cargo Aircraft	
PNEC	Predicted No-Effect Concentration	
PPE	PPE - Personal Protection Equipment	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
RMM	RMM - Risk Management Measures	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
TRGS	Technical Rules for Hazardous Substances	
STOT-RE	Specific Target Organ Toxicity-Repeated Exposure	
STOT-SE	Specific Target Organ Toxicity-Single Exposure	

AT - en 13/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
UFI	Unique Formula Identifier	
UN	UN - United Nations	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and Very Bioaccumulative	
WGK	Water Hazard Class	

Training advice

: Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Other information

: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169: 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements:		
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H280	Contains gas under pressure; may explode if heated.	
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H335	May cause respiratory irritation.	
EUH071	Corrosive to the respiratory tract.	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet (SDS), EU AT

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

End of document

AT - en 14/14