



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Reference number: EIGA113
 Issue date: 16/01/2013 Revision date: 20/11/2024 Supersedes version of: 14/04/2022 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
 Name : sulphur dioxide
 EC Index-No. : 016-011-00-9
 EC-No. : 231-195-2
 CAS-No. : 7446-09-5
 REACH registration No. : 01-2119485028-34
 Product code : 000010021800
 Formula : SO₂

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Relevant identified uses : See the list of identified uses and exposure scenarios in the annex of the safety data sheet.
 Perform risk assessment prior to use.

Use of the substance/mixture : Refrigerant
 Metal coating
 Calibration gas for analytical equipment
 Formulation of mixtures with gas in pressure receptacles.
 Glass processing.
 Preservative in food industry.
 Using gas as feedstock in chemical processes.
 Using gas alone or in mixtures for the calibration of analysis equipment.
 Using gas for metal treatment.
 Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use. Under controlled conditions.
 Industrial and professional. Perform risk assessment prior to use.
 Raw material for pharmaceutical products
 Water treatment

Title	Life cycle stage	Use descriptors
Industrial uses, closed contained conditions (ES Ref.: EIGA113-1)		PROC1, PROC8b, PROC9, ERC2
Industrial uses, closed and open conditions (ES Ref.: EIGA113-2)		PROC1, PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC22, PROC23, ERC2, ERC4, ERC6a, ERC6b, ERC6d
Professional uses (ES Ref.: EIGA113-3)		PROC8b, PROC9, PROC19, ERC6a, ERC7

Full text of use descriptors: see section 16

1.2.2. Uses advised against

Uses advised against : Consumer use.
 Uses other than those listed above are not supported, contact your supplier for more information on other uses.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1.3. Details of the supplier of the safety data sheet

Linde Gas GmbH
 Carl-von-Linde-Platz 1
 A-4651 Stadl-Paura
 Austria
 T +43 50 4273
office@at.linde-gas.com

1.4. Emergency telephone number

Emergency number : UMCO/NCEC: +44 1865 407333 (English); +49 89 220 61012 (German)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Gases under pressure : Liquefied gas	H280
Health hazards	Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318
	Acute toxicity (inhalation:gas) Category 3	H331

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04 GHS05 GHS06

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H280 - Contains gas under pressure; may explode if heated.
 H314 - Causes severe skin burns and eye damage.
 H331 - Toxic if inhaled.

EUH-statements :

EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention

: P260 - Do not breathe gas, vapours.
 P280 - Wear eye protection, face protection, protective clothing, protective gloves.

- Response

: P303+P361+P353+P315 - IF ON SKIN : (or hair) Take off immediately all contaminated clothing. Rinse skin with water or shower. Get immediate medical advice.
 P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice.
 P305+P351+P338+P315 - IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Storage : P403 - Store in a well-ventilated place.
P405 - Store locked up.

2.3. Other hazards

Other hazards : Not classified as PBT or vPvB. The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
sulphur dioxide	CAS-No.: 7446-09-5 EC-No.: 231-195-2 EC Index-No.: 016-011-00-9 REACH-no: 01-2119485028-34	100	Press. Gas (Liq.), H280 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3 (Inhalation:gas), H331 (ATE=1260 ppmv/4h) EUH071

Specific concentration limits:

Name	Product identifier	Specific concentration limits
sulphur dioxide	CAS-No.: 7446-09-5 EC-No.: 231-195-2 EC Index-No.: 016-011-00-9 REACH-no: 01-2119485028-34	(1 ≤ c ≤ 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.

First-aid measures after skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Most important symptoms and effects, both acute and delayed

Prolonged exposure to small concentrations may result in pulmonary oedema.
 May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
 Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
 See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance. Treat with corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None that are more hazardous than the product itself.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
 If possible, stop flow of product.
 Use water spray or fog to knock down fire fumes if possible.
 Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
 Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
 Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.1.2. For emergency responders

Emergency procedures : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use chemically protective clothing. Monitor concentration of released product. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Reduce vapour with fog or fine water spray. Try to stop release.

6.3. Methods and material for containment and cleaning up

Methods and material for containment and cleaning up : Hose down area with water.
Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product : Use only lubricants and sealings approved for the specific gas service.
Installation of a cross purge assembly between the container and the regulator is recommended.
Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
Avoid exposure, obtain special instructions before use.
The product must be handled in accordance with good industrial hygiene and safety procedures.
Only experienced and properly instructed persons should handle gases under pressure.
Consider pressure relief device(s) in gas installations.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
Do not smoke while handling product.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Avoid suck back of water, acid and alkalis.
Do not breathe gas.
Avoid release of product into work area.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Safe handling of the gas receptacle : Refer to supplier's container handling instructions.
 Do not allow backfeed into the container.
 Protect containers from physical damage; do not drag, roll, slide or drop.
 When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
 Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
 If user experiences any difficulty operating valve discontinue use and contact supplier.
 Never attempt to repair or modify container valves or safety relief devices.
 Damaged valves should be reported immediately to the supplier.
 Keep container valve outlets clean and free from contaminants particularly oil and water.
 Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
 Close container valve after each use and when empty, even if still connected to equipment.
 Never attempt to transfer gases from one cylinder/container to another.
 Never use direct flame or electrical heating devices to raise the pressure of a container.
 Do not remove or deface labels provided by the supplier for the identification of the content of the container.
 Suck back of water into the container must be prevented.
 Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatibilities : Observe all regulations and local requirements regarding storage of containers.
 Containers should not be stored in conditions likely to encourage corrosion.
 Container valve guards or caps should be in place.
 Containers should be stored in the vertical position and properly secured to prevent them from falling over.
 Stored containers should be periodically checked for general condition and leakage.
 Keep container below 50°C in a well ventilated place.
 Store containers in location free from fire risk and away from sources of heat and ignition.
 Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

sulphur dioxide (7446-09-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Sulphur dioxide
IOEL TWA	1.3 mg/m ³
IOEL TWA [ppm]	0.5 ppm
IOEL STEL	2.7 mg/m ³
IOEL STEL [ppm]	1 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

sulphur dioxide (7446-09-5)	
Austria - Occupational Exposure Limits	
Local name	Schwefeldioxid
MAK (OEL TWA)	1.3 mg/m ³
MAK (OEL TWA) [ppm]	0.5 ppm
MAK (OEL STEL)	2.7 mg/m ³ (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	1 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 156/2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

sulphur dioxide (7446-09-5)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	2.7 mg/m ³
Long-term - local effects, inhalation	2.7 mg/m ³
PNEC (additional information)	
Additional information	None established.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Gas detectors should be used when toxic gases may be released. Consider the use of a work permit system e.g. for maintenance activities. Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available).

8.2.2. Personal protection equipment

Personal protective equipment:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.

Personal protective equipment symbol(s):





sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Wear goggles and a face shield when transfilling or breaking transfer connections.
 Provide readily accessible eye wash stations and safety showers.
 Standard EN 166 - Personal eye-protection - specifications

8.2.2.2. Skin protection

Hand protection:

Wear working gloves when handling gas containers.
 Wear chemically resistant protective gloves.
 Standard EN 374 - Protective gloves against chemicals.
 Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.
 Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
 Chloroprene rubber (Neoprene®) (CR)

Other skin protection

Keep suitable chemically resistant protective clothing readily available for emergency use.
 Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
 Wear safety shoes while handling containers.
 Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Other information:

Keep suitable chemically resistant protective clothing readily available for emergency use.
 Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
 Wear safety shoes while handling containers.
 Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

8.2.2.3. Respiratory protection

Respiratory protection:

Recommended: Filter E (yellow).
 Keep self contained breathing apparatus readily available for emergency use.
 Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
 Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
 Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
 Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
 Gas filters do not protect against oxygen deficiency.
 Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .

8.2.2.4. Thermal hazards

Thermal hazard protection:

None in addition to the above sections.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance
 Physical state : Gas



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Colour	: Colourless.
Form	: Liquefied gas
Odour	: Pungent.
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.
Melting point	: -75.5 °C
Freezing point	: Not applicable
Boiling point	: -10 °C
Flammability	: Non flammable.
Oxidising properties	: No oxidising properties.
Explosive limits	: Not known.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: If dissolved in water pH-value will be affected.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Viscosity, dynamic	: 0.012 mPa·s @ 18 °C; Not applicable for gases and gas mixtures.
Solubility in water	: Completely soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Partition coefficient n-octanol/water (Log Pow)	: Not applicable for gas mixtures.
Vapour pressure	: 3.3 bar(a)
Vapour pressure at 50°C	: 8.4 bar(a)
Critical pressure	: 7884 kPa
Density	: 2.51 g/l 25 °C
Relative density	: 1.5
Relative vapour density at 20°C	: Not applicable.
Relative gas density	: 2.3
Particle characteristics	: Not applicable Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Critical temperature : 158 °C

9.2.2. Other safety characteristics

Molecular mass : 64 g/mol
 Gas group : Press. Gas (Liq.)
 Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

May react violently with alkalis. Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas. With water causes rapid corrosion of some metals. Reacts with water to form corrosive acids. Moisture. For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxic if inhaled.
 Acute toxicity (dermal) : Not classified
 Acute toxicity (inhalation) : Toxic if inhaled.

sulphur dioxide (7446-09-5)	
LC50 Inhalation - Rat [ppm]	1260 ppm/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.
 pH: If dissolved in water pH-value will be affected.

Serious eye damage/irritation : Causes serious eye damage.
 pH: If dissolved in water pH-value will be affected.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Reproductive toxicity : Not classified

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : Severe corrosion to the respiratory tract at high concentrations.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

sulphur dioxide (7446-09-5)	
Viscosity, kinematic	Not applicable for gases and gas mixtures.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information : Delayed fatal pulmonary oedema possible, The substance/mixture has no endocrine disrupting properties.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.
 Hazardous to the aquatic environment, short-term (acute) : Not classified
 Hazardous to the aquatic environment, long-term (chronic) : Not classified

sulphur dioxide (7446-09-5)	
LC50 96 h - Fish [mg/l]	No data available.
EC50 48h - Daphnia magna [mg/l]	89 mg/l
EC50 72h - Algae [mg/l]	48.1 mg/l

12.2. Persistence and degradability

sulphur dioxide (7446-09-5)	
Assessment	Not applicable for inorganic products.

12.3. Bioaccumulative potential

sulphur dioxide (7446-09-5)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for gas mixtures.
Partition coefficient n-octanol/water (Log Kow)	Not applicable for inorganic products.
Assessment	Product is an inorganic gas with a low potential to bioaccumulate in aquatic species.

12.4. Mobility in soil

sulphur dioxide (7446-09-5)	
Assessment	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Other adverse effects : May cause pH changes in aqueous ecological systems.
 Assessment : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.
 Effect on the ozone layer : No effect on the ozone layer.
 Effect on global warming : No known effects from this product.



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction. Contact supplier if guidance is required. Must not be discharged to atmosphere. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods. Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1079	UN 1079	UN 1079	UN 1079	UN 1079
14.2. UN proper shipping name				
SULPHUR DIOXIDE	SULPHUR DIOXIDE	Sulphur dioxide	SULPHUR DIOXIDE	SULPHUR DIOXIDE
Transport document description				
UN 1079 SULPHUR DIOXIDE, 2.3 (8), (C/D)	UN 1079 SULPHUR DIOXIDE, 2.3 (8)	UN 1079 Sulphur dioxide, 2.3 (8)	UN 1079 SULPHUR DIOXIDE, 2.3 (8)	UN 1079 SULPHUR DIOXIDE, 2.3 (8)
14.3. Transport hazard class(es)				
2.3 (8)	2.3 (8)	2.3 (8)	2.3 (8)	2.3 (8)
		Not applicable		
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				



sulphur dioxide

Safety Data Sheet


according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is correctly fitted.

Overland transport

Classification code (ADR) : 2TC
 Limited quantities (ADR) : 0
 Excepted quantities (ADR) : E0
 Packing instructions (ADR) : P200
 Mixed packing provisions (ADR) : MP9
 Portable tank and bulk container instructions (ADR) : (M), T50
 Portable tank and bulk container special provisions (ADR) : TP19
 Tank code (ADR) : PxDH(M)
 Tank special provisions (ADR) : TA4, TT9, TT10
 Vehicle for tank carriage : AT
 Transport category (ADR) : 1
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV10, CV36
 Special provisions for carriage - Operation (ADR) : S14
 Hazard identification number (Kemler No.) : 268
 Orange plates :



Tunnel restriction code (ADR) : C/D

Transport by sea

Limited quantities (IMDG) : 0
 Excepted quantities (IMDG) : E0
 Packing instructions (IMDG) : P200
 Tank instructions (IMDG) : T50
 Tank special provisions (IMDG) : TP19
 EmS-No. (Fire) : F-C
 EmS-No. (Spillage) : S-U
 Stowage category (IMDG) : D
 Stowage and handling (IMDG) : SW2
 Properties and observations (IMDG) : Non-flammable, toxic and corrosive gas with a pungent odour. Much heavier than air (2.3). Highly irritating to skin, eyes and mucous membranes.

Air transport

PCA Limited quantities (IATA) : FORBIDDEN
 PCA limited quantity max net quantity (IATA) : FORBIDDEN
 PCA packing instructions (IATA) : FORBIDDEN
 PCA max net quantity (IATA) : FORBIDDEN
 CAO packing instructions (IATA) : FORBIDDEN
 CAO max net quantity (IATA) : FORBIDDEN
 Special provisions (IATA) : A2



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ERG code (IATA) : 2CP

Inland waterway transport

Classification code (ADN) : 2TC
 Special provisions (ADN) : 274, 392, 662
 Limited quantities (ADN) : 0
 Excepted quantities (ADN) : E0
 Equipment required (ADN) : PP, EP, TOX, A
 Ventilation (ADN) : VE02
 Number of blue cones/lights (ADN) : 2

Rail transport

Classification code (RID) : 2TC
 Limited quantities (RID) : 0
 Excepted quantities (RID) : E0
 Packing instructions (RID) : P200
 Mixed packing provisions (RID) : MP9
 Portable tank and bulk container instructions (RID) : T50(M)
 Portable tank and bulk container special provisions (RID) : TP19
 Tank codes for RID tanks (RID) : PxDH(M)
 Special provisions for RID tanks (RID) : TU38, TE22, TE25, TA4, TT9, TT10, TM6
 Transport category (RID) : 1
 Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW10, CW36
 Hazard identification number (RID) : 268

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VOC Directive (2004/42)

Restrictions on use : None.

Seveso Directive (Disaster Risk Reduction)

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
H2 ACUTE TOXIC — Category 2, all exposure routes — Category 3, inhalation exposure route	50	200

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Ensure all national/local regulations are observed.

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work

Directive 2016/425/EEC on personal protective equipment

Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX)

Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

Austria

Poison Ordinance 2000 : Subject to the Poisons Ordinance 2000

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes:

Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
	ADR - Agreement concerning the International Carriage of Dangerous Goods by Road
	ATE - Acute Toxicity Estimate
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAO	Cargo Aircraft only / Cargo Aircraft only
CAS-No.	Chemical Abstract Service number



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
	CSA - Chemical Safety Assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC	European Inventory of Existing Commercial Chemical Substances
ED	Endocrine disrupting properties
	EINECS - European Inventory of Existing Commercial Chemical Substances
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IOELV	Indicative Occupational Exposure Limit Value
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PCA	Passenger and Cargo Aircraft / Passenger and Cargo Aircraft
PNEC	Predicted No-Effect Concentration
	PPE - Personal Protection Equipment
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
	RMM - Risk Management Measures
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TRGS	Technical Rules for Hazardous Substances



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
STOT-RE	Specific Target Organ Toxicity-Repeated Exposure
STOT-SE	Specific Target Organ Toxicity-Single Exposure
UFI	Unique Formula Identifier
	UN - United Nations
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Training advice : Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.
 Other information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Full text of use descriptors	
ERC2	Formulation into mixture
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC6a	Use of intermediate
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)
ERC6d	Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
ERC7	Use of functional fluid at industrial site
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC19	Manual activities involving hand contact



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of use descriptors	
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC22	Manufacturing and processing of minerals and/or metals at substantially elevated temperature
PROC23	Open processing and transfer operations at substantially elevated temperature
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

The classification complies with
DISCLAIMER OF LIABILITY

- : ATP 12
- : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet (SDS), EU AT

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Formulation of mixtures in pressure receptacles	EIGA113-1	Industrial uses, closed contained conditions	20
Calibration of analysis equipment	EIGA113-1	Industrial uses, closed contained conditions	20
Transfilling in pressure receptacles	EIGA113-1	Industrial uses, closed contained conditions	20
Metal treatment	EIGA113-2	Industrial uses, closed and open conditions	24
Feedstock in chemical processes	EIGA113-2	Industrial uses, closed and open conditions	24
Glass coating	EIGA113-2	Industrial uses, closed and open conditions	24
Water treatment	EIGA113-2	Industrial uses, closed and open conditions	24
Lubrication of rollers in glass manufacture	EIGA113-2	Industrial uses, closed and open conditions	24
Resin curing	EIGA113-2	Industrial uses, closed and open conditions	24
Refilling of refrigeration equipment	EIGA113-3	Professional uses	28



sulphur dioxide

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Wine making	EIGA113-3	Professional uses	28
-------------	-----------	-------------------	-----------

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

1. EIGA113-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA113-1
Revision date: 10/1/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
--------------------------------------	--

Environment	Use descriptors
CS1	ERC2

Worker	Use descriptors
CS2	PROC1
CS3	PROC8b, PROC9

Assessment method	MEASE
-------------------	-------

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: ERC2

ERC2	Formulation into mixture
------	--------------------------

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Not applicable as there is no release to wastewater

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

1.2.2. Control of worker exposure: PROC1

PROC1

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor or outdoor use

1.2.3. Control of worker exposure: PROC8b, PROC9

PROC8b

Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9

Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Concentration of substance in product	≤ 100 %
---------------------------------------	---------

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: ERC2

As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed

1.3.2. Worker exposure: PROC1

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	0.648 mg/m ³	Indoor or outdoor use	0.24

1.3.3. Worker exposure: PROC8b, PROC9

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	1.08 mg/m ³	Indoor or outdoor use	0.4

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

2. EIGA113-2: Industrial uses, closed and open conditions

2.1. Title section

Industrial uses, closed and open conditions

ES Ref.: EIGA113-2
Revision date: 10/1/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within closed or partially closed conditions
--------------------------------------	--

Environment	Use descriptors
CS1	ERC2, ERC4, ERC6a, ERC6b, ERC6d

Worker	Use descriptors
CS2	PROC1
CS3	PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC22, PROC23

Assessment method	MEASE
-------------------	-------

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: ERC2, ERC4, ERC6a, ERC6b, ERC6d

ERC2	Formulation into mixture
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC6a	Use of intermediate
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)
ERC6d	Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures	
No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Conditions and measures related to sewage treatment plant

Not applicable as there is no release to wastewater

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

2.2.2. Control of worker exposure: PROC1

PROC1

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

2.2.3. Control of worker exposure: PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC22, PROC23

PROC2

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC3

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition

PROC4

Chemical production where opportunity for exposure arises

PROC5

Mixing or blending in batch processes

PROC8b

Transfer of substance or mixture (charging and discharging) at dedicated facilities

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC22	Manufacturing and processing of minerals and/or metals at substantially elevated temperature
PROC23	Open processing and transfer operations at substantially elevated temperature

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Local exhaust ventilation - efficiency of at least [%]:	90
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374	Mandatory since the product is corrosive
Wear suitable working clothes	Personal protection measures have to be applied in case of potential exposure only.
Use suitable eye protection. Wear suitable face shield	Personal protection measures have to be applied in case of potential exposure only.
Face mask with an ABEK1 filter offering an assigned protection factor of 30	Personal protection measures have to be applied in case of potential exposure only.

Other conditions affecting workers exposure	
Indoor or outdoor use	

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: ERC2, ERC4, ERC6a, ERC6b, ERC6d

As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

2.3.2. Worker exposure: PROC1

2.3.3. Worker exposure: PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC22, PROC23

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	1.08 mg/m ³	Indoor or outdoor use, With LEV90%	0.4

2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

2.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

3. EIGA113-3: Professional uses

3.1. Title section

Professional uses

ES Ref.: EIGA113-3
Revision date: 10/1/2016

Processes, tasks, activities covered	Professional uses, including transfer of product in non-industrial settings
--------------------------------------	---

Environment

Use descriptors

CS1	ERC6a, ERC7
-----	-------------

Worker

Use descriptors

CS2	PROC8b, PROC9
CS3	PROC19

Assessment method	MEASE
-------------------	-------

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: ERC6a, ERC7

ERC6a	Use of intermediate
ERC7	Use of functional fluid at industrial site

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Regional use tonnage:	≤ 80000 t/yr
Emission Days (days/year)	365

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
No emissions to water. In case of emissions to water, pH impact on the receiving water should be avoided, e.g. by neutralizing the effluent	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Not applicable as there is no release to wastewater	
---	--

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

3.2.2. Control of worker exposure: PROC8b, PROC9

PROC8b

Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC9

Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

Drain down and flush system prior to equipment break-in or maintenance.

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374

Mandatory since the product is corrosive

Wear suitable working clothes. Chemical resistant safety shoes

Personal protection measures have to be applied in case of potential exposure only.

Use suitable eye protection. Wear suitable face shield

Personal protection measures have to be applied in case of potential exposure only.

Other conditions affecting workers exposure

Indoor or outdoor use

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

3.2.3. Control of worker exposure: PROC19

PROC19	Manual activities involving hand contact
--------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 15 min/day

Technical and organisational conditions and measures	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374	Mandatory since the product is corrosive
Wear suitable working clothes. Chemical resistant safety shoes	Personal protection measures have to be applied in case of potential exposure only.
Use suitable eye protection. Wear suitable face shield	Personal protection measures have to be applied in case of potential exposure only.
Face mask with an ABEK1 filter offering an assigned protection factor of 30	

Other conditions affecting workers exposure	
Indoor or outdoor use	

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: ERC6a, ERC7

As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed

3.3.2. Worker exposure: PROC8b, PROC9

sulphur dioxide

Annex to the safety data sheet: Exposure scenario

Reference number: EIGA113 CAS-No.: 7446-09-5 Product form: Substance Physical state: Gas

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	2.16 mg/m ³	Indoor or outdoor use, With LEV90%, With RPE95%	0.8

3.3.3. Worker exposure: PROC19

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Dermal - Acute - systemic effects		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario	
Acute - Local - Inhalation	2.16 mg/m ³	Indoor or outdoor use, With LEV90%, With RPE95%	0.8

3.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

3.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
------------------------	---

3.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : www.ebrc.de/mease.html
-------------------	---

End of document