

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

1 / 28

SECTION 1: Identification of the substance / mixture and of the company / undertaking**1.1 Product identifier**

Product name: C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Trade name: 16M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet**Supplier**

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

F+; R12 Repr. 1; R61 Xn; R20 Xn; R48/20

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Compressed gas	H280: Contains gas under pressure; may explode if heated.

Health Hazards

Toxic to reproduction	Category 1A	H360D: May damage the unborn child.
-----------------------	-------------	-------------------------------------

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

2 / 28

2.2 Label Elements

Contains: Carbon monoxide



Signal Words: Danger

Hazard Statement(s):
 H220: Extremely flammable gas.
 H280: Contains gas under pressure; may explode if heated.
 H360D: May damage the unborn child.

Precautionary Statement

Prevention:
 P202: Do not handle until all safety precautions have been read and understood.
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:
 P308+P313: IF exposed or concerned: Get medical advice / attention.
 P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381: Eliminate all ignition sources if safe to do so.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

Restricted to professional users.

2.3 Other hazards: None.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	Notes
Butane	C4H10	0,2000%	106-97-8	203-448-7	01-2119474691-32	#
pentane	C5H12	0,0500%	109-66-0	203-692-4	01-2119459286-30	#
n-hexane	C6H14	0,0600%	110-54-3	203-777-6	01-2119480412-44	#
Propene	C3H6	0,5000%	115-07-1	204-062-1	01-2119447103-50	
Carbon dioxide	CO2	1%	124-38-9	204-696-9	Listed in Annex IV / V of Regulation (EC) No	#

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

3 / 28

					1907 / 2006 (REACH), exempted from registration.	
Hydrogen	H2	1%	1333-74-0	215-605-7	Listed in Annex IV / V of Regulation (EC) No 1907 / 2006 (REACH), exempted from registration.	
Carbon monoxide	CO	0,5000%	630-08-0	211-128-3	01-2119480165-39	#
Methane	CH4	86,4400%	74-82-8	200-812-7	01-2119474442-39	
Ethane	C2H6	2,5000%	74-84-0	200-814-8	01-2119486765-21	
Ethylene	C2H4	0,5000%	74-85-1	200-815-3	01-2119462827-27	
Propane	C3H8	1%	74-98-6	200-827-9	01-2119486944-21	#
Helium	He	0,5000%	7440-59-7	231-168-5	Listed in Annex IV / V of Regulation (EC) No 1907 / 2006 (REACH), exempted from registration.	
Isobutane	C4H10	0,2000%	75-28-5	200-857-2	01-2119485395-27	#
Nitrogen	N2	5%	7727-37-9	231-783-9	Listed in Annex IV / V of Regulation (EC) No 1907 / 2006 (REACH), exempted from registration.	
Oxygen	O2	0,5000%	7782-44-7	231-956-9	Listed in Annex IV / V of Regulation (EC) No 1907 / 2006 (REACH), exempted from registration.	
isopentane; 2- methylbutane	C5H12	0,0500%	78-78-4	201-142-8	01-2119475602-38	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements.

All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

4 / 28

Classification

Chemical name	Classification		Notes
Butane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
pentane	DSD:	F+; R12 Xn; R65 R66 R67 N; R51 / 53	
	CLP:	Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 2;H411, Flam. Liq. 1;H224	Note C
n-hexane	DSD:	F; R11 Repr. 3; R62 Xi; R38 Xn; R65, R48 / 20 R67 N; R51 / 53	
	CLP:	Flam. Liq. 2;H225, Repr. 2;H361f, STOT RE 2;H373, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411	
Propene	DSD:	F+; R12	
	CLP:	Press. Gas Liquef. Gas;H280, Flam. Gas 1;H220	
Carbon dioxide	DSD:	none	
	CLP:	Press. Gas Liquef. Gas;H280	
Hydrogen	DSD:	F+; R12	
	CLP:	Press. Gas Compr. Gas;H280, Flam. Gas 1;H220	Note U
Carbon monoxide	DSD:	Repr. 1; R61 T; R23, R48 / 23 F+; R12	
	CLP:	Repr. 1A;H360D, Acute Tox. 3;H331, Flam. Gas 1;H220, Press. Gas Compr. Gas;H280, STOT RE 1;H372	
Methane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Compr. Gas;H280	Note U
Ethane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Ethylene	DSD:	F+; R12 R67	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280, STOT SE 3;H336	
Propane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Helium	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	
Isobutane	DSD:	F+; R12	
	CLP:	Press. Gas Liquef. Gas;H280, Flam. Gas 1;H220	
Nitrogen	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	
Oxygen	DSD:	O; R8	
	CLP:	Press. Gas Compr. Gas;H280, Oxid. Gas 1;H270	

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

5 / 28

isopentane; 2-methylbutane	DSD:	F+; R12 Xn; R65 R66 R67 N; R51 / 53	
	CLP:	Flam. Liq. 1;H224, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 2;H411	

DSD: Directive 67 / 548 / EEC.

CLP: Regulation No. 1272 / 2008.

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

The full text for all R-phrases and H-statements is displayed in section 16.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Low concentrations of CO2 cause increased respiration and headache.

Eye contact: Adverse effects not expected from this product.

Skin Contact: Adverse effects not expected from this product.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SAFETY DATA SHEET

C₅H₁₂ 0,05 %; C₅H₁₂ 0,05 %; C₆H₁₄ 0,06 %; C₄H₁₀ 0,2 %; C₄H₁₀ 0,2 %; C₃H₆ 0,5 %; CO 0,5 %; C₂H₄ 0,5 %; He 0,5 %; O₂ 0,5 %; CO₂ 1 %; H₂ 1 %; C₃H₈ 1 %; C₂H₆ 2,5 %; N₂ 5 %; CH₄ 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

6 / 28

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide.

5.2 Special hazards arising from the substance or mixture: Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. Eliminate all ignition sources if safe to do so. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections: Refer to sections 8 and 13.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

7/28

SECTION 7: Handling and storage:**7.1 Precautions for safe handling:**

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use only non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local / regional / national / international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

8 / 28

SECTION 8: Exposure controls / personal protection
8.1 Control Parameters
Occupational Exposure Limits

Chemical name	type	Exposure Limit Values		Source
Carbon dioxide	TWA	5.000 ppm	9.000 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	5.000 ppm	9.000 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	10.000 ppm	18.000 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Propane	MAK	1.000 ppm	1.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	2.000 ppm	3.600 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Carbon monoxide	MAK STEL	60 ppm	66 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	30 ppm	33 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Butane	MAK CEIL	1.600 ppm	3.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Isobutane	MAK CEIL	1.600 ppm	3.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
n-hexane	TWA	20 ppm	72 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	20 ppm	72 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK STEL	80 ppm	288 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
pentane	TWA	1.000 ppm	3.000 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	600 ppm	1.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	1.200 ppm	3.600 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
isopentane; 2-methylbutane	TWA	1.000 ppm	3.000 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK CEIL	1.200 ppm	3.600 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

9/28

	MAK	600 ppm	1.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
--	-----	---------	----------------------------	---

DNEL-Values

Critical component	type	Value	Remarks
pentane	Worker - inhalative, long-term - systemic	3000 mg/m ³	-
	Worker - dermal, long-term - systemic	432 mg/kg bw/day	-
n-hexane	Worker - inhalative, long-term - systemic	75 mg/m ³	-
	Worker - dermal, long-term - systemic	11 mg/kg bw/day	-
Propene	Worker - inhalative, short-term - local	860 mg/m ³	-
	Worker - inhalative, short-term - systemic	860 mg/m ³	-
Carbon monoxide	Worker - inhalative, long-term - systemic	23 mg/m ³	-
	Worker - inhalative, short-term - systemic	117 mg/m ³	-
	Worker - inhalative, long-term - local	23 mg/m ³	-
	Worker - inhalative, short-term - local	117 mg/m ³	-
Ethylene	Worker - inhalative, short-term - local	230 mg/m ³	-
	Worker - inhalative, short-term - systemic	230 mg/m ³	-
isopentane; 2-methylbutane	Worker - inhalative, long-term - systemic	3000 mg/m ³	-
	Worker - dermal, long-term - systemic	432 mg/kg bw/day	-

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

10/28

PNEC-Values

Critical component	type	Value	Remarks
pentane	Aquatic (freshwater)	230 µg/l	-
	Soil	0,55 mg/kg	-
	Sediment (marine water)	1,2 mg/kg	-
	Sewage treatment plant	3600 µg/l	-
	Sediment (freshwater)	1,2 mg/kg	-
	Aquatic (marine water)	230 µg/l	-
	Aquatic (intermit. releases)	880 µg/l	-
Propene	freshwater	1,38 mg/l	-
	marine water	1,38 mg/l	-
Carbon monoxide			PNEC not available.
Ethylene	Aquatic (freshwater)	1,67 mg/l	-
	Aquatic (marine water)	1,67 mg/l	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.

Eye / face protection:

Wear eye protection to EN 166 when using gases.
Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection:

Wear working gloves while handling containers
Guideline: EN 388 Protective gloves against mechanical risks.

Body protection:

Wear fire / flame resistant / retardant clothing.
Guideline: ISO / TR 2801:2007 Clothing for protection against heat and flame --
General recommendations for selection, care and use of protective clothing.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

11 / 28

Other: Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls: For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Compressed gas
Color:	C4H10: Colorless
	C5H12: Colourless
	C6H14: Colorless
	C3H6: Colorless
	CO2: Colorless
	H2: Colorless
	CO: Colorless
	CH4: Colorless
	C2H6: Colorless
	C2H4: Colorless
	C3H8: Colorless
	He: Colorless
	C4H10: Colorless
	N2: Colorless
	O2: Colorless
	C5H12: Colourless
Odor:	C4H10: Gasoline-like or natural gas odor
	C5H12: Gasoline-like odor
	C6H14: Gasoline-like odor
	C3H6: Odorless
	CO2: Odorless
	H2: Odorless
	CO: Odorless
	CH4: Odorless
	C2H6: Odorless
	C2H4: Faint sweet odor
	C3H8: Odorless
	He: Odorless

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

12 / 28

Odor Threshold:

C4H10: Gasoline-like or natural gas odor

N2: Odorless gas

O2: Odorless

C5H12: Faint

Odor threshold is subjective and is inadequate to warn of over exposure.

pH:

not applicable.

Melting Point:

No data available.

Boiling Point:

No data available.

Sublimation Point:

not applicable.

Critical Temp. (°C):

No data available.

Flash Point:

Not applicable to gases and gas mixtures.

Evaporation Rate:

Not applicable to gases and gas mixtures.

Flammability (solid, gas):

Flammable Gas

Flammability Limit - Upper (%):

not applicable.

Flammability Limit - Lower (%):

not applicable.

Vapor pressure:

No reliable data available.

Vapor density (air=1):

0,63 (calculated) (15 °C)

Relative density:

No data available.

Solubility(ies)**Solubility in Water:**

No data available.

Partition coefficient (n-octanol / water):

Not known.

Autoignition Temperature:

not applicable.

Decomposition Temperature:

Not known.

Viscosity**Kinematic viscosity:**

No data available.

Dynamic viscosity:

No data available.

Explosive properties:

Not applicable.

Oxidizing properties:

not applicable.

9.2 Other information:

None.

SECTION 10: Stability and reactivity**10.1 Reactivity:**

No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

Can form a potentially explosive atmosphere in air. May react violently with oxidants.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

13 / 28

- 10.4 Conditions to avoid:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- 10.5 Incompatible Materials:** Air and oxidizers. For material compatibility see latest version of ISO-11114.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information
--

General information: Carbon monoxide: Has been shown to produce adverse effects to the cardiovascular, central nervous, and reproductive systems in laboratory animals and chronically exposed humans.

11.1 Information on toxicological effects**Acute toxicity - Oral
Product**

Based on available data, the classification criteria are not met.

Component Information

pentane	LD 50 (Rat): > 2.000 mg / kg
---------	------------------------------

n-hexane	LD 50 (Rat): 16 g / kg
----------	------------------------

isopentane; 2-methylbutane	LD 50 (Rat): > 2.000 mg / kg
----------------------------	------------------------------

**Acute toxicity - Dermal
Product**

Based on available data, the classification criteria are not met.

Component Information

n-hexane	LD 50 (Rabbit): > 2.000 mg / kg
----------	---------------------------------

**Acute toxicity - Inhalation
Product**

ATEmix (4 h): > 20000 ppm Based on available data, the classification criteria are not met.

Component Information

pentane	LC 50 (Rat, 4 h): > 25,3 mg / l Remarks: Vapor
---------	--

n-hexane	LC 50 (Rat, 4 h): 73860 ppm Remarks: Vapor
----------	--

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

14 / 28

Propene	LC 50 (Rat, 4 h): 369733 ppm
Carbon monoxide	LC 50 (Rat, 4 h): 1300 ppm LC 50 (Rat, 1 h): 3760 ppm
Ethane	LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key study
Ethylene	LC 50 (Rat, 5 h): > 11.473 mg / m3 Remarks: Inhalation Experimental result, Supporting study
Isobutane	LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key study
isopentane; 2-methylbutane	LC 50 (Rat, 4 h): > 25,3 mg / l Remarks: Vapor

Repeated dose toxicity**Component Information**

Butane	NOAEL (Rat(Female, Male), Inhalation, >= 42 d): 16.000 ppm(m) Inhalation Experimental result, Key study
pentane	NOAEL (Rat(Female, Male), Inhalation): 20.000 mg / m3
Propene	NOAEL (Rat(Female, Male), Inhalation, 1 - 20 d): 10.000 ppm(m) Inhalation Experimental result, Key study
Carbon monoxide	LOAEL (Rat(Female), Inhalation, 72 Weeks): 200 ppm(m) Inhalation Experimental result, Key study LOAEC (Rat, Inhalation): 200 ppm (Target Organ(s): Respiratory system)
Methane	NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation Read-across based on grouping of substances (category approach), Key study
Ethane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4.000 ppm(m) Inhalation Experimental result, Key study NOAEC (Rat, Inhalation): 19678 mg / m3
Ethylene	LOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 300 ppm(m) Inhalation Experimental result, Key study LOAEC (Rat): 300 ppm May cause central nervous system depression.
Propane	LOAEL (Rat(Female, Male), Inhalation): 21.641 mg / m3 Inhalation Experimental result, Key study
Isobutane	NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation Read-across based on grouping of substances (category approach), Key study
isopentane; 2-methylbutane	NOAEL (Rat(Female, Male), Inhalation): 20.000 mg / m3 NOAEL (Rat, Inhalation): 30 mg / l

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

15 / 28

Skin Corrosion / Irritation**Product**

Based on available data, the classification criteria are not met.

Component Information

pentane

in vivo (Rabbit): Not classified as an Irritant

Carbon monoxide

Not classified as an irritant.

isopentane; 2-methylbutane

in vivo (Rabbit): Not classified as an Irritant

Serious Eye Damage / Eye Irritation**Product**

Based on available data, the classification criteria are not met.

Component Information

pentane

in vivo (Rabbit, 48 hrs): Not irritatingOECD GHS

n-hexane

in vivo (Rabbit, 24 - 72 hrs): Not irritatingEU

Carbon monoxide

Not classified as an irritant.

Ethane

Not irritating

isopentane; 2-methylbutane

in vivo (Rabbit, 24 hrs): Not irritatingOECD GHS

Respiratory or Skin Sensitization**Product**

Based on available data, the classification criteria are not met.

Component Information

Carbon monoxide

No known effects from this product.

Germ Cell Mutagenicity**Product**

Based on available data, the classification criteria are not met.

Component Information

Carbon monoxide

There is no evidence of mutagenic potential.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

16 / 28

In vitro**Component Information**

Methane

Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome Aberration Test)): Negative.

Ethane

Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Negative.

In vivo**Component Information**

Methane

Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Ethane

Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Carcinogenicity**Product**

Based on available data, the classification criteria are not met.

Component Information

Carbon monoxide

No evidence of carcinogenic effects.

Ethylene

Rat
NOAEC: 3.003 ppm**Reproductive toxicity****Product**

May damage fertility or the unborn child.

Component Information

Carbon monoxide

May damage fertility or the unborn child.

Reproductive toxicity (Fertility)**Component Information**

n-hexane

LC50: 5.000 ppm

Carbon monoxide

NOAEC (embryotoxicity): 65 ppm

Methane

Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 9.000 ppm
 Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 3.000 ppm

Ethylene

Rat (OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)) NOAEC: 5.000 ppm

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

17 / 28

Developmental toxicity (Teratogenicity)**Component Information**

Carbon monoxide LOAEC: 125 ppm

Methane Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
NOAEC: 9.000 ppm

Ethylene Rat
NOAEC: 5.000 ppm

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Component Information

Carbon monoxide Route of Exposure: Inhalation
Target Organ(s): Blood
Causes damage to red blood cells (haemolytic poison). Carbon monoxide binds reversibly to haemoglobin (Hb) to form carboxyhaemoglobin (CoHb), reducing the capacity of the blood to transport oxygen.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Component Information

Carbon monoxide Route of Exposure: Inhalation
Target Organ(s): Heart
Risk of serious health injuries in case of long term exposure.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity**Acute toxicity**

Product No ecological damage caused by this product.

Acute toxicity - Fish**Component Information**

Butane LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study

pentane LC 50 (Oncorhynchus mykiss, 96 h): 4,26 mg/l (Static renewal) Remarks: experimental result

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

18/28

n-hexane	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,101 - 2,981 mg/l (Flow through) Remarks: Mortality
Propene	LC 50 (Various, 96 h): 51,7 mg/l Remarks: QSAR QSAR, Key study
Carbon monoxide	LC 50 (Fish (no species mentioned)): 672,6 mg/l Remarks: QSAR QSAR, Supporting study
Methane	LC 50 (Various, 96 h): 27,98 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Ethane	LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study LC50 (Fish, 96 h): 91,4 mg/l
Ethylene	LC 50 (Various, 96 h): 126,012 mg/l Remarks: QSAR QSAR, Supporting study
Propane	LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Isobutane	LC 50 (Various, 96 h): 27,98 mg/l (QSAR) Remarks: QSAR QSAR, Key study
isopentane; 2-methylbutane	LC 50 (Oncorhynchus mykiss, 96 h): 4,26 mg/l (Static renewal) Remarks: interpreted LC 50 (Rainbow trout (Oncorhynchus mykiss), 96 h): 4,26 mg/l

Acute toxicity - Aquatic Invertebrates**Component Information**

Butane	LC 50 (Daphnid, 48 h): 14,22 mg/l (QSAR) Remarks: QSAR QSAR, Key study LC50 (Water flea (Daphnia magna), 48 h): 14,2 mg/l
pentane	EC 50 (Water flea (Daphnia magna), 48 h): 2.7 mmol / m ³
n-hexane	LC 50 (Water flea (Daphnia magna), 48 h): 45 mmol / m ³
Propene	LC 50 (Daphnia sp., 48 h): 28,2 mg/l Remarks: QSAR QSAR, Key study
Carbon monoxide	LC 50 (48 h): 307,5 mg/l Remarks: QSAR QSAR, Supporting study
Methane	LC 50 (Daphnid, 48 h): 27,14 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Ethane	LC 50 (Daphnid, 48 h): 16,33 mg/l (QSAR) Remarks: QSAR QSAR, Key study EC50 (Water flea (Daphnia magna), 48 h): 46,6 mg/l
Ethylene	LC 50 (Daphnia sp., 48 h): 62,482 mg/l Remarks: QSAR QSAR, Supporting study
Propane	LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study
Isobutane	LC 50 (Daphnid, 48 h): 14,22 mg/l (QSAR) Remarks: QSAR QSAR, Key study

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

19/28

isopentane; 2-methylbutane

EC 50 (Water flea (Daphnia magna)): 2,3 mg/l

**Toxicity to microorganisms
Component Information**

Methane

EC 50 (Alga, 96 h): 19,37 mg/l Not harmful to microorganisms

Ethane

EC50 (Alga, 72 h): 16,5 mg/l

Propane

EC50 (Alga, 72 h): 11,9 mg/l

**Chronic Toxicity - Fish
Component Information**

Propene

NOEC (Various (Freshwater), 30 Days): 51,7 mg/l

**Chronic Toxicity - Aquatic Invertebrates
Component Information**

Propene

LC50 (Water flea (Daphnia magna), 16 d): 3,1 mg/l

**Toxicity to Aquatic Plants
Component Information**

Butane

LC50 (Alga, 72 h): 7,7 mg/l

pentane

EC 50 (Green algae (Selenastrum capricornutum), 72 h): 10,7 mg/l

NOEC (Green algae (Selenastrum capricornutum), 72 h): 2,04 mg/l

Propene

EC 50 (Aquatic plants, 96 h): 12,1 mg/l

NOEC (Aquatic plants, 96 h): 4,5 mg/l

Ethylene

EbC50 (Algae (Chlorella vulgaris), 72 h): 40,5 mg/l (OECD Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test))

isopentane; 2-methylbutane

NOEC (Algae (Pseudokirchneriella subcapitata), 72 h): 7,51 mg/l

EC 50 (Algae (Pseudokirchneriella subcapitata), 72 h): 10,7 mg/l

**12.2 Persistence and Degradability
Product**

Not applicable to gases and gas mixtures..

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

20/28

Component Information

Carbon monoxide Will not undergo hydrolysis.

Biodegradation**Component Information**

Carbon monoxide Not readily biodegradable. Inorganic compound.

Methane 100 %

Photodegradation**Component Information**

pentane Non-significant photolysis

Stability in water**Component Information**

pentane 87 %Non-significant hydrolysis

12.3 Bioaccumulative Potential**Product**

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

Component Information

Carbon monoxide Because of the low log Kow, accumulation in organisms is not expected.

12.4 Mobility in Soil**Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

Component Information

pentane Henry's Law Constant: 7.010 MPa (25 °C)

Propene Henry's Law Constant: 1.099 MPa (25 °C)

Carbon monoxide Because of its high volatility, the product is unlikely to cause ground or water pollution.

Methane Henry's Law Constant: 3.690 MPa (25 °C)

Ethylene Henry's Law Constant: 1.279 MPa (25 °C)

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 %;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

21 / 28

isopentane; 2-methylbutane

Henry's Law Constant: 7.851 MPa

**12.5 Results of PBT and vPvB
assessment
Product**

Not classified as PBT or vPvB.

12.6 Other Adverse Effects:

Global Warming Potential

Global warming potential: 19,7

Contains greenhouse gas(es). When discharged in large quantities may contribute to the greenhouse effect.

Component Information

Butane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 4 100-yr

pentane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 5 100-yr

Methane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 25 100-yr

Ethane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 6 100-yr

Propane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 3 100-yr

Isobutane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 3 100-yr

isopentane; 2-methylbutane

EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 5 100-yr

Carbon dioxide

UN / IPCC. Greenhouse Gas Global Warming Potentials (IPCC Fourth Assessment Report, Climate Change, Table TS.2
- Global warming potential: 1 100-yr

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

22 / 28

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes
Container:

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information

ADR

14.1 UN Number:	UN 1954
14.2 UN Proper Shipping Name:	COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Carbon Monoxide)
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	23
Tunnel restriction code:	(B / D)
14.4 Packing Group:	–
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	–

RID

14.1 UN Number:	UN 1954
14.2 UN Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Carbon Monoxide)
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
14.4 Packing Group:	–
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	–

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

23 / 28

IMDG

14.1 UN Number: UN 1954
 14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Carbon Monoxide)
 14.3 Transport Hazard Class(es)
 Class: 2.1
 Label(s): 2.1
 EmS No.: F-D, S-U
 14.3 Packing Group: –
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: –

IATA

14.1 UN Number: UN 1954
 14.2 Proper Shipping Name: Compressed gas, flammable, n.o.s.(Methane, Carbon Monoxide)
 14.3 Transport Hazard Class(es):
 Class: 2.1
 Label(s): 2.1
 14.4 Packing Group: –
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: –
 Other information
 Passenger and cargo aircraft: Forbidden.
 Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL73 / 78 and the IBC Code: not applicable

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture:**EU Regulations**

Regulation (EC) No. 1907 / 2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
pentane	109-66-0	- <0,1%

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

24 / 28

n-hexane	110-54-3	- <0,1%
Propene	115-07-1	0,1 - 1,0%
Hydrogen	1333-74-0	1,0 - 10%
Carbon monoxide	630-08-0	0,1 - 1,0%
Methane	74-82-8	80 - 90%
Ethylene	74-85-1	0,1 - 1,0%
Propane	74-98-6	1,0 - 10%
isopentane; 2-methylbutane	78-78-4	- <0,1%

Directive 92 / 85 / EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

Chemical name	CAS-No.	Concentration
Carbon monoxide	630-08-0	0,1 - 1,0%
pentane	109-66-0	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%

Directive 96 / 61 / EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Carbon dioxide	124-38-9	1,0 - 10%
Carbon monoxide	630-08-0	0,1 - 1,0%

Directive 96 / 82 / EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	80 - 90%
Hydrogen	1333-74-0	1,0 - 10%
Ethane	74-84-0	1,0 - 10%
Propane	74-98-6	1,0 - 10%

SAFETY DATA SHEET

C₅H₁₂ 0,05 %; C₅H₁₂ 0,05 %; C₆H₁₄ 0,06 %; C₄H₁₀ 0,2 %; C₄H₁₀ 0,2 %; C₃H₆ 0,5 %; CO 0,5 %; C₂H₄ 0,5 %; He 0,5 %; O₂ 0,5 %; CO₂ 1 %; H₂ 1 %; C₃H₈ 1 %; C₂H₆ 2,5 %; N₂ 5 %; CH₄ 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

25 / 28

Butane	106-97-8	0,1 - 1,0%
Propene	115-07-1	0,1 - 1,0%
Carbon monoxide	630-08-0	0,1 - 1,0%
Ethylene	74-85-1	0,1 - 1,0%
Isobutane	75-28-5	0,1 - 1,0%
Oxygen	7782-44-7	0,1 - 1,0%
pentane	109-66-0	0 - <0,1%
n-hexane	110-54-3	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%

Directive 98 / 24 / EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	1,0 - 10%
Butane	106-97-8	0,1 - 1,0%
Propene	115-07-1	0,1 - 1,0%
Carbon monoxide	630-08-0	0,1 - 1,0%
Ethylene	74-85-1	0,1 - 1,0%
Oxygen	7782-44-7	0,1 - 1,0%
pentane	109-66-0	0 - <0,1%
n-hexane	110-54-3	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%

National Regulations

Council Directive 89 / 391 / EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89 / 686 / EEC on personal protective equipment Directive 94 / 9 / EC on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333 / 2008 and (EU) No. 231 / 2012 and are labelled as such may be used as food additives.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

26 / 28

This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information**Revision Information:**

Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances

<http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

27 / 28

Wording of the R-phrases and H-statements in section 2 and 3

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H270	May cause or intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
R8	Contact with combustible material may cause fire.
R11	Highly flammable.
R12	Extremely flammable.
R20	Harmful by inhalation.
R23	Toxic by inhalation.
R38	Irritating to skin.
R48 / 20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R48 / 23	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
R51 / 53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R61	May cause harm to the unborn child.
R62	Possible risk of impaired fertility.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Training information: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/ 2008 as amended.

Flam. Gas 1, H220

Repr. 1A, H360D

Press. Gas Compr. Gas, H280

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national / local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C6H14 0,06 %;C4H10 0,2 %;C4H10 0,2 %;C3H6 0,5 %;CO 0,5 %;C2H4 0,5 %;He 0,5 %;O2 0,5 %;CO2 1 %;H2 1 % ;C3H8 1 %;C2H6 2,5 %;N2 5 %;CH4 86,44 %

Issue Date: 26.01.2017

Version: 1.0

SDS No.: 000010037914

Last revised date: 26.01.2017

28/28

Last revised date: 26.01.2017

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.