

SAFETY DATA SHEET CH4 10 %; Ar 90 %

 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 1/15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: CH4 10 %;Ar 90 %

Trade name: Gasart 269 Argon-Methan 90/10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas GmbH Telephone: +43 50 4273

Carl-von-Linde-Platz 1 A-4651 Stadl-Paura

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information

Center: +43 1 406 43 43

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas Category 1 H220: Extremely flammable gas.

Gases under pressure Compressed gas H280: Contains gas under pressure; may explode if

heated.

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.



SAFETY DATA SHEET CH4 10 %; Ar 90 %

 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 2/15

Precautionary Statements

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

2.3 Other hazards: None.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical	Concentration	CAS-No.	EC No.	REACH Registration	Notes
	formula				No.	
Methane	CH4	10%	74-82-8	200-812-7	01-2119474442-39	
Argon	Ar	90%	7440-37-1	231-147-0	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

Classification

Chemical name	Classification		Notes
Methane	CLP:	, Flam. Gas 1;H220, Press. Gas Compr. Gas;H280	Note U
Argon	CLP:	, Press. Gas Compr. Gas;H280	

CLP: Regulation No. 1272/2008.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

The full text for all H-statements is displayed in section 16.

^{##} This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.





 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 3/15

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Adverse effects not expected from this product.

Skin Contact: Adverse effects not expected from this product.

Ingestion: Ingestion is not considered a potential route of exposure.

 ${\bf 4.2\,Most\,important\,symptoms\,and}$

effects, both acute and

delayed:

Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water. Dry powder. Foam.

Unsuitable extinguishing

media:

Carbon Dioxide.

5.2 Special hazards arising from the

substance or mixture:

Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting

procedures:

In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the

fire. Isolate the source of the fire or let it burn out.





 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 4/15

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections:

Refer to sections 8 and 13.



SAFETY DATA SHEET CH4 10 %: Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 12.09.2018 Last revised date:

5/15

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.



SAFETY DATA SHEET CH4 10 %; Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 Last revised date: 12.09.2018 6/15

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas

treatment. Do not eat, drink or smoke when using the product.

Eye/face protection: Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Wear working gloves while handling containers

Guideline: EN 388 Protective gloves against mechanical risks.

Body protection: Wear fire resistant or flame retardant clothing.

Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.

Other: Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.





Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 Last revised date: 12.09.2018 7/15

Environmental exposure

For waste disposal, see section 13 of the SDS.

controls:

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Gas

Form: Compressed gas Color: CH4: Colorless Ar: Colorless

CH4: Odorless Odor:

Ar: Odorless

Odor Threshold: Odor threshold is subjective and is inadequate to warn of over

exposure.

not applicable. pH: **Melting Point:** No data available. **Boiling Point:** No data available. not applicable. **Sublimation Point:** Critical Temp. (°C): No data available.

Flash Point: Not applicable to gases and gas mixtures. Not applicable to gases and gas mixtures. **Evaporation Rate:**

Flammability (solid, gas): Flammable Gas Flammability Limit - Upper (%): not applicable. Flammability Limit - Lower (%): not applicable.

No reliable data available. Vapor pressure: Vapor density (air=1): 1,32 (calculated) (15 °C)

No data available. Relative density:

Solubility(ies)

Solubility in Water: No data available.

Partition coefficient (n-octanol/water): Not known. **Autoignition Temperature:** not applicable. **Decomposition Temperature:** Not known.

Viscosity

No data available. Kinematic viscosity: Dynamic viscosity: No data available. Not applicable. **Explosive properties:** not applicable. Oxidizing properties:

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined

spaces, particularly at or below ground level.





 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 8/15

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of hazardous Can form a potentially explosive atmosphere in air. May react violently with

reactions: oxidants.

10.4 Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

10.5 Incompatible Materials: Air and oxidizers. For material compatibility see latest version of ISO-11114.

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral

Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

Product Based on available data, the classification criteria are not met.

Component Information

Methane LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key

study

Repeated dose toxicity
Component Information

Methane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation

Read-across based on grouping of substances (category approach), Key study

Skin Corrosion/Irritation

Product Based on available data, the classification criteria are not met.





 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 9/15

Serious Eye Damage/Eye Irritation

Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization

Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product Based on available data, the classification criteria are not met.

In vitro

Component Information

Methane Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome

Aberration Test)): Negative.

In vivo

Component Information

Methane Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity (Fertility)
Component Information

Methane Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity

Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity

Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 3.000 ppm

Developmental toxicity (Teratogenicity)

Component Information

Methane Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study

with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..



SAFETY DATA SHEET CH4 10 %; Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 12.09.2018 Last revised date:

10/15

SECTION 12: Ecological information

General information: not applicable

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

Acute toxicity - Fish **Component Information**

> Methane LC 50 (Various, 96 h): 49,9 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates

Component Information

Methane LC 50 (Daphnia sp., 48 h): 69,43 mg/I Remarks: QSAR QSAR, Key study

Toxicity to microorganisms Component Information

> Methane EC 50 (Alga, 96 h): 19,37 mg/l Not harmful to microorganisms

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation

Component Information

Methane 100 % (385,5 h) Detected in water. Experimental result, Key study

12.3 Bioaccumulative potential

The subject product is expected to biodegrade and is not expected to persist for **Product**

long periods in an aquatic environment.

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water

pollution.

Component Information

Methane Henry's Law Constant: 3.690 MPa (25 °C)

12.5 Results of PBT and vPvB

assessment

Not classified as PBT or vPvB. Product

SDS_AT - 000010022024



SAFETY DATA SHEET CH4 10 %; Ar 90 %

 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 11/15

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 1,1

Contains greenhouse gas(es). When discharged in large quantities may contribute

to the greenhouse effect.

Component Information

Methane

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Do not discharge into any place where its accumulation could be dangerous.

Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared

through a suitable burner with flash back arrestor.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing

dangerous substances.

SECTION 14: Transport information

ADR

14.1 UN Number: UN 1954

14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Argon)

14.3 Transport Hazard Class(es)

 Class:
 2

 Label(s):
 2.1

 Hazard No. (ADR):
 23

 Tunnel restriction code:
 (B/D)

14.4 Packing Group:

14.5 Environmental hazards: not applicable

14.6 Special precautions for user: -



SAFETY DATA SHEET CH4 10 %; Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 12.09.2018 Last revised date:

12/15

RID

14.1 UN Number: UN 1954

14.2 UN Proper Shipping Name COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Argon)

14.3 Transport Hazard Class(es)

2 Class: Label(s): 2.1 14.4 Packing Group:

14.5 Environmental hazards: not applicable

14.6 Special precautions for user:

IMDG

14.1 UN Number: UN 1954

14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Argon)

14.3 Transport Hazard Class(es)

Class: 2.1 Label(s): 2.1 F-D, S-U EmS No.:

14.3 Packing Group:

14.5 Environmental hazards: not applicable

14.6 Special precautions for user:

IATA

14.1 UN Number: UN 1954

14.2 Proper Shipping Name: Compressed gas, flammable, n.o.s. (Methane, Argon)

14.3 Transport Hazard Class(es):

Class: 2.1 Label(s): 2.1 14.4 Packing Group:

14.5 Environmental hazards: not applicable

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Forbidden. Forbidden. Cargo aircraft only:

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from

> the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure

adequate air ventilation.





 Issue Date:
 16.09.2013
 Version: 1.2
 SDS No.: 000010022024

 Last revised date:
 12.09.2018
 13/15

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	10 - 20%

Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	10 - 20%

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	10 - 20%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 94/9/EC on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.



SAFETY DATA SHEET CH4 10 %; Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 Last revised date: 12.09.2018 14/15

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling

guide.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and

oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database

Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental

Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

Training information: Users of breathing apparatus must be trained. Ensure operators understand the

flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1, H220

Press. Gas Compr. Gas, H280

Other information:Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no

liability for injury or damage resulting from its use can be accepted.

Last revised date: 12.09.2018

Disclaimer: This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.



SAFETY DATA SHEET CH4 10 %; Ar 90 %

Issue Date: 16.09.2013 Version: 1.2 SDS No.: 000010022024 Last revised date: 12.09.2018

15/15