



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 1/16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: C3H8 13 %;CH4 87 %
Other Name: G21 (EN 437)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use. Under controlled conditions.
Uses advised against Contact supplier for more information on uses. Uses other than those listed above are not supported.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas GmbH
 Carl-von-Linde-Platz 1
 A-4651 Stadl-Paura

Telephone: +43 50 4273

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Compressed gas	H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 2/16



Signal Word: Danger

Hazard Statement(s): H220: Extremely flammable gas.
 H280: Contains gas under pressure; may explode if heated.

Precautionary Statements
 General

None.

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381: In case of leakage, eliminate all ignition sources.

Storage:

P403: Store in a well-ventilated place.

Disposal

None.

2.3 Other hazards

None.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Methane	CH ₄	87%	74-82-8	01-2119474442-39	-	
Propane	C ₃ H ₈	13%	74-98-6	01-2119486944-21	-	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.
 # # This substance has workplace exposure limit(s).
 PBT: persistent, bioaccumulative and toxic substance.
 vPvB: very persistent and very bioaccumulative substance.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 3/16

Classification

Chemical name	Classification		Notes
Methane	CLP:	, Flam. Gas 1;H220, Press. Gas Compr. Gas;H280	
Propane	CLP:	, Press. Gas Liquef. Gas;H280, Flam. Gas 1;H220	

CLP: Regulation No. 1272/2008.

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Adverse effects not expected from this product.

Skin Contact: Adverse effects not expected from this product.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water. Dry powder. Foam.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 4/16

Unsuitable extinguishing media: Carbon Dioxide.

5.2 Special hazards arising from the substance or mixture: Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections: Refer to sections 8 and 13.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
5/16

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 6/16

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Propane	MAK	1.000 ppm 1.800 mg/m ³	Austria. MAK List OEL Ordinance (GKV), as ammended (09 2018)
	MAK CEIL	2.000 ppm 3.600 mg/m ³	Austria. MAK List OEL Ordinance (GKV), as ammended (09 2018)

8.2 Exposure controls

Appropriate engineering controls: Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 7/16

Eye/face protection:	Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection	
Hand Protection:	Guideline: EN 388 Protective gloves against mechanical risks. Additional Information: Wear working gloves while handling containers
Body protection:	Wear fire resistant or flame retardant clothing. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Compressed gas
Color:	CH4: Colorless C3H8: Colorless
Odor:	CH4: Odorless C3H8: Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 8/16

pH:	Not applicable.
Melting Point:	No data available.
Boiling Point:	No data available.
Sublimation Point:	Not applicable.
Critical Temp. (°C):	No data available.
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable Gas
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	No reliable data available.
Vapor density (air=1):	0,69 (calculated) (15 °C)
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	No data available.
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

9.2 Other information: None.

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidizers. For material compatibility see latest version of ISO-11114.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 9/16

10.6 Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product Based on available data, the classification criteria are not met.

Component Information
 Methane LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key study

Repeated dose toxicity Component Information
 Methane NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation Read-across based on grouping of substances (category approach), Key study
 Propane LOAEL (Rat(Female, Male), Inhalation): 21.641 mg/m³ Inhalation Experimental result, Key study

Skin Corrosion/Irritation Product Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization Product Based on available data, the classification criteria are not met.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 10/16

Germ Cell Mutagenicity

Product

Based on available data, the classification criteria are not met.

In vitro

Component Information

Methane

Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome Aberration Test)): Negative.

In vivo

Component Information

Methane

Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Carcinogenicity

Product

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product

Based on available data, the classification criteria are not met.

Reproductive toxicity (Fertility)

Component Information

Methane

Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 9.000 ppm
 Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 3.000 ppm

Developmental toxicity (Teratogenicity)

Component Information

Methane

Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 9.000 ppm

Specific Target Organ Toxicity - Single Exposure

Product

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product

Based on available data, the classification criteria are not met.

Aspiration Hazard

Product

Not applicable to gases and gas mixtures..



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 11/16

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity
Product

No ecological damage caused by this product.

Acute toxicity - Fish
Component Information

Methane LC 50 (Various, 96 h): 49,9 mg/l (QSAR) Remarks: QSAR QSAR, Key study
 Propane LC 50 (Various, 96 h): 49,9 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates
Component Information

Methane LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study
 Propane LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study

Toxicity to microorganisms
Component Information

Methane **EC 50 (Alga, 96 h): 8,57 mg/l**

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation
Component Information

Methane 50 % (3,19 d) Detected in water. QSAR, Weight of Evidence study
 Propane 100 % (385,5 h) Detected in water. Experimental result, Key study

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 12/16

12.4 Mobility in soil
Product

Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Results of PBT and vPvB
assessment
Product

Not classified as PBT or vPvB.

12.6 Other adverse effects:

Global Warming Potential

Global warming potential: 18,6
 Contains greenhouse gas(es). When discharged in large quantities may contribute to the greenhouse effect.

Component Information
 Methane

EU. Non-Fluorinated Substance GWPs (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases
 - Global warming potential: 25

Propane

EU. Non-Fluorinated Substance GWPs (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases
 - Global warming potential: 3

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes
Container:

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 13/16

SECTION 14: Transport information

ADR

14.1 UN Number: UN 1954
 14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Propane)
 14.3 Transport Hazard Class(es)
 Class: 2
 Label(s): 2.1
 Hazard No. (ADR): 23
 Tunnel restriction code: (B/D)
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1954
 14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Propane)
 14.3 Transport Hazard Class(es)
 Class: 2
 Label(s): 2.1
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 1954
 14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Propane)
 14.3 Transport Hazard Class(es)
 Class: 2.1
 Label(s): 2.1
 EmS No.: F-D, S-U
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 14/16

IATA

14.1 UN Number: UN 1954
 14.2 Proper Shipping Name: Compressed gas, flammable, n.o.s.(Methane, Propane)
 14.3 Transport Hazard Class(es):
 Class: 2.1
 Label(s): 2.1
 14.4 Packing Group: -
 14.5 Environmental hazards: Not applicable
 14.6 Special precautions for user: -
 Other information
 Passenger and cargo aircraft: Forbidden.
 Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	80 - 90%
Propane	74-98-6	10 - 20%

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Classification	Lower-tier Requirements	Upper-tier Requirements
P2. Flammable gas	10 t	50 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 15/16

Chemical name	CAS-No.	Concentration
Methane	74-82-8	80 - 90%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
 This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
 Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
 European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
 European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
 European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.
 International Programme on Chemical Safety (<http://www.inchem.org/>)
 ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
 Matheson Gas Data Book, 7th Edition.
 National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
 The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
 The European Chemical Industry Council (CEFIC) ERICards.
 United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
 Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
 Substance specific information from suppliers.
 Details given in this document are believed to be correct at the time of publication.



SAFETY DATA SHEET
C3H8 13 %;CH4 87 %

Issue Date: 10.02.2015
 Last revised date: 12.01.2021

Version: 1.1

SDS No.: 000010022666
 16/16

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 as amended.	Classification procedure
Flammable gas, Category 1	On basis of test data
Gases under pressure, Compressed gas	On basis of test data

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Training information: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1, H220
 Press. Gas Compr. Gas, H280

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 12.01.2021

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.