

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		1/33
Last revised date :	27.10.2022		

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Product name: Hydrogen sulphide Trade name: Gasart 482 Schwefelwasserstoff 2.3 Additional identification Chemical name: Hydrogen sulphide Chemical formula: H2S INDEX No. 016-001-00-4 CAS-No. 7783-06-4 231-977-3 EC No. **REACH Registration No.** 01-2119445737-29 1.2 Relevant identified uses of the substance or mixture and uses advised against Industrial and professional use for chemical analysis, calibration, (routine) Identified uses: quality control, laboratory use. Under controlled conditions. Industrial and professional. Perform risk assessment prior to use. Use for electronic component manufacture. Use for metal treatment. Use the gas as odorising agent in another gas (e.g. LPG). Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical processes. Uses advised against Contact supplier for more information on uses. Uses other than those listed above are not supported.Consumer use. 1.3 Details of the supplier of the safety data sheet Supplier Linde Gas GmbH Telephone: +43 50 4273 Carl-von-Linde-Platz 1 A-4651 Stadl-Paura

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number UMCO: +49 89 220 61012 (German), +44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas

Category 1A H220: Extremely flammable gas.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

H١	ydroger	r sul	phide
	Juiogei		pinde

Issue Date:	16.01.2013	Versio	on: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023			2/33
Last revised date :	27.10.2022			
Gases under pressure		Liquefied gas	H280: Contains g	as under pressure; may explode if

heated.

Health Hazards		
Acute toxicity (Inhalation - gas)	Category 2	H330: Fatal if inhaled.
Specific Target Organ Toxicity - Single Exposure Environmental Hazards	Category 3	H335: May cause respiratory irritation.
Acute hazards to the aquatic environment	Category 1	H400: Very toxic to aquatic life.

2.2 Label Elements

Contains:	Hydrogen sulphide
Signal Word:	Danger
Hazard Statement(s):	H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated. H330: Fatal if inhaled. H335: May cause respiratory irritation. H400: Very toxic to aquatic life.
Precautionary Statements General	None.
Prevention:	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260: Do not breathe gas/vapors. P273: Avoid release to the environment.
Response:	P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention. P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381: In case of leakage, eliminate all ignition sources.
Storage:	P403: Store in a well-ventilated place. P405: Store locked up.
Disposal	None.
000010021740	



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sul	phide
--------------	-------

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		3/33
Last revised date :	27.10.2022		

Unknown toxicity - Health Acute toxicity, inhalation, gas	0 %
Unknown toxicity - Environment	
Acute hazards to the aquatic environment	100 %
Chronic hazards to the aquatic environment	100 %
Acute hazards to the aquatic environment	0 %

2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin. Not classified as PBT or vPvB.

Endocrine disrupting properties-Toxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties-Ecotoxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		4/33
Last revised date :	27.10.2022		

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Hydrogen sulphide
INDEX No.:	016-001-00-4
CAS-No.:	7783-06-4
EC No.:	231-977-3
REACH Registration No.:	01-2119445737-29
Purity:	100%
	The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	Gasart 482 Schwefelwasserstoff 2.3

Irade name:

Chemical name	Chemical formula	Concentration	CAS-No.		REACH Registration No.	M-Factor:	Notes
Hydrogen sulphide	H2S	100%	7783-06-4	231-977-3	01- 2119445737- 29	Aquatic Toxicity (Acute): 1	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

This substance is listed as SVHC.PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SECTION 4: First aid measures

General:	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
4.1 Description of first aid measures Inhalation:	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Eye contact:	Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
Skin Contact:	Contact with evaporating liquid may cause frostbite or freezing of skin.
Ingestion:	Ingestion is not considered a potential route of exposure.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		5/33
Last revised date :	27.10.2022		

4.2 Most important symptoms and effects, both acute and delayed:May be fatal if inhaled. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Causes damage to organs.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards:	May be fatal if inhaled. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Causes damage to organs.
Treatment:	Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice/attention. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards:	Heat may cause the containers to explode.		
5.1 Extinguishing media Suitable extinguishing media:	Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam.		
Unsuitable extinguishing media:	Carbon Dioxide.		
5.2 Special hazards arising from the substance or mixture:	Fire or excessive heat may produce hazardous decomposition products. Fire or excessive heat may produce hazardous decomposition products.		
Hazardous Combustion Products:	If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Sulphur dioxide		
5.3 Advice for firefighters			
Special fire-fighting procedures:	In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.		
Special protective equipment for fire-fighters:	Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus. Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)		



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		6/33
Last revised date :	27.10.2022		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open- circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
6.2 Environmental Precautions:	Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.
6.3 Methods and material for containment and cleaning up:	Provide adequate ventilation. Eliminate sources of ignition. Wash contaminated equipment or sites of leaks with copious quantities of water.
6.4 Reference to other sections:	Refer to sections 8 and 13.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		7/33
Last revised date :	27.10.2022		

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an uright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance wit



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		8/33
Last revised date :	27.10.2022		

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Keep away from food, drink and animal feeding stuffs. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Form of exposure	Exposure Limi	t Values	Source
hydrogen sulphide	TWA		5 ppm	7 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	STEL		10 ppm	14 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	MAK CEIL		5 ppm	7 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended (04 2021)
	MAK		5 ppm	7 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001, as amended (04 2021)

Please refer to the latest edition of the appropriate source text and consult an industrial hygienist or similar professional, or local agencies, for further information.

Biological Limit Values

No biological exposure limits noted for the ingredient(s).



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		9/33
Last revised date :	27.10.2022		

DNEL-Values

Critical component	Туре	Value	Remarks
Hydrogen sulphide	Workers - Inhalation, Local, long-term	7 mg/m3	respiratory tract irritation
	Workers - Inhalation, Systemic, short-term	14 mg/m3	-
	Workers - Inhalation, Systemic, long-term	7 mg/m3	Repeated dose toxicity
	Workers - Inhalation, Local, short-term	14 mg/m3	-
	Workers - Eyes, Local effect		Hazard unknown (no further information necessary)

PNEC-Values

Critical component	Туре	Value	Remarks
Hydrogen sulphide	Sewage treatment plant	1,33 mg/l	-
Hydrogen sulphide	Aquatic (freshwater)	0,03 µg/l	-
Hydrogen sulphide	Aquatic (intermit. releases)	0,19 µg/l	-
Hydrogen sulphide	Aquatic (marine water)	0,003 µg/l	-
Hydrogen sulphide	Air	7 mg/m3	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of flammable gases or vapours may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		10/33
Last revised date :	27.10.2022		

Individual protection measures, such as personal protective equipment

General information:	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Eye/face protection:	Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection Hand Protection:	Guideline: EN 388 Protective gloves against mechanical risks. Additional Information: Wear working gloves while handling containers Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro- organisms. Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection:	Wear fire resistant or flame retardant clothing. Keep suitable chemically resistant protective clothing readily available for emergency use. Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame General recommendations for selection, care and use of protective clothing.Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		11/33
Last revised date :	27.10.2022		

Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Obtain special instructions before use. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Appearance

Appearance	
Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Strong odor of rotten eggs
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
Melting Point:	-123 °F/-86 °C Experimental result, Key study
Boiling Point:	-76,4 °F/-60,2 °C
Flammability:	Flammable Gas
Upper/lower limit on flammability or explo	osive limits
Explosive limit - upper:	45,5 %(V) Experimental result, Supporting study
Explosive limit - lower:	3,9 %(V)
Flash Point:	Not applicable to gases and gas mixtures.
Autoignition Temperature:	270 °C Experimental result, Key study
Decomposition Temperature:	When heated to decomp, emits highly toxic fumes of sulfoxides.
pH:	Not applicable
Viscosity	
Dynamic viscosity:	0,013 mPa.s (77 °F/25 °C) Experimental result, Not specified
Kinematic viscosity:	No data available.
Solubility(ies)	
Solubility in Water:	3,98 g/l
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not known.
Dispersion Stability:	No data available.
Vapor pressure:	20.851 hPa (77 °F/25 °C) Experimental result, Key study
Relative density:	0,92
Density:	0,0015 g/cm3 (32 °F/0 °C)
AT 000010021740	

SDS_AT - 000010021749



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		12/33
Last revised date :	27.10.2022		

Relative vapor density:	1,2
Particle characteristics:	Not applicable
9.2 Other information	
Flammability:	Tci: 8,9
Minimum ignition temperature:	518 °F/270 °C
Molecular weight:	34,08 g/mol (H2S)
Critical Temp. (°C):	100,0 °C

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Avoid moisture in the installation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible Materials:	Air and oxidizers. Moisture. For material compatibility see latest version of ISO- 11114. With water causes rapid corrosion of some metals.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Sulphur dioxide

SECTION 11: Toxicological information

General information:	None.
11.1 Information on hazard classes a	s defined in Regulation (EC) No 1272/2008
Acute toxicity - Oral Product	Based on available data, the classification criteria are not met.
Acute toxicity - Dermal Product	Based on available data, the classification criteria are not met.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Hydrogen sulphide					
Issue Date: Revision Date: Last revised date :	16.01.2013 27.09.2023 27.10.2022	Version: 2.1	SDS No.: 000010021749 13/33		
Acute toxicity - Inhalation Product		f inhaled.			
Hydrogen sulphide	LC 50	LC 50 (Rat, 4 h): 356 ppm			
Repeated dose toxicity Hydrogen sulphide		LOAEL (Rat(Female, Male), Inhalation, 90 d): 30,5 ppm(m) Inhalation Experimental result, Key study			
Skin Corrosion/Irritation Product		Based on available data, the classification criteria are not met.			
Serious Eye Damage/Eye Product		on available data, the classification cri	teria are not met.		
Respiratory or Skin Sens Product		Based on available data, the classification criteria are not met.			
Germ Cell Mutagenicity Product	Based	Based on available data, the classification criteria are not met.			
In vitro		Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Negative.			
Carcinogenicity Product	Based	Based on available data, the classification criteria are not met.			
Reproductive toxicity Product	Based	Based on available data, the classification criteria are not met.			
Reproductive toxicity (Fe	Fertili	Fertility: Rat NOAEC: 80 ppm			
Specific Target Organ To. Product	Route	xposure of Exposure: Inhalation s irritation to the respiratory tract May	cause respiratory irritation.		
Specific Target Organ Toxicity - Repeated ExposureProductRoute of Exposure: Inhalation Causes damage to the central nervous system.			n.		



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Hydrogen sulphide				
Issue Date: Revision Date: Last revised date :	16.01.2013 27.09.2023 27.10.2022	Version: 2.1	SDS No.: 000010021749 14/33	
Aspiration Hazard Product	Not ap	pplicable to gases and gas mixtures		
11.2 Information on other ha	zards			
Endocrine disrupting pro Product:	The su endoci Delega	bstance/mixture does not contain com rine disrupting properties according to ated regulation (EU) 2017/2100 or Com 605 at levels of 0.1% or higher.;	REACH Article 57(f) or Commission	
Components: Hydrogen sulphide	The su endoc Deleg	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.;		
Other information Product:		No data available.		
SECTION 12: Ecological info	mation			
General information:	theen	Very toxic to aquatic organisms. Endangering to drinking water. Avoid release to the environment. Product is not allowed to be discharged into ground water or the aquatic environment. Not applicable		
12.1 Toxicity				
Acute toxicity Product		Toxic to aquatic organisms. Very toxic to aquatic life.		
12.2 Persistence and Degrad Product		Not applicable to gases and gas mixtures		
Biodegradation		Inorganic The product is not readily biodegradable.		
12.3 Bioaccumulative potent Product		The substance has no potential for bioaccumulation.		
12.4 Mobility in soil Product	The su	bstance has low mobility in soil.		
12.5 Results of PBT and vPvBassessmentProductNot classified as PBT or vPvB.				



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide	
-------------------	--

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		15/33
Last revised date :	27.10.2022		

Other Ecological Information

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

12.6 Endocrine disrupting properties:

Product:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Components:	
Hydrogen sulphide	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse offects	

12.7 Other adverse effects:

Other hazards	
Product:	No data available.

Other effects:

SECTION 13: Disposal considerations	

13.1 Waste treatment methods

General information:	Must not be discharged to atmosphere. Consult supplier for specific recommendations.	
Disposal methods:	Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.	
European Waste Codes Container:	16 05 04*: Gases in pressure containers (including halons) containing hazardous substances.	



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen su	lphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		16/33
Last revised date :	27.10.2022		

SECTION 14: Transport information

ADR

14.1 UN number or ID number: 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es)	UN 1053 HYDROGEN SULPHIDE
Class:	2
Hazard No. (ADR):	263
	(B/D) -
Limited quantity	None.
14.5 Environmental hazards: 14.6 Special precautions for user:	Environmentally Hazardous
Label(s): Hazard No. (ADR): Tunnel restriction code: 14.4 Packing Group: Limited quantity Excepted quantity 14.5 Environmental hazards:	2.3, 2.1 263 (B/D) - None. None.

RID

14.1 UN number or ID number: 14.2 UN Proper Shipping Name 14.3 Transport Hazard Class(es)	UN 1053 HYDROGEN SULPHIDE
Class:	2
Label(s):	2.3, 2.1
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.
14.5 Environmental hazards:	Environmentally Hazardous
14.6 Special precautions for user:	–
IMDG	
14.1 UN number or ID number: 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es)	UN 1053 HYDROGEN SULPHIDE
Class:	2.3
Label(s):	2.3, 2.1
EmS No.:	F-D, S-U
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Ц١	idroad	lphide
П	/uiuy	ipiliue

		, , ,	
Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		17/33
Last revised date :	27.10.2022		

- 14.5 Environmental hazards: Not applicable
- 14.6 Special precautions for user:

IATA

14.1 UN number or ID number: 14.2 Proper Shipping Name: 14.3 Transport Hazard Class(es): Class:	UN 1053 Hydrogen sulphide 2.3
Label(s):	-
14.4 Packing Group:	-
Limited quantity	None.
Excepted quantity	None.
14.5 Environmental hazards:	Environmentally Hazardous
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Forbidden.
Cargo aircraft only:	Forbidden.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. REACH Annex XIV, Substances Subject to Authorization as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		18/33
Last revised date :	27.10.2022		

amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as **amended:** None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: None present or none present in regulated quantities.

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.
Hydrogen sulphide	7783-06-4

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:

Chemical	CAS-No.	Lower-tier Requirements	Upper-tier Requirements
Hydrogen sulphide	7783-06-4	5 t	20 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen sulphide	7783-06-4	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 2016/425/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives. This Safety Data Sheet has been produced to comply with Regulation (EU) 2020/878.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

ECTION 16: Other information		
Revision Information:	Not relevant.	
Abbreviations and acronyms: AT/MAK:	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended	
ECTLV:	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC,	
SDS AT-000010021749		



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		19/33
Last revised date :	27.10.2022		

	2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended
AT/MAK / MAK:	Maximum allowable concentration:
AT/MAK / MAK CEIL:	MAK Ceiling Limit Value:
ECTLV / STEL:	Short Term Exposure Limit (STEL):
ECTLV / TWA:	Time Weighted Average (TWA):

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR -Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

```
Hydrogen sulphide
```

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		20/33
Last revised date :	27.10.2022		

Key literature references and sources for data:	Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to: Agency for Toxic Substances and Diseases Registry (ATSDR) (http://www.atsdr.cdc.gov/). European Chemical Agency: Guidance on the Compilation of Safety Data Sheets. European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended. International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets. Matheson Gas Data Book, 7th Edition. National Institute for Standards and Technology (NIST) Standard Reference Database Number 69. The ESIS (European Chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/). The European Chemical Industry Council (CEFIC) ERICards. United States of America's National Library of Medicine's toxicology data network TOXNET (http://toxnet.nlm.nih.gov/index.html) Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH). Substance specific information from suppliers. Details given in this document are believed to be correct at the time of publication.
--	---

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.	
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

Training information:Users of breathing apparatus must be trained. Ensure operators understand the
toxicity hazard. Ensure operators understand the flammability hazard. Ensure
operators understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1A, H220 Press. Gas Liq. Gas, H280 Acute Tox. 2, H330 STOT SE 3, H335 Aquatic Acute 1, H400



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		21/33
Last revised date :	27.10.2022		

Other information:Before using this product in any new process or experiment, a thorough material
compatibility and safety study should be carried out. Ensure adequate air ventilation.
Ensure all national/local regulations are observed. Whilst proper care has been
taken in the preparation of this document, no liability for injury or damage resulting
from its use can be accepted.Last revised date:27.09.2023

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		22/33
Last revised date :	27.10.2022		

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1)

Exposure Scenario 2)

Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use the gas as odorising agent in another gas (e.g. LPG)., Using gas for metal treatment., Use for electronic component manufacture., Using gas as feedstock in chemical processes. Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

Exposure Scenario 1)

Exposure scenario worker

1. Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use the gas as odorising agent in another gas (e.g. LPG)., Using gas for metal treatment., Use for electronic component manufacture., Using gas as feedstock in chemical processes.

List of use descriptors	
Sector(s) of use	SUO: Other
	SU4: Manufacture of food products
	SU8: Manufacture of bulk, large scale chemicals (including petroleum products)
	SU9: Manufacture of fine chemicals
	SU11: Manufacture of rubber products
	SU15: Manufacture of fabricated metal products, except machinery and equipment
	SU16: Manufacture of computer, electronic and optical products, electrical equipment
Product categories [PC]:	PC2: Adsorbents
	PC14: Metal surface treatment products
	PC21: Laboratory chemicals
	PC33: Semiconductors



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		23/33
Last revised date :	27.10.2022		

Name of contributing environmental scenario and corresponding ERC	Industrial use: ERC2: Formulation into mixture
	ERC6a: Use of intermediate
	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)
	ERC7: Use of functional fluid at industrial site
Contributing Scenarios	Industrial use: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes

PROC8b: Transfer of substance or mixture (charging and discharging)

PROC9: Transfer of substance or mixture into small containers

with equivalent containment condition

(dedicated filling line, including weighing)

at dedicated facilities

PROC16: Use of fuels

2.1. Contributing exposure scenario controlling environmental exposure for: Industrial use

Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,013 mPa.s (77 °F/25 °C)

Amounts used



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		24/33
Last revised date :	27.10.2022		

Annual amount per site

50 t

Frequency and duration of use

Batch process:	not relevant
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m3/d	not relevant	not relevant	Assumed on-site sewage treatment plant flow (m3/d):	Estimated 2000 m3/day

Other given operational conditions affecting environmental exposure

tupo		Emission factors			Domoska
type	Emission days		Soil	Water	Remarks
Continuous release	260	95 %	-	-	Closed systems are used in order to prevent unintended emissions

Other relevant operational conditions

not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		25/33
Last revised date :	27.10.2022		

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Direct emissions to the municipal STP should not be made.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Industrial use

Process Categories:	PROC1: Chemical production or refinery in closed process without
	likelihood of exposure or processes with equivalent containment
	conditions
	PROC3: Manufacture or formulation in the chemical industry in closed
	batch processes with occasional controlled exposure or processes with
	equivalent containment condition
	PROC8b: Transfer of substance or mixture (charging and discharging)



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Н١	ydrog	חסר	cu	Inh	ida
- 11	yuiuu	Jen	SU	ווקו	IUC

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		26/33
Last revised date :	27.10.2022		

	at dedicated facilities PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) PROC16: Use of fuels
--	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	20851 hPa
Process temperature:	25 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC3, PROC8b, PROC9, PROC16

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Transfer of substance or mixture (charging and



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		27/33
Last revised date :	27.10.2022		

	discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Use of fuels
--	--

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
See chapter 7 of the safety data sheet				Undertake operation under enclosed conditions.

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		28/33
Last revised date :	27.10.2022		

Environment:

Industrial use:

none

Health:

Industrial use:

попе

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra

Exposure Scenario 2)

Exposure scenario worker

1. Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

List of use descriptors		
Sector(s) of use	SU0: Other	
Product categories [PC]:	PC21: Laboratory chemicals	
Name of contributing environmental scenario and corresponding ERC	Using gas alone or in mixtures for the calibration of analysis equipment.: ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)	
Contributing Scenarios	Using gas alone or in mixtures for the calibration of analysis equipment.: PROC15: Use as laboratory reagent	

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Product characteristics

Concentration of the substance in a mixture:

Covers percentage substance in the product up to 100 %.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		29/33
Last revised date :	27.10.2022		

Physical form of the product

See section 9 of the SDS.

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,013 mPa.s (77 °F/25 °C)

Amounts used

Annual amount per site

10 kg

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	not relevant

Environment factors not influenced by risk management

Flow rate of receiving surface water (m ³ /d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m3/d	not relevant	not relevant	Assumed on-site sewage treatment plant flow (m3/d):	Estimated 2000 m3/day

Other given operational conditions affecting environmental exposure

tupo	Emission days		ctors		Bomarke
type	EIIIISSIUII Udys	Air	Soil	Water	Remarks
Intermittent release	260	95 %	-	-	Closed systems are used in order to prevent unintended emissions

Other relevant operational conditions

not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		30/33
Last revised date :	27.10.2022		

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions		
Air	not relevant		
Soil	not relevant		
Water	not relevant		
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.		

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant	
Discharge rate:	not relevant	
Treatment effectiveness:	not relevant	
Sludge treatment technique:	not relevant	
Measures to limit air emissions:	not relevant	
Remarks:	Direct emissions to the municipal STP should not be made.	

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		31/33
Last revised date :	27.10.2022		

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Process Categories:

PROC15: Use as laboratory reagent

Product characteristics

Concentration of the substance in a mixture: Covers percentage substance in the product up to 100 %.

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	20851 hPa
Process temperature:	25 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor use				Use as laboratory reagent

Other relevant operational conditions:

. See section 8 of the SDS.

Risk management measures (RMM)



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		32/33
Last revised date :	27.10.2022		

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
See chapter 7 of the safety data sheet				Undertake operation under enclosed conditions.

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas alone or in mixtures for the calibration of analysis equipment.:

попе

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 2.1	SDS No.: 000010021749
Revision Date:	27.09.2023		33/33
Last revised date :	27.10.2022		

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating
conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific
risk management measures. For scaling see http://www.ecetoc.org/tra