

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

1/16

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product name: CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet**Supplier**

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273**E-mail:** office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

Not classified

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure

Compressed gas

H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements

Signal Words: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

2/16

Precautionary Statement

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards: None.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	Notes
butane	C ₄ H ₁₀	100PPM	106-97-8	203-448-7	01-2119474691-32	#
methane	CH ₄	100PPM	74-82-8	200-812-7	01-2119474442-39	
ethane	C ₂ H ₆	100PPM	74-84-0	200-814-8	01-2119486765-21	
propane	C ₃ H ₈	100PPM	74-98-6	200-827-9	01-2119486944-21	#
Helium	He	99,9500%	7440-59-7	231-168-5	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	
Isobutane	C ₄ H ₁₀	100PPM	75-28-5	200-857-2	01-2119485395-27	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements.

All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

3/16

Classification

Chemical name	Classification		Notes
butane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
methane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Compr. Gas;H280	Note U
ethane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
propane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Helium	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	
Isobutane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	

DSD: Directive 67/548/EEC.

CLP: Regulation No. 1272/2008.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

The full text for all R-phrases and H-statements is displayed in section 16.

SECTION 4: First aid measures

General:

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation:

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact:

Adverse effects not expected from this product.

Skin Contact:

Adverse effects not expected from this product.

Ingestion:

Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed:

Respiratory arrest.

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

4/16

4.3 Indication of any immediate medical attention and special treatment needed**Hazards:** None.**Treatment:** None.**SECTION 5: Firefighting measures****General Fire Hazards:** Heat may cause the containers to explode.**5.1 Extinguishing media****Suitable extinguishing media:** Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent.**Unsuitable extinguishing media:** None.**5.2 Special hazards arising from the substance or mixture:** None.**Hazardous Combustion Products:** None.**5.3 Advice for firefighters****Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Guideline EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.**6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so.**6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation.

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

5/16

6.4 Reference to other sections: Refer to sections 8 and 13.**SECTION 7: Handling and storage:****7.1 Precautions for safe handling:**

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

6/16

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	type	Exposure Limit Values		Source
butane	MAK CEIL	1.600 ppm	3.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
propane	MAK	1.000 ppm	1.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	2.000 ppm	3.600 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Isobutane	MAK CEIL	1.600 ppm	3.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (eg. welded pipes). Do not eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Eye/face protection:

Wear eye protection to EN 166 when using gases.
Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection:

Wear working gloves while handling containers
Guideline: EN 388 Protective gloves against mechanical risks.

Body protection:

No special precautions.

Other:

Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

7/16

Respiratory Protection:	Not required.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:

Gas

Form:

Compressed gas

Color:

C₄H₁₀: ColorlessCH₄: ColorlessC₂H₆: ColorlessC₃H₈: Colorless

He: Colorless

C₄H₁₀: Colorless

Odor:

C₄H₁₀: Gasoline-like or natural gas odorCH₄: OdorlessC₂H₆: OdorlessC₃H₈: Odorless

He: Odorless

C₄H₁₀: Slight odor, Gasoline-like or natural gas odor

Odor Threshold:

Odor threshold is subjective and is inadequate to warn of over exposure.

pH:

not applicable.

Melting Point:

No data available.

Boiling Point:

No data available.

Sublimation Point:

not applicable.

Critical Temp. (°C):

No data available.

Flash Point:

Not applicable to gases and gas mixtures.

Evaporation Rate:

Not applicable to gases and gas mixtures.

Flammability (solid, gas):

This product is not flammable.

Flammability Limit - Upper (%):

not applicable.

Flammability Limit - Lower (%):

not applicable.

Vapor pressure:

No reliable data available.

Vapor density (air=1):

0,14 (calculated) (15 °C)

Relative density:

No data available.

Solubility(ies)

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

8/16

Solubility in Water:	No data available.
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	not applicable.

9.2 Other information: None.**SECTION 10: Stability and reactivity**

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of Hazardous Reactions:	None.
10.4 Conditions to Avoid:	None.
10.5 Incompatible Materials:	No reaction with any common materials in dry or wet conditions.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**General information:** None.**11.1 Information on toxicological effects**

Acute toxicity - Oral Product	Based on available data, the classification criteria are not met.
Acute toxicity - Dermal Product	Based on available data, the classification criteria are not met.
Acute toxicity - Inhalation Product	Not classified for acute toxicity based on available data.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

9/16

Component Information

methane LC 50 (Rat, 4 h): > 13023 ppm Remarks: Vapor

Isobutane LC 50 (Rat, 15 min): 570000 ppm

Repeated dose toxicity**Component Information**

methane NOAEC (Rat, Inhalation): 4000 ppm

LOAEC (Rat, Inhalation): 12000 ppm

ethane NOAEC (Rat, Inhalation): 19678 mg/m³**Skin Corrosion/Irritation****Product**

Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation**Product**

Based on available data, the classification criteria are not met.

Component Information

butane Not irritating

ethane Not irritating

Respiratory or Skin Sensitization**Product**

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity**Product**

Based on available data, the classification criteria are not met.

In vitro**Component Information**

methane Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome Aberration Test)): Negative.

ethane Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Negative.

In vivo**Component Information**

methane Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

ethane Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

10/16

Carcinogenicity**Product**

Based on available data, the classification criteria are not met.

Reproductive toxicity**Product**

Based on available data, the classification criteria are not met.

Reproductive toxicity (Fertility)**Component Information**

methane

Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 3.000 ppm

Developmental toxicity (Teratogenicity)**Component Information**

methane

Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))

NOAEC: 9.000 ppm

Specific Target Organ Toxicity - Single Exposure**Product**

Based on available data, the classification criteria are not met.

Component Information**Specific Target Organ Toxicity - Repeated Exposure****Product**

Based on available data, the classification criteria are not met.

Aspiration Hazard**Product**

Not applicable to gases and gas mixtures..

SECTION 12: Ecological information**12.1 Toxicity****Acute toxicity****Product**

No ecological damage caused by this product.

Acute toxicity - Fish**Component Information**

methane

LC 50 (Various (Freshwater), 96 h): 27,98 mg/l (calculated)

ethane

LC50 (Fish, 96 h): 91,4 mg/l

propane

LC50 (Fish, 96 h): 49,9 mg/l

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

11/16

Acute toxicity - Aquatic Invertebrates**Component Information**

methane	LC 50 (Water flea (Daphnia magna), 48 h): 27,14 mg/l
ethane	EC50 (Water flea (Daphnia magna), 48 h): 46,6 mg/l
propane	EC50 (Water flea (Daphnia magna), 48 h): 27,1 mg/l

Toxicity to microorganisms**Component Information**

methane	EC 50 (Alga, 96 h): 19,37 mg/l Not harmful to microorganisms
ethane	EC50 (Alga, 72 h): 16,5 mg/l
propane	EC50 (Alga, 72 h): 11,9 mg/l

12.2 Persistence and Degradability**Product**

Not applicable to gases and gas mixtures..

Biodegradation**Component Information**

methane	100 %
---------	-------

12.3 Bioaccumulative Potential**Product**

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.4 Mobility in Soil**Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

Component Information

methane	Henry's Law Constant: 3.690 MPa (25 °C)
---------	---

12.5 Results of PBT and vPvB assessment**Product**

Not classified as PBT or vPvB.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

12/16

12.6 Other Adverse Effects:

Global Warming Potential

Global warming potential: 0
Contains fluorinated greenhouse gases covered by the Kyoto protocol. When discharged in large quantities may contribute to the greenhouse effect.

Component Information

methane

UN / IPCC. Greenhouse Gas Global Warming Potentials (IPCC Fourth Assessment Report, Climate Change, Table TS.2
- Global warming potential: 25 100-yr

butane

ethane

Global warming potential: 6

propane

Global warming potential: 3

Isobutane

Global warming potential: 3

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:

Do not discharge into any place where its accumulation could be dangerous. Vent to atmosphere in a well ventilated place.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container:

16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

13/16

SECTION 14: Transport information**ADR**

14.1 UN Number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.2
Hazard No. (ADR):	-
Tunnel restriction code:	(E)
14.4 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-

RID

14.1 UN Number:	UN 1950
14.2 UN Proper Shipping Name	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-

IMDG

14.1 UN Number:	UN 1950
14.2 UN Proper Shipping Name:	AEROSOLS
14.3 Transport Hazard Class(es)	
Class:	2.2
Label(s):	2.2
EmS No.:	F-D, S-U
14.3 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-

IATA

14.1 UN Number:	UN 1950
14.2 Proper Shipping Name:	Aerosols, non-flammable
14.3 Transport Hazard Class(es):	
Class:	2.2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

14/16

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
butane	106-97-8	- <0,1%
propane	74-98-6	- <0,1%

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.:

Chemical name	CAS-No.	Concentration
methane	74-82-8	0 - <0,1%
ethane	74-84-0	0 - <0,1%
propane	74-98-6	0 - <0,1%

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

Chemical name	CAS-No.	Concentration
methane	74-82-8	0 - <0,1%
ethane	74-84-0	0 - <0,1%
propane	74-98-6	0 - <0,1%

Directive 96/82/EC (Seveso II): on the control of major accident hazards involving dangerous substances:

SAFETY DATA SHEET

CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

15/16

Chemical name	CAS-No.	Concentration
butane	106-97-8	0 - <0,1%
ethane	74-84-0	0 - <0,1%
propane	74-98-6	0 - <0,1%
Isobutane	75-28-5	0 - <0,1%

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
butane	106-97-8	0 - <0,1%
methane	74-82-8	0 - <0,1%
ethane	74-84-0	0 - <0,1%
propane	74-98-6	0 - <0,1%
Isobutane	75-28-5	0 - <0,1%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

SAFETY DATA SHEET**CH₄ 0,01 %;C₂H₆ 0,01 %;C₃H₈ 0,01 %;C₄H₁₀ 0,01 %;C₄H₁₀ 0,01 %;He 99,95 % in Minican**

Issue Date: 29.04.2015

Version: 1.0

SDS No.: 000010022899

Last revised date: 10.12.2015

16/16

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the R-phrases and H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
R12	Extremely flammable.

Training information:

Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Compr. Gas, H280

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

10.12.2015

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.