

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

1 / 23

SECTION 1: Identification of the substance / mixture and of the company / undertaking**1.1 Product identifier**

Product name: C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Trade name: L 1-11 K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.

Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet**Supplier**

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

F+; R12

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Compressed gas	H280: Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012
Last revised date: 24.01.2017

Version: 1.0

SDS No.: 000010001143
2/23

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H220: Extremely flammable gas.
H280: Contains gas under pressure; may explode if heated.

Precautionary Statement

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: Eliminate all ignition sources if safe to do so.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

2.3 Other hazards: None.

SECTION 3: Composition / information on ingredients**3.2 Mixtures**

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	Notes
pentane	C5H12	500PPM	109-66-0	203-692-4	01-2119459286-30	#
isopentane; 2-methylbutane	C5H12	500PPM	78-78-4	201-142-8	01-2119475602-38	#
Neopentane	C5H12	500PPM	463-82-1	207-343-7	Not available.	#
n-hexane	C6H14	500PPM	110-54-3	203-777-6	01-2119480412-44	#
Butane	C4H10	1.000PPM	106-97-8	203-448-7	01-2119474691-32	#
Isobutane	C4H10	1.000PPM	75-28-5	200-857-2	01-2119485395-27	#
Propane	C3H8	3.000PPM	74-98-6	200-827-9	01-2119486944-21	#
Ethane	C2H6	7.500PPM	74-84-0	200-814-8	01-2119486765-21	
Carbon dioxide	CO2	1,5500%	124-38-9	204-696-9	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	#
Nitrogen	N2	11%	7727-37-9	231-783-9	Listed in Annex IV/V	

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

3/23

					of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	
Methane	CH4	86%	74-82-8	200-812-7	01-2119474442-39	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Classification		Notes
pentane	DSD:	F+; R12 Xn; R65 R66 R67 N; R51 / 53	
	CLP:	Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 2;H411, Flam. Liq. 1;H224	Note C
isopentane; 2-methylbutane	DSD:	F+; R12 Xn; R65 R66 R67 N; R51 / 53	
	CLP:	Flam. Liq. 1;H224, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 2;H411	
Neopentane	DSD:	N; R51 / 53 F+; R12	
	CLP:	Flam. Gas 1;H220, Aquatic Chronic 2;H411, Press. Gas Liquef. Gas;H280	
n-hexane	DSD:	F; R11 Repr. 3; R62 Xi; R38 Xn; R65, R48 / 20 R67 N; R51 / 53	
	CLP:	Flam. Liq. 2;H225, Repr. 2;H361f, STOT RE 2;H373, Asp. Tox. 1;H304, Skin Irrit. 2;H315, STOT SE 3;H336, Aquatic Chronic 2;H411	
Butane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Isobutane	DSD:	F+; R12	
	CLP:	Press. Gas Liquef. Gas;H280, Flam. Gas 1;H220	
Propane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Ethane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Liquef. Gas;H280	
Carbon dioxide	DSD:	none	
	CLP:	Press. Gas Liquef. Gas;H280	
Nitrogen	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	
Methane	DSD:	F+; R12	
	CLP:	Flam. Gas 1;H220, Press. Gas Compr. Gas;H280	Note U

DSD: Directive 67 / 548 / EEC.

CLP: Regulation No. 1272 / 2008.

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

4/23

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

The full text for all R-phrases and H-statements is displayed in section 16.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Low concentrations of CO2 cause increased respiration and headache.

Eye contact: Adverse effects not expected from this product.

Skin Contact: Adverse effects not expected from this product.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

5/23

5.2 Special hazards arising from the substance or mixture:

Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters**Special fire fighting procedures:**

In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. Eliminate all ignition sources if safe to do so. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition.

6.4 Reference to other sections:

Refer to sections 8 and 13.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012
Last revised date: 24.01.2017

Version: 1.0

SDS No.: 000010001143
6 / 23

SECTION 7: Handling and storage:**7.1 Precautions for safe handling:**

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use only non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local / regional / national / international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

7/23

SECTION 8: Exposure controls / personal protection
8.1 Control Parameters
Occupational Exposure Limits

Chemical name	type	Exposure Limit Values		Source
Carbon dioxide	TWA	5.000 ppm	9.000 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	5.000 ppm	9.000 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	10.000 ppm	18.000 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Propane	MAK	1.000 ppm	1.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	2.000 ppm	3.600 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Butane	MAK CEIL	1.600 ppm	3.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Isobutane	MAK CEIL	1.600 ppm	3.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	800 ppm	1.900 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
pentane	TWA	1.000 ppm	3.000 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	600 ppm	1.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	1.200 ppm	3.600 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
isopentane; 2-methylbutane	TWA	1.000 ppm	3.000 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK CEIL	1.200 ppm	3.600 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK	600 ppm	1.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
Neopentane	TWA	1.000 ppm	3.000 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	600 ppm	1.800 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	1.200 ppm	3.600 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
n-hexane	TWA	20 ppm	72 mg/m3	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC,

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

8/23

			2006/15/EC, 2009/161/EU (12 2009)
	MAK	20 ppm 72 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK STEL	80 ppm 288 mg/m3	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

DNEL-Values

Critical component	type	Value	Remarks
pentane	Worker - inhalative, long-term - systemic	3000 mg/m3	-
	Worker - dermal, long-term - systemic	432 mg/kg bw/day	-
isopentane; 2-methylbutane	Worker - inhalative, long-term - systemic	3000 mg/m3	-
	Worker - dermal, long-term - systemic	432 mg/kg bw/day	-
n-hexane	Worker - inhalative, long-term - systemic	75 mg/m3	-
	Worker - dermal, long-term - systemic	11 mg/kg bw/day	-

PNEC-Values

Critical component	type	Value	Remarks
pentane	Aquatic (freshwater)	230 µg/l	-
	Soil	0,55 mg/kg	-
	Sediment (marine water)	1,2 mg/kg	-
	Sewage treatment plant	3600 µg/l	-
	Sediment (freshwater)	1,2 mg/kg	-
	Aquatic (marine water)	230 µg/l	-
	Aquatic (intermit. releases)	880 µg/l	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

9/23

Individual protection measures, such as personal protective equipment

General information:	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.
Eye / face protection:	Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection	
Hand Protection:	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks.
Body protection:	Wear fire / flame resistant / retardant clothing. Guideline: ISO / TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Not required.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state:	Gas
Form:	Compressed gas
Color:	C5H12: Colorless C6H14: Colorless C4H10: Colorless C4H10: Colorless C3H8: Colorless C2H6: Colorless

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012
Last revised date: 24.01.2017

Version: 1.0

SDS No.: 000010001143
10/23

Odor:

CH4: Colorless
CO2: Colorless
N2: Colorless
C5H12: Colourless
C5H12: Colourless
C6H14: Gasoline-like odor
N2: Odorless gas
C5H12: Sweetish
C4H10: Gasoline-like or natural gas odor
C3H8: Odorless
C2H6: Odorless
CO2: Odorless
CH4: Odorless
C5H12: Gasoline-like odor
C5H12: Faint
C4H10: Gasoline-like or natural gas odor

Odor Threshold:

Odor threshold is subjective and is inadequate to warn of over exposure.

pH:

not applicable.

Melting Point:

No data available.

Boiling Point:

No data available.

Sublimation Point:

not applicable.

Critical Temp. (°C):

No data available.

Flash Point:

Not applicable to gases and gas mixtures.

Evaporation Rate:

Not applicable to gases and gas mixtures.

Flammability (solid, gas):

Flammable Gas

Flammability Limit - Upper (%):

not applicable.

Flammability Limit - Lower (%):

not applicable.

Vapor pressure:

No reliable data available.

Vapor density (air=1):

0,64 (calculated) (15 °C)

Relative density:

No data available.

Solubility(ies)**Solubility in Water:**

No data available.

Partition coefficient (n-octanol / water):

Not known.

Autoignition Temperature:

not applicable.

Decomposition Temperature:

Not known.

Viscosity**Kinematic viscosity:**

No data available.

Dynamic viscosity:

No data available.

Explosive properties:

Not applicable.

Oxidizing properties:

not applicable.

9.2 Other information:

None.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

11 / 23

SECTION 10: Stability and reactivity

- 10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.
- 10.2 Chemical Stability:** Stable under normal conditions.
- 10.3 Possibility of hazardous reactions:** Can form a potentially explosive atmosphere in air. May react violently with oxidants.
- 10.4 Conditions to avoid:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- 10.5 Incompatible Materials:** Air and oxidizers. For material compatibility see latest version of ISO-11114.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Component Information
pentane LD 50 (Rat): > 2.000 mg / kg

isopentane; 2-methylbutane LD 50 (Rat): > 2.000 mg / kg

n-hexane LD 50 (Rat): 16 g / kg

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Component Information
n-hexane LD 50 (Rabbit): > 2.000 mg / kg

SAFETY DATA SHEET

C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₆H₁₄ 0,05 %;C₄H₁₀ 0,1 %;C₄H₁₀ 0,1 %;C₃H₈ 0,3 %;C₂H₆ 0,75 %;CO₂ 1,55 %;N₂ 11 %;CH₄ 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

12 / 23

Acute toxicity - Inhalation**Product**

Based on available data, the classification criteria are not met.

Component Information

pentane

LC 50 (Rat, 4 h): > 25,3 mg / l Remarks: Vapor

isopentane; 2-methylbutane

LC 50 (Rat, 4 h): > 25,3 mg / l Remarks: Vapor

Neopentane

LC 40 (Mouse, 2 h): 340000 ppm

n-hexane

LC 50 (Rat, 4 h): 73860 ppm Remarks: Vapor

Isobutane

LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key study

Repeated dose toxicity**Component Information**

pentane

NOAEL (Rat(Female, Male), Inhalation): 20.000 mg / m³

isopentane; 2-methylbutane

NOAEL (Rat(Female, Male), Inhalation): 20.000 mg / m³
NOAEL (Rat, Inhalation): 30 mg / l

Butane

NOAEL (Rat(Female, Male), Inhalation, >= 42 d): 16.000 ppm(m) Inhalation
Experimental result, Key study

Isobutane

NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation
Read-across based on grouping of substances (category approach), Key study

Propane

LOAEL (Rat(Female, Male), Inhalation): 21.641 mg / m³ Inhalation Experimental
result, Key study

Ethane

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4.000 ppm(m) Inhalation
Experimental result, Key study
NOAEC (Rat, Inhalation): 19678 mg / m³

Methane

NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation
Read-across based on grouping of substances (category approach), Key study**Skin Corrosion / Irritation****Product**

Based on available data, the classification criteria are not met.

Component Information

pentane

in vivo (Rabbit): Not classified as an Irritant

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

13 / 23

isopentane; 2-
methylbutane

in vivo (Rabbit): Not classified as an Irritant

Serious Eye Damage / Eye Irritation**Product**

Based on available data, the classification criteria are not met.

Component Information

pentane

in vivo (Rabbit, 48 hrs): Not irritatingOECD GHS

isopentane; 2-
methylbutane

in vivo (Rabbit, 24 hrs): Not irritatingOECD GHS

n-hexane

in vivo (Rabbit, 24 - 72 hrs): Not irritatingEU

Ethane

Not irritating

Respiratory or Skin Sensitization**Product**

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity**Product**

Based on available data, the classification criteria are not met.

In vitro**Component Information**

Ethane

Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)): Negative.

Methane

Chromosome aberration (OECD Guideline 473 (In Vitro Mammalian Chromosome Aberration Test)): Negative.

In vivo**Component Information**

Ethane

Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Methane

Drosophila Sex-Linked Recessive Lethal Assay (SLRL) test: Negative.

Carcinogenicity**Product**

Based on available data, the classification criteria are not met.

Reproductive toxicity**Product**

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

14/ 23

Reproductive toxicity (Fertility)**Component Information**

n-hexane LC50: 5.000 ppm

Methane Gestation: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 9.000 ppm
 Fertility: Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 3.000 ppm

Developmental toxicity (Teratogenicity)**Component Information**

Methane Rat Inhalation (OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test))
 NOAEC: 9.000 ppm

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Component Information**Specific Target Organ Toxicity - Repeated Exposure**

Product Based on available data, the classification criteria are not met.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity**Acute toxicity**

Product No ecological damage caused by this product.

Acute toxicity - Fish**Component Information**

pentane LC 50 (Oncorhynchus mykiss, 96 h): 4,26 mg/l (Static renewal) Remarks: experimental result

isopentane; 2-methylbutane LC 50 (Oncorhynchus mykiss, 96 h): 4,26 mg/l (Static renewal) Remarks: interpreted
 LC 50 (Rainbow trout (Oncorhynchus mykiss), 96 h): 4,26 mg/l

n-hexane LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,101 - 2,981 mg/l (Flow through) Remarks: Mortality

Butane LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

15/23

Isobutane	LC 50 (Various, 96 h): 27,98 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Propane	LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Ethane	LC 50 (Various, 96 h): 147,54 mg/l (QSAR) Remarks: QSAR QSAR, Key study LC50 (Fish, 96 h): 91,4 mg/l
Methane	LC 50 (Various, 96 h): 27,98 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates**Component Information**

pentane	EC 50 (Water flea (Daphnia magna), 48 h): 2.7 mmol / m ³
isopentane; 2-methylbutane	EC 50 (Water flea (Daphnia magna)): 2,3 mg/l
n-hexane	LC 50 (Water flea (Daphnia magna), 48 h): 45 mmol / m ³
Butane	LC 50 (Daphnid, 48 h): 14,22 mg/l (QSAR) Remarks: QSAR QSAR, Key study LC50 (Water flea (Daphnia magna), 48 h): 14,2 mg/l
Isobutane	LC 50 (Daphnid, 48 h): 14,22 mg/l (QSAR) Remarks: QSAR QSAR, Key study
Propane	LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study
Ethane	LC 50 (Daphnid, 48 h): 16,33 mg/l (QSAR) Remarks: QSAR QSAR, Key study EC50 (Water flea (Daphnia magna), 48 h): 46,6 mg/l
Methane	LC 50 (Daphnid, 48 h): 27,14 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Toxicity to microorganisms**Component Information**

Propane	EC50 (Alga, 72 h): 11,9 mg/l
Ethane	EC50 (Alga, 72 h): 16,5 mg/l
Methane	EC 50 (Alga, 96 h): 19,37 mg/l Not harmful to microorganisms

Toxicity to Aquatic Plants**Component Information**

pentane	EC 50 (Green algae (Selenastrum capricornutum), 72 h): 10,7 mg/l NOEC (Green algae (Selenastrum capricornutum), 72 h): 2,04 mg/l
---------	---

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

16 / 23

isopentane; 2-methylbutane

NOEC (Algae (Pseudokirchneriella subcapitata), 72 h): 7,51 mg/l
 EC 50 (Algae (Pseudokirchneriella subcapitata), 72 h): 10,7 mg/l

Butane

LC50 (Alga, 72 h): 7,7 mg/l

12.2 Persistence and Degradability**Product**

Not applicable to gases and gas mixtures..

Biodegradation**Component Information**

Methane

100 %

Photodegradation**Component Information**

pentane

Non-significant photolysis

Stability in water**Component Information**

pentane

87 %Non-significant hydrolysis

12.3 Bioaccumulative Potential**Product**

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.4 Mobility in Soil**Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

Component Information

pentane

Henry's Law Constant: 7.010 MPa (25 °C)

isopentane; 2-methylbutane

Henry's Law Constant: 7.851 MPa

Methane

Henry's Law Constant: 3.690 MPa (25 °C)

12.5 Results of PBT and vPvB**assessment****Product**

Not classified as PBT or vPvB.

Component Information

SAFETY DATA SHEET

C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₆H₁₄ 0,05 %;C₄H₁₀ 0,1 %;C₄H₁₀ 0,1 %;C₃H₈ 0,3 %;C₂H₆ 0,75 %;CO₂ 1,55 %;N₂ 11 %;CH₄ 86 %

Issue Date: 20.12.2012
Last revised date: 24.01.2017

Version: 1.0

SDS No.: 000010001143
17/23

12.6 Other Adverse Effects:**Global Warming Potential**

Global warming potential: 19,1
Contains fluorinated greenhouse gases covered by the Kyoto protocol. When discharged in large quantities may contribute to the greenhouse effect.

Component Information

Carbon dioxide	<u>UN / IPCC. Greenhouse Gas Global Warming Potentials (IPCC Fourth Assessment Report, Climate Change, Table TS.2</u> - Global warming potential: 1 100-yr
Methane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 25 100-yr
pentane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 5 100-yr
isopentane; 2-methylbutane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 5 100-yr
Butane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 4 100-yr
Isobutane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 3 100-yr
Propane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 3 100-yr
Ethane	<u>EU. Annexes I, II (F-gases subject to emission limits/reporting), IV (GWPs for mixture calculations), Reg. 517/2014/EU on fluorinated greenhouse gases</u> - Global warming potential: 6 100-yr

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

18/23

SECTION 13: Disposal considerations**13.1 Waste treatment methods****General information:**

Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Disposal methods:

Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes**Container:**

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information**ADR**

14.1 UN Number:	UN 1954
14.2 UN Proper Shipping Name:	COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Hexane)
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	23
Tunnel restriction code:	(B/D)
14.4 Packing Group:	–
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	–

RID

14.1 UN Number:	UN 1954
14.2 UN Proper Shipping Name	COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Hexane)
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
14.4 Packing Group:	–
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	–

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

19/23

IMDG

14.1 UN Number: UN 1954
 14.2 UN Proper Shipping Name: COMPRESSED GAS, FLAMMABLE, N.O.S.(Methane, Hexane)
 14.3 Transport Hazard Class(es):
 Class: 2.1
 Label(s): 2.1
 EmS No.: F-D, S-U
 14.3 Packing Group: –
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: –

IATA

14.1 UN Number: UN 1954
 14.2 Proper Shipping Name: Compressed gas, flammable, n.o.s.(Methane, Hexane)
 14.3 Transport Hazard Class(es):
 Class: 2.1
 Label(s): 2.1
 14.4 Packing Group: –
 14.5 Environmental hazards: not applicable
 14.6 Special precautions for user: –
 Other information
 Passenger and cargo aircraft: Forbidden.
 Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL73 / 78 and the IBC Code: not applicable

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture:**EU Regulations**

Regulation (EC) No. 1907 / 2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
pentane	109-66-0	- <0,1%

SAFETY DATA SHEET

C₅H₁₂ 0,05 %; C₅H₁₂ 0,05 %; C₅H₁₂ 0,05 %; C₆H₁₄ 0,05 %; C₄H₁₀ 0,1 %; C₄H₁₀ 0,1 %; C₃H₈ 0,3 %; C₂H₆ 0,75 %; CO₂ 1,55 %; N₂ 11 %; CH₄ 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

20/23

isopentane; 2-methylbutane	78-78-4	- <0,1%
Neopentane	463-82-1	- <0,1%
n-hexane	110-54-3	- <0,1%
Propane	74-98-6	0,1 - 1,0%
Methane	74-82-8	80 - 90%

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.:

Chemical name	CAS-No.	Concentration
pentane	109-66-0	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%
Neopentane	463-82-1	0 - <0,1%

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

Chemical name	CAS-No.	Concentration
pentane	109-66-0	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%
Neopentane	463-82-1	0 - <0,1%

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Carbon dioxide	124-38-9	1,0 - 10%

Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Methane	74-82-8	80 - 90%
Butane	106-97-8	0,1 - 1,0%
Isobutane	75-28-5	0,1 - 1,0%

SAFETY DATA SHEET

C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₆H₁₄ 0,05 %;C₄H₁₀ 0,1 %;C₄H₁₀ 0,1 %;C₃H₈ 0,3 %;C₂H₆ 0,75 %;CO₂ 1,55 %;N₂ 11 %;CH₄ 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

21 / 23

Propane	74-98-6	0,1 - 1,0%
Ethane	74-84-0	0,1 - 1,0%
pentane	109-66-0	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%
Neopentane	463-82-1	0 - <0,1%
n-hexane	110-54-3	0 - <0,1%

Directive 98 / 24 / EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Butane	106-97-8	0,1 - 1,0%
pentane	109-66-0	0 - <0,1%
isopentane; 2-methylbutane	78-78-4	0 - <0,1%
Neopentane	463-82-1	0 - <0,1%
n-hexane	110-54-3	0 - <0,1%

National Regulations

Council Directive 89 / 391 / EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89 / 686 / EEC on personal protective equipment Directive 94 / 9 / EC on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333 / 2008 and (EU) No. 231 / 2012 and are labelled as such may be used as food additives.
This Safety Data Sheet has been produced to comply with Regulation (EU) 453 / 2010.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

SAFETY DATA SHEET

C5H12 0,05 %;C5H12 0,05 %;C5H12 0,05 %;C6H14 0,05 %;C4H10 0,1 %;C4H10 0,1 %;C3H8 0,3 %;C2H6 0,75 %;CO2 1,55 %;N2 11 %;CH4 86 %

Issue Date: 20.12.2012
Last revised date: 24.01.2017

Version: 1.0

SDS No.: 000010001143
22 / 23

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the R-phrases and H-statements in section 2 and 3

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
R11	Highly flammable.
R12	Extremely flammable.
R38	Irritating to skin.
R48 / 20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R51 / 53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62	Possible risk of impaired fertility.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY DATA SHEET

C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₅H₁₂ 0,05 %;C₆H₁₄ 0,05 %;C₄H₁₀ 0,1 %;C₄H₁₀ 0,1 %;C₃H₈ 0,3 %;C₂H₆ 0,75 %;CO₂ 1,55 %;N₂ 11 %;CH₄ 86 %

Issue Date: 20.12.2012

Version: 1.0

SDS No.: 000010001143

Last revised date: 24.01.2017

23 / 23

Training information: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/ 2008 as amended.

Flam. Gas 1, H220

Press. Gas Compr. Gas, H280

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national / local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 24.01.2017

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.