



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013 Version: 1.1 SDS No.: 000010021800  
 Last revised date: 11.02.2022 1/40

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Product name:** Sulfur dioxide  
**Trade name:** Gasart 479 Schwefeldioxid 3.8

**Additional identification**

**Chemical name:** Sulphur dioxide  
**Chemical formula:** SO<sub>2</sub>  
**INDEX No.** 016-011-00-9  
**CAS-No.** 7446-09-5  
**EC No.** 231-195-2  
**REACH Registration No.** 01-2119485028-34

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses:** Industrial and professional. Perform risk assessment prior to use. Formulation of mixtures with gas in pressure receptacles. Calibration gas for analytical equipment Use of gas to manufacture pharmaceutical products. Metal coating Glass processing. Water treatment. Refrigerant. Using gas as feedstock in chemical processes. Preservative in food industry.  
**Uses advised against** Consumer use. Contact supplier for more information on uses. Uses other than those listed above are not supported. Industrial or technical grade is unsuitable for medical and/or food applications or inhalation.

**1.3 Details of the supplier of the safety data sheet**

**Supplier**  
 Linde Gas GmbH Telephone: +43 50 4273  
 Carl-von-Linde-Platz 1  
 A-4651 Stadl-Paura  
  
**E-mail:** office@at.linde-gas.com

**1.4 Emergency telephone number:** Emergency number UMC0: +49 89 220 61012 (German), +44 1865 407333 (English)

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013 Version: 1.1 SDS No.: 000010021800  
 Last revised date: 11.02.2022 2/40

Gases under pressure Liquefied gas H280: Contains gas under pressure; may explode if heated.

**Health Hazards**

Acute toxicity (Inhalation - gas) Category 3 H331: Toxic if inhaled.  
 Skin corrosion Category 1B H314: Causes severe skin burns and eye damage.  
 Serious eye damage Category 1 H318: Causes serious eye damage.

**2.2 Label Elements**

Contains: Sulphur dioxide



Signal Word: Danger

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.  
 H331: Toxic if inhaled.  
 H314: Causes severe skin burns and eye damage.

**Precautionary Statements**  
 General

None.

**Prevention:**

P260: Do not breathe gas/vapors.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.  
 P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.  
 P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Storage:**

P403: Store in a well-ventilated place.  
 P405: Store locked up.

**Disposal**

None.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013 Version: 1.1 SDS No.: 000010021800  
 Last revised date: 11.02.2022 3/40

**Supplemental information**

EUH071: Corrosive to the respiratory tract.

**2.3 Other hazards**

Contact with evaporating liquid may cause frostbite or freezing of skin.

**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

**Chemical name** Sulphur dioxide  
**INDEX No.:** 016-011-00-9  
**CAS-No.:** 7446-09-5  
**EC No.:** 231-195-2  
**REACH Registration No.:** 01-2119485028-34  
**Purity:** 100%  
 The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.  
**Trade name:** Gasart 479 Schwefeldioxid 3.8

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Sulphur dioxide	SO <sub>2</sub>	100%	7446-09-5	01-2119485028-34	-	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

# This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

**SECTION 4: First aid measures**

**General:** Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

**Inhalation:** Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013 Version: 1.1 SDS No.: 000010021800  
 Last revised date: 11.02.2022 4/40

**Eye contact:** Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

**Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.

**Ingestion:** Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Hazards:** Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

**SECTION 5: Firefighting measures**

**General Fire Hazards:** Heat may cause the containers to explode.

**5.1 Extinguishing media**

**Suitable extinguishing media:** Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.

**Unsuitable extinguishing media:** None.

**5.2 Special hazards arising from the substance or mixture:** Fire or excessive heat may produce hazardous decomposition products.

**5.3 Advice for firefighters**

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.



### SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

#### Sulfur dioxide

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
5/40

**Special protective equipment for fire-fighters:**

Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.  
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

**SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
- 6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.
- 6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.
- 6.4 Reference to other sections:** Refer to sections 8 and 13.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		6/40

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**7.2 Conditions for safe storage, including any incompatibilities:** Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):** None.



### SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

#### Sulfur dioxide

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
7/40

## SECTION 8: Exposure controls/personal protection

### 8.1 Control Parameters

#### Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Sulphur dioxide	STEL	1 ppm 2,7 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (02 2017)
	TWA	0,5 ppm 1,3 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (02 2017)
	MAK STEL	1 ppm 2,7 mg/m <sup>3</sup>	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended (04 2021)
	MAK	0,5 ppm 1,3 mg/m <sup>3</sup>	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended (04 2021)

#### DNEL-Values

Critical component	Type	Value	Remarks
Sulphur dioxide	Workers - Inhalation, Local, short-term	2,7 mg/m <sup>3</sup>	respiratory tract irritation
	Workers - Inhalation, Local, long-term	2,7 mg/m <sup>3</sup>	respiratory tract irritation

### 8.2 Exposure controls

#### Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.



## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

### Sulfur dioxide

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
8/40

#### Individual protection measures, such as personal protective equipment

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
- Hand Protection:** Guideline: EN 388 Protective gloves against mechanical risks.  
Additional Information: Wear working gloves while handling containers  
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.  
Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Body protection:** Keep suitable chemically resistant protective clothing readily available for emergency use.  
Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
- Other:** Wear safety shoes while handling containers  
Guideline: ISO 20345 Personal protective equipment - Safety footwear.





**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		9/40

**Respiratory Protection:** Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres

Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking. Material: Filter E

Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.

**Thermal hazards:** No precautionary measures are necessary.

**Hygiene measures:** Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

**Environmental exposure controls:** For waste disposal, see section 13 of the SDS.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Appearance**

<b>Physical state:</b>	Gas
<b>Form:</b>	Liquefied gas
<b>Color:</b>	Colorless
<b>Odor:</b>	biting
<b>Odor Threshold:</b>	Odor threshold is subjective and is inadequate to warn of over exposure.
<b>pH:</b>	Not applicable.
<b>Melting Point:</b>	-75,5 °C Other, Key study
<b>Boiling Point:</b>	-10,05 °C (101,325 kPa) Other, Key study
<b>Sublimation Point:</b>	Not applicable.
<b>Critical Temp. (°C):</b>	158,0 °C
<b>Flash Point:</b>	Not applicable to gases and gas mixtures.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		10/40

Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Nonflammable Gas
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	3.271 hPa (20 °C) Other, Key study
Vapor density (air=1):	2,263 (0 °C) AIR=1
Relative density:	2,26
Solubility(ies)	
Solubility in Water:	Completely soluble in water
Solubility (other):	water: 0,113 g/ml (20 °C)
Partition coefficient (n-octanol/water):	Not applicable
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,012 mPa.s (18 °C)
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.
 9.2 Other information:	 Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
Molecular weight:	64,06 g/mol (SO <sub>2</sub> )

<b>SECTION 10: Stability and reactivity</b>
---

10.1 Reactivity:	No data available.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	May polymerise. May react violently with alkaline-earth and alkali metals. OXIDIZING! Reacts violently with strong bases. Reacts with Moisture Reacts with water to form corrosive acids.
10.4 Conditions to avoid:	Avoid contact with oxidizing agents. Avoid alkalis and/or heat. Avoid contact with strong reducing agents. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Avoid moisture in the installation. May attack some plastics, rubber and coatings. Moisture. Oxidizing, avoid contact with reducing agents. Polymerization initiators.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		11/40

**10.5 Incompatible Materials:** Moisture. For material compatibility see latest version of ISO-11114.

**10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

<b>SECTION 11: Toxicological information</b>
--

**General information:** None.

**11.1 Information on toxicological effects**

**Acute toxicity - Oral Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal Product** Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation Product** Toxic if inhaled.

Sulphur dioxide LC 50 (Rat, 4 h): 1260 ppm  
Remarks: Delayed fatal pulmonary oedema possible.

**Repeated dose toxicity Sulphur dioxide** NOAEL (Rat(Female, Male), Inhalation, 4 Weeks): 5 ppm(m) Inhalation  
Experimental result, Key study

**Skin Corrosion/Irritation Product** Causes severe burns.

**Serious Eye Damage/Eye Irritation Product** Causes serious eye damage.

**Respiratory or Skin Sensitization Product** Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity Product** Based on available data, the classification criteria are not met.

**Carcinogenicity Product** Based on available data, the classification criteria are not met.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		12/40

**Reproductive toxicity**  
**Product** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**  
**Product** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**  
**Product** Based on available data, the classification criteria are not met.

**Aspiration Hazard**  
**Product** Not applicable to gases and gas mixtures..

**SECTION 12: Ecological information**

**General information:** Not applicable

**12.1 Toxicity**

**Acute toxicity**  
**Product** No ecological damage caused by this product.

**12.2 Persistence and Degradability**

**Product** Not applicable to gases and gas mixtures..

**12.3 Bioaccumulative potential**

**Product** The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil**

**Product** Because of its high volatility, the product is unlikely to cause ground or water pollution.

Sulphur dioxide

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB assessment**

**Product** Not classified as PBT or vPvB.

**12.6 Other adverse effects:**

No ecological damage caused by this product.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		13/40

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**General information:** Must not be discharged to atmosphere. Consult supplier for specific recommendations.

**Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

**European Waste Codes**

**Container:** 16 05 04\*: Gases in pressure containers (including halons) containing dangerous substances.

**SECTION 14: Transport information**

**ADR**

14.1 UN Number:	UN 1079
14.2 UN Proper Shipping Name:	SULPHUR DIOXIDE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
Hazard No. (ADR):	268
Tunnel restriction code:	(C/D)
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-

**RID**

14.1 UN Number:	UN 1079
14.2 UN Proper Shipping Name	SULPHUR DIOXIDE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		14/40

**IMDG**

14.1 UN Number:	UN 1079
14.2 UN Proper Shipping Name:	SULPHUR DIOXIDE
14.3 Transport Hazard Class(es)	
Class:	2.3
Label(s):	2.3, 8
EmS No.:	F-C, S-U
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-

**IATA**

14.1 UN Number:	UN 1079
14.2 Proper Shipping Name:	Sulphur dioxide
14.3 Transport Hazard Class(es):	
Class:	2.3
Label(s):	-
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Forbidden.
Cargo aircraft only:	Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

**SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

**EU Regulations**

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 15/40

Classification	Lower-tier Requirements	Upper-tier Requirements
H2: ACUTE TOXIC (Category 2, all exposure routes; Category 3, inhalation)	50 t	200 t

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Sulphur dioxide	7446-09-5	100%

**National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

Revision Information: Not relevant.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013 Version: 1.1 SDS No.: 000010021800  
 Last revised date: 11.02.2022 16/40

**Key literature references and sources for data:**

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:  
 Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).  
 European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.  
 European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>  
 European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.  
 International Programme on Chemical Safety (<http://www.inchem.org/>)  
 ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.  
 Matheson Gas Data Book, 7th Edition.  
 National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.  
 The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).  
 The European Chemical Industry Council (CEFIC) ERICards.  
 United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)  
 Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).  
 Substance specific information from suppliers.  
 Details given in this document are believed to be correct at the time of publication.

**Wording of the H-statements in section 2 and 3**

H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

**Training information:** Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

**Classification according to Regulation (EC) No 1272/2008 as amended.**

Press. Gas Liq. Gas, H280  
 Acute Tox. 3, H331  
 Skin Corr. 1B, H314  
 Eye Dam. 1, H318





**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date:	16.01.2013	Version: 1.1	SDS No.: 000010021800
Last revised date:	11.02.2022		17/40

**Other information:** Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**Last revised date:** 11.02.2022

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 18/40

# Annex to the extended Safety Data Sheet (eSDS)

**Content**

Exposure Scenario 1)	Industrial:, Formulation of mixtures in pressure receptacles, Laboratory use, Use of gas to manufacture pharmaceutical products.
Exposure Scenario 2)	Industrial:, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating
Exposure Scenario 3)	Professional:, Refilling of refrigeration equipment

**Exposure Scenario 1)**

Exposure Scenario worker

1.Industrial:, Formulation of mixtures in pressure receptacles, Laboratory use, Use of gas to manufacture pharmaceutical products.

**List of use descriptors**

Sector(s) of use	SU9: Manufacture of fine chemicals SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals PC29: Pharmaceuticals

Name of contributing environmental scenario and corresponding ERC	<u>Industrial use:</u> ERC2: Formulation into mixture  ERC6a: Use of intermediate  ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
---	--

Contributing Scenarios	<u>Industrial use:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions  PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent
------------------------	---



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 19/40

	containment conditions  PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities  PROC15: Use as laboratory reagent
--	---

**2.1. Contributing exposure scenario controlling environmental exposure for:** Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Use of gas to manufacture pharmaceutical products.

**Product characteristics**

<b>Concentration of the substance in a mixture:</b>	Covers percentage substance in the product up to 100 %.
---	---

<b>Physical form of the product</b>	See section 9 of the SDS.
-------------------------------------	---------------------------

<b>Viscosity:</b>	
<b>Kinematic viscosity:</b>	No data available.
<b>Dynamic viscosity:</b>	0,012 mPa.s (18 °C)

**Amounts used**

<b>Regional use tonnage:</b>	80000 tonnes/yr
------------------------------	-----------------

**Frequency and duration of use**

<b>Batch process:</b>	365 Emission days
<b>Continuous process:</b>	not relevant

**Environment factors not influenced by risk management**

**Other given operational conditions affecting environmental exposure**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 20/40

Other relevant operational conditions	not relevant
---------------------------------------	--------------

**Risk management measures (RMM)**

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet (Environmental exposure controls).

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**

Air	Handle substance within a closed system. Effectiveness: 98 %.
Soil	not relevant
Water	not relevant
Sediment:	not relevant
Remarks:	not relevant

**Organisational measures to prevent/limit release from site:**

none

**Conditions and measures related to sewage treatment plant**

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 21/40

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Additional good practice advice beyond the REACH Chemical Safety Report**

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Use of gas to manufacture pharmaceutical products.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC15: Use as laboratory reagent
---------------------	---

**Product characteristics**

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	3271 hPa
Process temperature:	20 °C
Remarks	not relevant

**Amounts used**

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 22/40

**Frequency and duration of use**

	Use duration:	Frequency of use:	Remarks
Exposure time	<= 8 h		
Exposure duration		5 days per week	

**Human factors not influenced by risk management**

This information is not available.

**Other given operational conditions affecting workers exposure**

Other relevant operational conditions: . See section 8 of the SDS.

**Risk management measures (RMM)**

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet

**Technical conditions and measures to control dispersion from source towards the worker**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).				Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).				Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
Provide a good standard of controlled ventilation (5 to 10	Ensure that direct skin contact is avoided.			Transfer of substance or mixture (charging and discharging) at dedicated facilities



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 23/40

air changes per hour).				
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).	Ensure that direct skin contact is avoided.			Use as laboratory reagent

**Organisational measures to prevent/limit releases, dispersion and exposure**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

**Conditions and measures related to personal protection, hygiene and health evaluation**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

**Additional good practice advice beyond the REACH Chemical Safety Report**

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out. Ensure operatives are trained to minimise exposure Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

**3. Exposure estimation**

**Environment:**

Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfiling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Use of gas to manufacture pharmaceutical products.:

ERC2, ERC6a, ERC8a:

Compartment	PEC	RCR	Method	Remarks
freshwater	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
-------------	-----	-----	--------	---------



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 24/40

freshwater - intermittent	mg/l	< 1	Not applicable	No hazard identified
---------------------------	------	-----	----------------	----------------------

Compartment	PEC	RCR	Method	Remarks
marine water	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine water - intermittent	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Sewage treatment plant	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
freshwater sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Soil	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Air	mg/m <sup>3</sup>	< 1	Not applicable	No hazard identified

Health:





## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

## Sulfur dioxide

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
25/40

Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Use of gas to manufacture pharmaceutical products.:

PROC1, PROC2, PROC3:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use.	0,648 mg/m <sup>3</sup>	0,24	MEASE	none

PROC8b, PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use.	1,08 mg/m <sup>3</sup>	0,4	MEASE	none

PROC1, PROC2, PROC3, PROC8b, PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC1, PROC2, PROC3, PROC8b, PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 26/40

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ebrc.de/ebrc/ebrc-mease.php>

**Exposure Scenario 2)**

Exposure Scenario worker

1. Industrial:, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating

List of use descriptors	
Sector(s) of use	SU9: Manufacture of fine chemicals  SU13: Manufacture of other non-metallic mineral products, e.g. plasters, cement  SU14: Manufacture of basic metals, including alloys  SU15: Manufacture of fabricated metal products, except machinery and equipment  SU23: Electricity, steam, gas water supply and sewage treatment
Product categories [PC]:	PC14: Metal surface treatment products  PC21: Laboratory chemicals  PC37: Water treatment chemicals  PC15: Non-metal surface treatment products
Name of contributing environmental scenario and corresponding ERC	<u>Industrial use:</u> ERC6a: Use of intermediate  ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)  ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
Contributing Scenarios	<u>Industrial use:</u> PROC1: Chemical production or refinery in closed process without



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 27/40

	likelihood of exposure or processes with equivalent containment conditions  PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities  PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
--	---

**2.1. Contributing exposure scenario controlling environmental exposure for:** Industrial use, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating

**Product characteristics**

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,012 mPa.s (18 °C)

**Amounts used**

Regional use tonnage:	80000 tonnes/yr
-----------------------	-----------------

**Frequency and duration of use**

Batch process:	365 Emission days
Continuous process:	not relevant

**Environment factors not influenced by risk management**

**Other given operational conditions affecting environmental exposure**

Other relevant operational conditions	not relevant
---------------------------------------	--------------

**Risk management measures (RMM)**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 28/40

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet (Environmental exposure controls).

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**

Air	Handle substance within a closed system. Effectiveness: 98 %.
Soil	not relevant
Water	not relevant
Sediment:	not relevant
Remarks:	not relevant

**Organisational measures to prevent/limit release from site:**

none

**Conditions and measures related to sewage treatment plant**

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Fraction of used amount transferred to external waste treatment:



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 29/40

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Additional good practice advice beyond the REACH Chemical Safety Report**

Ensure operatives are trained to minimise releases

**2.2. Contributing exposure scenario controlling worker exposure for: Industrial use, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating**

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
---------------------	--

**Product characteristics**

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
-------------------------------	---------------------------

Vapour pressure:	3271 hPa
------------------	----------

Process temperature:	20 °C
----------------------	-------

Remarks	not relevant
---------	--------------

**Amounts used**

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.

**Frequency and duration of use**

	Use duration:	Frequency of use:	Remarks
Exposure time	<= 8 h		
Exposure duration		5 days per week	

**Human factors not influenced by risk management**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
30/40

This information is not available.

**Other given operational conditions affecting workers exposure**

Other relevant operational conditions: . See section 8 of the SDS.

**Risk management measures (RMM)**

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet

**Technical conditions and measures to control dispersion from source towards the worker**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Handle product within a closed system.				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Provide a good standard of controlled ventilation (5 to 10 air changes per hour): 90 %	Ensure that direct skin contact is avoided.			Transfer of substance or mixture (charging and discharging) at dedicated facilities
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour): 90 %	Ensure that direct skin contact is avoided.			Manufacturing and processing of minerals and/or metals at substantially elevated temperature

**Organisational measures to prevent/limit releases, dispersion and exposure**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
31/40

**Conditions and measures related to personal protection, hygiene and health evaluation**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

**Additional good practice advice beyond the REACH Chemical Safety Report**

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out. Ensure operatives are trained to minimise exposure Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

**3. Exposure estimation**

**Environment:**

Industrial use, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating:

ERC6a, ERC6b, ERC8b:

Compartment	PEC	RCR	Method	Remarks
freshwater	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
freshwater - intermittent	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine water	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine water - intermittent	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Sewage treatment	mg/l	< 1	Not applicable	No hazard identified



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
32/40

plant				
-------	--	--	--	--

Compartment	PEC	RCR	Method	Remarks
freshwater sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Soil	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Air	mg/m <sup>3</sup>	< 1	Not applicable	No hazard identified

**Health:**

Industrial use, Using gas for metal treatment., Using gas as feedstock in chemical processes., Water treatment., Glass coating:

**PROC1:**

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use.	0,648 mg/m <sup>3</sup>	0,24	MEASE	none

**PROC8b, PROC22:**

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use.	1,08 mg/m <sup>3</sup>	0,4	MEASE	none

**PROC1, PROC8b, PROC22:**





**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 33/40

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC1, PROC8b, PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**

Check that RMMs and OCs are as described above or of equivalent efficiency. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ebrc.de/ebrc/ebrc-mease.php>

Exposure Scenario 3)

Exposure Scenario worker

**1. Professional:, Refilling of refrigeration equipment**

List of use descriptors	
Sector(s) of use	
Product categories [PC]:	PC16: Heat transfer fluids

Name of contributing environmental scenario and corresponding ERC	Professional use: ERC9a: Widespread use of functional fluid (indoor)
---	---



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 34/40

	ERC9b: Widespread use of functional fluid (outdoor)
--	---

<b>Contributing Scenarios</b>	<u>Professional use:</u> PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
-------------------------------	---

**2.1. Contributing exposure scenario controlling environmental exposure for: Professional use, Refrigerant., Refilling of refrigeration equipment**

**Product characteristics**

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

<b>Viscosity:</b>	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,012 mPa.s (18 °C)

**Amounts used**

Regional use tonnage:	80000 tonnes/yr
-----------------------	-----------------

**Frequency and duration of use**

Batch process:	365 Emission days
Continuous process:	not relevant

**Environment factors not influenced by risk management**

**Other given operational conditions affecting environmental exposure**

Other relevant operational conditions	not relevant
---------------------------------------	--------------

**Risk management measures (RMM)**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 35/40

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet (Environmental exposure controls).

**Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil**

Air	Handle substance within a closed system. Effectiveness: 98 %.
Soil	not relevant
Water	not relevant
Sediment:	not relevant
Remarks:	not relevant

**Organisational measures to prevent/limit release from site:**

none

**Conditions and measures related to sewage treatment plant**

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

**Conditions and measures related to external treatment of waste for disposal**

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

**Conditions and measures related to external recovery of waste**

Fraction of used amount transferred to external waste treatment:



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 36/40

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

**Additional good practice advice beyond the REACH Chemical Safety Report**

Ensure operatives are trained to minimise releases

**2.2. Contributing exposure scenario controlling worker exposure for: Professional use, Refrigerant., Refilling of refrigeration equipment**

Process Categories:	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
---------------------	---

**Product characteristics**

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
-------------------------------	---------------------------

Vapour pressure:	3271 hPa
------------------	----------

Process temperature:	20 °C
----------------------	-------

Remarks	not relevant
---------	--------------

**Amounts used**

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.

**Frequency and duration of use**

	Use duration:	Frequency of use:	Remarks
Exposure time	<= 8 h		
Exposure duration		5 days per week	

**Human factors not influenced by risk management**

This information is not available.

**Other given operational conditions affecting workers exposure**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 37/40

**Other relevant operational conditions:** . See section 8 of the SDS.

**Risk management measures (RMM)**

**Technical conditions and measures at process level (source) to prevent release**

See section 8 of the safety data sheet

**Technical conditions and measures to control dispersion from source towards the worker**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of controlled ventilation (5 to 10 air changes per hour): 90 %	Ensure that direct skin contact is avoided.			Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

**Organisational measures to prevent/limit releases, dispersion and exposure**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

**Conditions and measures related to personal protection, hygiene and health evaluation**

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

**Additional good practice advice beyond the REACH Chemical Safety Report**

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out. Ensure operatives are trained to minimise exposure Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

**3. Exposure estimation**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 38/40

**Environment:**

Professional use, Refrigerant., Refilling of refrigeration equipment:

ERC9a, ERC9b:

Compartment	PEC	RCR	Method	Remarks
freshwater	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
freshwater - intermittent	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine water	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine water - intermittent	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Sewage treatment plant	mg/l	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
freshwater sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
marine sediment	mg/kg dry weight	< 1	Not applicable	No hazard identified

Compartment	PEC	RCR	Method	Remarks
Soil	mg/kg	< 1	Not applicable	No hazard identified



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
 Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
 39/40

	dry weight			
--	------------	--	--	--

Compartment	PEC	RCR	Method	Remarks
Air	mg/m <sup>3</sup>	< 1	Not applicable	No hazard identified

Health:  
 Professional use, Refrigerant., Refilling of refrigeration equipment:  
 PROC8a:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor/Outdoor use.	2,16 mg/m <sup>3</sup>	0,8	MEASE	none

PROC8a:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC8a:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic				MEASE	Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

**4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES**



**SAFETY DATA SHEET**

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

**Sulfur dioxide**

Issue Date: 16.01.2013  
Last revised date: 11.02.2022

Version: 1.1

SDS No.: 000010021800  
40/40

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ebrc.de/ebrc/ebrc-mease.php>