

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
1/16

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**

**Product name:** Chlorine  
**Trade name:** Gasart 464 Chlor 2.8, Gasart 465 Chlor 5.0, Chlor 4.0

**Additional identification**

**Chemical name:** Chlorine  
**Chemical formula:** Cl<sub>2</sub>  
**INDEX No.** 017-001-00-7  
**CAS-No.** 7782-50-5  
**EC No.** 231-959-5  
**REACH Registration No.** 01-2119486560-35

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses:** Industrial and professional. Perform risk assessment prior to use.  
Bleaching agent.  
Use as an Intermediate (transported, on-site isolated).  
Use for electronic component manufacture.  
Use of gas to manufacture pharmaceutical products.  
Using gas alone or in mixtures for the calibration of analysis equipment.  
Using gas as feedstock in chemical processes.  
Using gas for metal treatment.  
Water treatment.  
Formulation of mixtures with gas in pressure receptacles.  
Biocidal uses.

**Uses advised against** Consumer use.

**1.3 Details of the supplier of the safety data sheet****Supplier**

Linde Gas GmbH  
Carl-von-Linde-Platz 1  
A-4651 Stadl-Paura

**Telephone:** +43 50 4273**E-mail:** office@at.linde-gas.com

**1.4 Emergency telephone number:** Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

## SAFETY DATA SHEET

## Chlorine

Issue Date: 16.01.2013  
 Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
 2/16

## SECTION 2: Hazards identification

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008 as amended.

## Physical Hazards

Oxidizing gases	Category 1	H270: May cause or intensify fire; oxidizer.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

## Health Hazards

Acute toxicity (Inhalation - gas)	Category 2	H330: Fatal if inhaled.
Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation.

## Environmental Hazards

Acute hazards to the aquatic environment	Category 1	H400: Very toxic to aquatic life.
Chronic hazards to the aquatic environment	Category 1	H410: Very toxic to aquatic life with long lasting effects.

## 2.2 Label Elements

Contains:

Chlorine



Signal Words:

Danger

Hazard Statement(s):

H270: May cause or intensify fire; oxidizer.  
 H280: Contains gas under pressure; may explode if heated.  
 H330: Fatal if inhaled.  
 H315: Causes skin irritation.  
 H319: Causes serious eye irritation.  
 H410: Very toxic to aquatic life with long lasting effects.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
3/16

**Precautionary Statements**

- Prevention:** P220: Keep/Store away from combustible materials.  
P244: Keep valves and fittings free from oil and grease.  
P260: Do not breathe gas/vapors.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.
- Response:** P302+P352: IF ON SKIN: Wash with plenty of water.  
P332+P313: If skin irritation occurs: Get medical advice/attention.  
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.  
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Get immediate medical advice/attention.  
P370+P376: In case of fire: Stop leak if safe to do so.
- Storage:** P403: Store in a well-ventilated place.  
P405: Store locked up.
- Disposal:** None.

**Supplemental label information**

EUH071: Corrosive to the respiratory tract.

**2.3 Other hazards:** Contact with evaporating liquid may cause frostbite or freezing of skin.

**SECTION 3: Composition/information on ingredients****3.1 Substances**

<b>Chemical name</b>	Chlorine
<b>INDEX No.:</b>	017-001-00-7
<b>CAS-No.:</b>	7782-50-5
<b>EC No.:</b>	231-959-5
<b>REACH Registration No.:</b>	01-2119486560-35
<b>Purity:</b>	100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

**Trade name:** Gasart 464 Chlor 2.8, Gasart 465 Chlor 5.0, Chlor 4.0

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
4/16

**SECTION 4: First aid measures**

**General:** Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

**Inhalation:** Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

**Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Contact with evaporating liquid may cause frostbite or freezing of skin.

**Ingestion:** Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Hazards:** Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

**Treatment:** Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

**SECTION 5: Firefighting measures**

**General Fire Hazards:** Heat may cause the containers to explode.

**5.1 Extinguishing media**

**Suitable extinguishing media:** Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.

**Unsuitable extinguishing media:** None.

**5.2 Special hazards arising from the substance or mixture:** Fire or excessive heat may produce hazardous decomposition products. Supports combustion.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
5/16

**5.3 Advice for firefighters****Special fire fighting procedures:**

In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

**Special protective equipment for fire-fighters:**

Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.  
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:**

Evacuate area. In case of leakage, eliminate all ignition sources. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**6.2 Environmental Precautions:**

Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

**6.3 Methods and material for containment and cleaning up:**

Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.

**6.4 Reference to other sections:**

Refer to sections 8 and 13.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
6/16

**SECTION 7: Handling and storage:****7.1 Precautions for safe handling:**

Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep equipment free from oil and grease. Open valve slowly to avoid pressure shock. Use only oxygen approved lubricants and sealants. Use only with equipment cleaned for oxygen service and rated for the pressure. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**7.2 Conditions for safe storage, including any incompatibilities:**

Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material. Avoid asphalted locations for storage, transfer and use (ignition risk if spilt). Segregate from flammable gases and other flammable materials being stored.

**7.3 Specific end use(s):**

None.

## SAFETY DATA SHEET

## Chlorine

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
7/16

## SECTION 8: Exposure controls/personal protection

## 8.1 Control Parameters

## Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Chlorine	STEL	0,5 ppm 1,5 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	STEL	0,5 ppm 1,5 mg/m <sup>3</sup>	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	0,5 ppm 1,5 mg/m <sup>3</sup>	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (12 2011)
	MAK CEIL	0,5 ppm 1,5 mg/m <sup>3</sup>	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

## DNEL-Values

Critical component	Type	Value	Remarks
Chlorine	Worker - inhalative, long-term - systemic	0,75 mg/m <sup>3</sup>	-
	Worker - inhalative, short-term - systemic	1,5 mg/m <sup>3</sup>	-
	Worker - inhalative, long-term - local	0,75 mg/m <sup>3</sup>	-
	Worker - inhalative, short-term - local	1,5 mg/m <sup>3</sup>	-
	Worker - dermal, long-term - local	0,5 % wt	-

## PNEC-Values

Critical component	Type	Value	Remarks
Chlorine	Aquatic (freshwater)	0,21 µg/l	-
	Aquatic (marine water)	0,042 µg/l	-
	Sewage treatment plant	0,03 mg/l	-

## 8.2 Exposure controls

## Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of oxidizing gases may be released. Avoid oxygen rich (>23,5%) atmospheres. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
8/16

**Individual protection measures, such as personal protective equipment**

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
- Hand Protection:** Wear working gloves while handling containers  
Guideline: EN 388 Protective gloves against mechanical risks.  
Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.  
For short term use:  
Material: Chloroprene rubber.  
Break-through time: > 30 min  
Glove thickness: 0,4 mm  
For long term use:  
Material: Fluoroelastomer.  
Break-through time: > 480 min  
Glove thickness: 0,7 mm
- Body protection:** No special precautions.
- Other:** Wear safety shoes while handling containers  
Guideline: ISO 20345 Personal protective equipment - Safety footwear.
- Respiratory Protection:** Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.  
Material: Filter B  
Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.  
Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.



**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
9/16

<b>Thermal hazards:</b>	No precautionary measures are necessary.
<b>Hygiene measures:</b>	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
<b>Environmental exposure controls:</b>	For waste disposal, see section 13 of the SDS.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

<b>Physical state:</b>	Gas
<b>Form:</b>	Liquefied gas
<b>Color:</b>	Greenish yellow
<b>Odor:</b>	Pungent irritating odor.
<b>Odor Threshold:</b>	Odor threshold is subjective and is inadequate to warn of over exposure.
<b>pH:</b>	If dissolved in water pH-value will be affected.
<b>Melting Point:</b>	-101 °C
<b>Boiling Point:</b>	-34 °C
<b>Sublimation Point:</b>	not applicable.
<b>Critical Temp. (°C):</b>	144,0 °C
<b>Flash Point:</b>	Not applicable to gases and gas mixtures.
<b>Evaporation Rate:</b>	Not applicable to gases and gas mixtures.
<b>Flammability (solid, gas):</b>	This product is not flammable.
<b>Flammability Limit - Upper (%):</b>	not applicable.
<b>Flammability Limit - Lower (%):</b>	not applicable.
<b>Vapor pressure:</b>	6.780 hPa (20 °C) Experimental result, Key study
<b>Vapor density (air=1):</b>	2,5
<b>Relative density:</b>	No data available.
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	5,1 g/l (30 °C)
<b>Partition coefficient (n-octanol/water):</b>	Not known.
<b>Autoignition Temperature:</b>	not applicable.
<b>Decomposition Temperature:</b>	Not known.
<b>Viscosity</b>	
<b>Kinematic viscosity:</b>	No data available.
<b>Dynamic viscosity:</b>	0,013 mPa.s (20 °C) Liquid Gas
<b>Explosive properties:</b>	Not applicable.

## SAFETY DATA SHEET

### Chlorine

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
10/16

**Oxidizing properties:** Oxidizing

**9.2 Other information:** Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

**Molecular weight:** 70,91 g/mol (Cl<sub>2</sub>)

### SECTION 10: Stability and reactivity

**10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.

**10.2 Chemical Stability:** Stable under normal conditions.

**10.3 Possibility of hazardous reactions:** Violently oxidises organic material. May react violently with combustible materials. May react violently with reducing agents.

**10.4 Conditions to avoid:** Avoid moisture in the installation.

**10.5 Incompatible Materials:** Moisture. Combustible materials Reducing agents. Keep equipment free from oil and grease. For material compatibility see latest version of ISO-11114. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (>30 bar) oxygen lines and equipment in case of combustion.

**10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

**General information:** None.

#### 11.1 Information on toxicological effects

**Acute toxicity - Oral Product** Based on available data, the classification criteria are not met.

Chlorine LD 50 (Rat): 8.910 mg/kg Remarks: Read-across from supporting substance (structural analogue or surrogate), Supporting study

**Acute toxicity - Dermal Product** Based on available data, the classification criteria are not met.

Chlorine LD 50 (Rabbit): > 20.000 mg/kg Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
11/16

**Acute toxicity - Inhalation****Product**

Fatal if inhaled.

Chlorine

LC 50 (Rat, 1 h): 293 ppm  
LC 50 (Rat, 4 h): 146,5 ppm Remarks: Delayed fatal pulmonary oedema possible.

**Repeated dose toxicity**

Chlorine

NOAEL (Monkey(Female, Male), Inhalation, 1 yr): 0,5 ppm(m) Inhalation  
Experimental result, Key study

**Skin Corrosion/Irritation****Product**

Causes skin irritation.

Chlorine

Severely irritating to skin.

**Serious Eye Damage/Eye Irritation****Product**

Causes serious eye irritation.

Chlorine

Severely irritating to eyes.

**Respiratory or Skin Sensitization****Product**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity****Product**

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure****Product**

May cause respiratory irritation.

Chlorine

Route of Exposure: Inhalation - vapor  
Severe corrosion to the respiratory tract at high concentrations.

**Specific Target Organ Toxicity - Repeated Exposure****Product**

Based on available data, the classification criteria are not met.

**Aspiration Hazard****Product**

Not applicable to gases and gas mixtures..

## SAFETY DATA SHEET

## Chlorine

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
12/16

**SECTION 12: Ecological information**

**General information:** Avoid release to the environment. Product is not allowed to be discharged into ground water or the aquatic environment.

**12.1 Toxicity****Acute toxicity  
Product**

Very toxic to aquatic life with long lasting effects.

**Acute toxicity - Fish  
Chlorine**

LC 50 (Various, 96 h): 0,032 mg/l (flow-through) Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study  
LC 50 (Fish, 96 h): 0,032 mg/l

**Acute toxicity - Aquatic Invertebrates**

Chlorine

NOAEL (Daphnia magna, 48 h): 50 µg/l (flow-through) Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study

**Toxicity to microorganisms**

Chlorine

EC 50 (Algae (Scenedesmus subspicatus), 72 h): 0,001 mg/l

**Chronic Toxicity - Aquatic Invertebrates**

Chlorine

LOAEL (V. iris (Ambloplites rupestris) and Cottus carolinae (E. capsaeformis), 21 d): 30 µg/l (flow-through) Read-across from supporting substance (structural analogue or surrogate), Supporting study

**Additional ecological information**

None.

**12.2 Persistence and Degradability****Product**

Not applicable to gases and gas mixtures..

**Biodegradation**

Inorganic The product is not readily biodegradable.

**12.3 Bioaccumulative potential****Product**

The substance has no potential for bioaccumulation.

**12.4 Mobility in soil****Product**

The substance has low mobility in soil.

**12.5 Results of PBT and vPvB****assessment****Product**

Not classified as PBT or vPvB.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
13/16

**12.6 Other adverse effects:****Other Ecological Information**

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

**General information:** Must not be discharged to atmosphere. Consult supplier for specific recommendations.

**Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

**European Waste Codes**

**Container:** 16 05 04\*: Gases in pressure containers (including halons) containing dangerous substances.

**SECTION 14: Transport information****ADR**

14.1 UN Number: UN 1017  
14.2 UN Proper Shipping Name: CHLORINE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.3, 5.1, 8  
Hazard No. (ADR): 265  
Tunnel restriction code: (C/D)  
14.4 Packing Group: -  
14.5 Environmental hazards: Environmentally Hazardous  
14.6 Special precautions for user: -

**RID**

14.1 UN Number: UN 1017  
14.2 UN Proper Shipping Name: CHLORINE  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.3, 5.1, 8  
14.4 Packing Group: -  
14.5 Environmental hazards: Environmentally Hazardous  
14.6 Special precautions for user: -

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
14/16

**IMDG**

14.1 UN Number: UN 1017  
14.2 UN Proper Shipping Name: CHLORINE  
14.3 Transport Hazard Class(es)  
Class: 2.3  
Label(s): 2.3, 5.1, 8  
EmS No.: F-C, S-U  
14.3 Packing Group: -  
14.5 Environmental hazards: Marine Pollutant  
14.6 Special precautions for user: -

**IATA**

14.1 UN Number: UN 1017  
14.2 Proper Shipping Name: Chlorine  
14.3 Transport Hazard Class(es):  
Class: 2.3  
Label(s): -  
14.4 Packing Group: -  
14.5 Environmental hazards: Environmentally Hazardous  
14.6 Special precautions for user: -  
Other information  
Passenger and cargo aircraft: Forbidden.  
Cargo aircraft only: Forbidden.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:**

## SAFETY DATA SHEET

## Chlorine

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
15/16

Chemical name	CAS-No.	Concentration
Chlorine	7782-50-5	100%

**Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:**

Chemical name	CAS-No.	Concentration
Chlorine	7782-50-5	100%

**National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

**15.2 Chemical safety assessment:** CSA has been carried out.

**SECTION 16: Other information**

**Revision Information:** Not relevant.

**Key literature references and sources for data:**

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)  
(<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances  
<http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

**SAFETY DATA SHEET****Chlorine**

Issue Date: 16.01.2013  
Last revised date: 12.09.2018

Version: 1.2

SDS No.: 000010021781  
16/16

**Wording of the H-statements in section 2 and 3**

H270	May cause or intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Training information:** Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard. Ensure operators understand the hazards.

**Classification according to Regulation (EC) No 1272/2008 as amended.**

Ox. Gas 1, H270  
Press. Gas Liq. Gas, H280  
Acute Tox. 2, H330  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT SE 3, H335  
Aquatic Acute 1, H400  
Aquatic Chronic 1, H410

**Other information:** Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**Last revised date:** 12.09.2018

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.