

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
1/13**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Product name:** Hydrogen, compressed**Trade name:** Gasart 318 Wasserstoff 3.0, Gasart 320 Wasserstoff 5.0, Gasart 323 Wasserstoff 6.0**Additional identification****Chemical name:** Hydrogen**Chemical formula:** H<sub>2</sub>**INDEX No.** 001-001-00-9**CAS-No.** 1333-74-0**EC No.** 215-605-7**REACH Registration No.** Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.**1.2 Relevant identified uses of the substance or mixture and uses advised against****Identified uses:** Industrial and professional. Perform risk assessment prior to use.  
Aerosol propellant. Balance gas for mixtures. Calibration gas. Carrier gas.  
Chemical synthesis. Combustion, melting and cutting processes. Fuel cells.  
Fuel gas for welding, cutting, heating, brazing and soldering applications.  
Laboratory use. Laser gas. Process gas. Test gas.  
Consumer use.**Uses advised against** Fuel gas Propellant gas. Shielding gas in gas welding.  
This gas is not intended to be filled into balloons for consumer use and advertising purposes because of the danger of explosion. Do not inflate commercial balloons.**1.3 Details of the supplier of the safety data sheet****Supplier**Linde Gas GmbH  
Carl-von-Linde-Platz 1  
A-4651 Stadl-Paura**Telephone:** +43 50 4273**E-mail:** office@at.linde-gas.com**1.4 Emergency telephone number:** Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
2/13**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 as amended.

**Physical Hazards**

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Compressed gas	H280: Contains gas under pressure; may explode if heated.

**2.2 Label Elements****Signal Words:** Danger**Hazard Statement(s):** H220: Extremely flammable gas.  
H280: Contains gas under pressure; may explode if heated.**Precautionary Statements**

<b>Prevention:</b>	P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>Response:</b>	P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381: In case of leakage, eliminate all ignition sources.
<b>Storage:</b>	P403: Store in a well-ventilated place.
<b>Disposal:</b>	None.

**2.3 Other hazards:** None.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
3/13**SECTION 3: Composition/information on ingredients****3.1 Substances**

<b>Chemical name</b>	Hydrogen
<b>INDEX No.:</b>	001-001-00-9
<b>CAS-No.:</b>	1333-74-0
<b>EC No.:</b>	215-605-7
<b>REACH Registration No.:</b>	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.
<b>Purity:</b>	100% The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
<b>Trade name:</b>	Gasart 318 Wasserstoff 3.0, Gasart 320 Wasserstoff 5.0, Gasart 323 Wasserstoff 6.0

**SECTION 4: First aid measures**

**General:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**4.1 Description of first aid measures**

**Inhalation:** In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

**Eye contact:** Adverse effects not expected from this product.

**Skin Contact:** Adverse effects not expected from this product.

**Ingestion:** Ingestion is not considered a potential route of exposure.

**4.2 Most important symptoms and effects, both acute and delayed:** Respiratory arrest.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Hazards:** None.

**Treatment:** None.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**

Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
4/13

**SECTION 5: Firefighting measures**

**General Fire Hazards:** Heat may cause the containers to explode.

**5.1 Extinguishing media**

**Suitable extinguishing media:** Water. Dry powder. Foam.

**Unsuitable extinguishing media:** Carbon Dioxide.

**5.2 Special hazards arising from the substance or mixture:** None.

**Hazardous Combustion Products:** None.

**5.3 Advice for firefighters**

**Special fire fighting procedures:** In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:** Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

**6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so.

**6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation. Eliminate sources of ignition.

**6.4 Reference to other sections:** Refer to sections 8 and 13.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**

Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
5/13

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling:**

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

**7.2 Conditions for safe storage, including any incompatibilities:**

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

**7.3 Specific end use(s):**

None.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
6/13**SECTION 8: Exposure controls/personal protection****8.1 Control Parameters****Occupational Exposure Limits**

None of the components have assigned exposure limits.

**8.2 Exposure controls****Appropriate engineering controls:**

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

**Individual protection measures, such as personal protective equipment****General information:**

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.

**Eye/face protection:**

Wear eye protection to EN 166 when using gases.  
Guideline: EN 166 Personal Eye Protection.

**Skin protection****Hand Protection:**

Wear working gloves while handling containers  
Guideline: EN 388 Protective gloves against mechanical risks.

**Body protection:**

Wear fire resistant or flame retardant clothing.  
Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame --  
General recommendations for selection, care and use of protective clothing.

**Other:**

Wear safety shoes while handling containers  
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

**Respiratory Protection:**

Not required.

**Thermal hazards:**

No precautionary measures are necessary.

**Hygiene measures:**

Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
7/13**Environmental exposure controls:**

For waste disposal, see section 13 of the SDS.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

<b>Physical state:</b>	Gas
<b>Form:</b>	Compressed gas
<b>Color:</b>	Colorless
<b>Odor:</b>	Odorless
<b>Odor Threshold:</b>	Odor threshold is subjective and is inadequate to warn of over exposure.
<b>pH:</b>	not applicable.
<b>Melting Point:</b>	-259,2 °C
<b>Boiling Point:</b>	-253 °C
<b>Sublimation Point:</b>	not applicable.
<b>Critical Temp. (°C):</b>	-240,0 °C
<b>Flash Point:</b>	Not applicable to gases and gas mixtures.
<b>Evaporation Rate:</b>	Not applicable to gases and gas mixtures.
<b>Flammability (solid, gas):</b>	Flammable Gas
<b>Flammability Limit - Upper (%):</b>	77 %(V)
<b>Flammability Limit - Lower (%):</b>	4 %(V)
<b>Vapor pressure:</b>	No reliable data available.
<b>Vapor density (air=1):</b>	0,069
<b>Relative density:</b>	0,07
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	1,62 mg/l
<b>Partition coefficient (n-octanol/water):</b>	Not known.
<b>Autoignition Temperature:</b>	560 °C
<b>Decomposition Temperature:</b>	Not known.
<b>Viscosity</b>	
<b>Kinematic viscosity:</b>	No data available.
<b>Dynamic viscosity:</b>	No data available.
<b>Explosive properties:</b>	Not applicable.
<b>Oxidizing properties:</b>	not applicable.

**9.2 Other information:**

None.

**Molecular weight:**2,02 g/mol (H<sub>2</sub>)

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
8/13**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity:</b>	No reactivity hazard other than the effects described in sub-section below.
<b>10.2 Chemical Stability:</b>	Stable under normal conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
<b>10.4 Conditions to avoid:</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>10.5 Incompatible Materials:</b>	Air and oxidizers. For material compatibility see latest version of ISO-11114.
<b>10.6 Hazardous Decomposition Products:</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****General information:** None.**11.1 Information on toxicological effects**

<b>Acute toxicity - Oral Product</b>	Based on available data, the classification criteria are not met.
<b>Acute toxicity - Dermal Product</b>	Based on available data, the classification criteria are not met.
<b>Acute toxicity - Inhalation Product</b>	Based on available data, the classification criteria are not met.
<b>Skin Corrosion/Irritation Product</b>	Based on available data, the classification criteria are not met.
<b>Serious Eye Damage/Eye Irritation Product</b>	Based on available data, the classification criteria are not met.
<b>Respiratory or Skin Sensitization Product</b>	Based on available data, the classification criteria are not met.
<b>Germ Cell Mutagenicity Product</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity Product</b>	Based on available data, the classification criteria are not met.



**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
9/13**Reproductive toxicity****Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure****Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure****Product**

Based on available data, the classification criteria are not met.

**Aspiration Hazard****Product**

Not applicable to gases and gas mixtures..

**SECTION 12: Ecological information****12.1 Toxicity****Acute toxicity****Product**

No ecological damage caused by this product.

**12.2 Persistence and Degradability****Product**

Not applicable to gases and gas mixtures..

**12.3 Bioaccumulative potential****Product**

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil****Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB assessment****Product**

Not classified as PBT or vPvB.

**12.6 Other adverse effects:****Global Warming Potential**Global warming potential: 6  
Contains greenhouse gas(es). When discharged in large quantities may contribute to the greenhouse effect.

Hydrogen

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
10/13**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

**General information:** Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

**Disposal methods:** Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

**European Waste Codes**

**Container:** 16 05 04\*: Gases in pressure containers (including halons) containing dangerous substances.

**SECTION 14: Transport information****ADR**

14.1 UN Number: UN 1049  
14.2 UN Proper Shipping Name: HYDROGEN, COMPRESSED  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.1  
Hazard No. (ADR): 23  
Tunnel restriction code: (B/D)  
14.4 Packing Group: -  
14.5 Environmental hazards: not applicable  
14.6 Special precautions for user: -

**RID**

14.1 UN Number: UN 1049  
14.2 UN Proper Shipping Name: HYDROGEN, COMPRESSED  
14.3 Transport Hazard Class(es)  
Class: 2  
Label(s): 2.1  
14.4 Packing Group: -  
14.5 Environmental hazards: not applicable  
14.6 Special precautions for user: -

**SAFETY DATA SHEET**  
**Hydrogen, compressed**

Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
11/13

**IMDG**

14.1 UN Number: UN 1049  
14.2 UN Proper Shipping Name: HYDROGEN, COMPRESSED  
14.3 Transport Hazard Class(es)  
Class: 2.1  
Label(s): 2.1  
EmS No.: F-D, S-U  
14.3 Packing Group: -  
14.5 Environmental hazards: not applicable  
14.6 Special precautions for user: -

**IATA**

14.1 UN Number: UN 1049  
14.2 Proper Shipping Name: Hydrogen, compressed  
14.3 Transport Hazard Class(es):  
Class: 2.1  
Label(s): 2.1  
14.4 Packing Group: -  
14.5 Environmental hazards: not applicable  
14.6 Special precautions for user: -  
Other information  
Passenger and cargo aircraft: Forbidden.  
Cargo aircraft only: Forbidden.

**14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code:** not applicable

**Additional identification:** Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

<b>SECTION 15: Regulatory information</b>
---

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:**

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	100%

**SAFETY DATA SHEET**  
**Hydrogen, compressed**Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
12/13**Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:**

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	100%

**National Regulations**

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.  
This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

**15.2 Chemical safety assessment:** No Chemical Safety Assessment has been carried out.**SECTION 16: Other information****Revision Information:** Not relevant.**Key literature references and sources for data:**

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:  
Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).  
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.  
European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>  
European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.  
International Programme on Chemical Safety (<http://www.inchem.org/>)  
ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.  
Matheson Gas Data Book, 7th Edition.  
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.  
The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).  
The European Chemical Industry Council (CEFIC) ERICards.  
United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)  
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).  
Substance specific information from suppliers.  
Details given in this document are believed to be correct at the time of publication.

**SAFETY DATA SHEET**  
**Hydrogen, compressed**

Issue Date: 16.01.2013  
Last revised date: 26.11.2018

Version: 1.2

SDS No.: 000010021694  
13/13

**Wording of the H-statements in section 2 and 3**

H220 Extremely flammable gas.  
H280 Contains gas under pressure; may explode if heated.

**Training information:** Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

**Classification according to Regulation (EC) No 1272/2008 as amended.**

Flam. Gas 1, H220  
Press. Gas Compr. Gas, H280

**Other information:** Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**Last revised date:** 26.11.2018

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.