



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
1/46

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Hydrogen chloride, anhydrous

Trade name: Gasart 466 Chlorwasserstoff, Gasart 484 Chlorwasserstoff 5.0, Chlorwasserstoff 2.8, Chlorwasserstoff 4.5, Chlorwasserstoff 5.5

Additional identification

Chemical name: Hydrogen chloride
Chemical formula: HCl
INDEX No. 017-002-00-2
CAS-No. 7647-01-0
EC No. 231-595-7
REACH Registration No. 01-2119484862-27

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Use for electronic component manufacture.
Use gas as catalyst regenerator.
Use of gas to manufacture pharmaceutical products.
Using gas alone or in mixtures for the calibration of analysis equipment.
Using gas as feedstock in chemical processes.
Using gas for metal treatment.
Formulation of mixtures with gas in pressure receptacles.
Intermediate

Uses advised against Consumer use. Contact supplier for more information on uses. Uses other than those listed above are not supported.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273

E-mail: office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number UMC0: +49 89 220 61012 (German), +44 1865 407333 (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 2/46

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.
----------------------	---------------	---

Health Hazards

Acute toxicity (Inhalation - gas)	Category 3	H331: Toxic if inhaled.
Skin corrosion	Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage	Category 1	H318: Causes serious eye damage.

2.2 Label Elements

Contains: Hydrogen chloride



Signal Word: Danger

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.
 H331: Toxic if inhaled.
 H314: Causes severe skin burns and eye damage.

Precautionary Statements

General None.

Prevention: P260: Do not breathe gas/vapors.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.
 P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
 P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Storage: P403: Store in a well-ventilated place.
 P405: Store locked up.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013 Version: 3.1 SDS No.: 000010021725
 Last revised date: 23.02.2022 3/46

Disposal None.

Supplemental information

EUH071: Corrosive to the respiratory tract.

2.3 Other hazards Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name Hydrogen chloride
INDEX No.: 017-002-00-2
CAS-No.: 7647-01-0
EC No.: 231-595-7
REACH Registration No.: 01-2119484862-27
Purity: 100%
 The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name: Gasart 466 Chlorwasserstoff, Gasart 484 Chlorwasserstoff 5.0, Chlorwasserstoff 2.8, Chlorwasserstoff 4.5, Chlorwasserstoff 5.5

Chemical name	Chemical formula	Concentration	CAS-No.	REACH Registration No.	M-Factor:	Notes
Hydrogen chloride	HCl	100%	7647-01-0	01-2119484862-27	-	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 4/46

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Causes severe skin burns and eye damage. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013 Version: 3.1 SDS No.: 000010021725
 Last revised date: 23.02.2022 5/46

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: None that are more toxic than the product itself.

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
 Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections: Refer to sections 8 and 13.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		6/46

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities: Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 7/46

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Hydrogen chloride	TWA	5 ppm 8 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	STEL	10 ppm 15 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	MAK	5 ppm 8 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), as amended (04 2021)
	MAK CEIL	10 ppm 15 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), as amended (04 2021)

DNEL-Values

Critical component	Type	Value	Remarks
Hydrogen chloride	Workers - Inhalation, Local, long-term	8 mg/m ³	respiratory tract irritation
	Workers - Eyes, Local effect		Medium hazard (no threshold derived)
	Workers - Inhalation, Local, short-term	15 mg/m ³	respiratory tract irritation

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
8/46

Individual protection measures, such as personal protective equipment

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
- Hand Protection:** Guideline: EN 388 Protective gloves against mechanical risks.
Additional Information: Wear working gloves while handling containers
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
Additional Information: Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Material: Chloroprene rubber.
Break-through time: > 480 min
Glove thickness: 0,5 mm
- Body protection:** Keep suitable chemically resistant protective clothing readily available for emergency use.
Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.
- Other:** Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		9/46

Respiratory Protection: Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres

Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking. Material: Filter E

Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.

Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls: For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless to slight yellow
Odor:	Pungent
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	If dissolved in water pH-value will be affected.
Melting Point:	-114,22 °C Other, Not specified
Boiling Point:	-85 °C
Sublimation Point:	Not applicable.
Critical Temp. (°C):	51,4 °C
Flash Point:	Not applicable to gases and gas mixtures.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		10/46

Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	Not applicable.
Flammability Limit - Lower (%):	Not applicable.
Vapor pressure:	4.260 kPa (20 °C)
Vapor density (air=1):	1,3
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	720 g/l
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	When heated to decomp, emits toxic fumes of hydrogen chloride.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	Not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight: 36,46 g/mol (HCl)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	No reactivity hazard other than the effects described in sub-section below.
10.4 Conditions to avoid:	Avoid moisture in the installation.
10.5 Incompatible Materials:	Moisture. For material compatibility see latest version of ISO-11114. Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas. With water causes rapid corrosion of some metals. May react violently with alkalis.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013 Version: 3.1 SDS No.: 000010021725
 Last revised date: 23.02.2022 11/46

10.6 Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation Product Toxic if inhaled.

Hydrogen chloride
 LC 50 (Rat, 4 h): 1405 ppm
 LC 50 (Rat, 1 h): 2810 ppm
 Remarks: Delayed fatal pulmonary oedema possible.

Repeated dose toxicity Hydrogen chloride NOAEL (Rat(Female, Male), Inhalation, 4 - 91 d): 10 ppm(m) Inhalation
 Experimental result, Key study

Skin Corrosion/Irritation Product Causes severe burns.

Serious Eye Damage/Eye Irritation Product Causes serious eye damage.

Hydrogen chloride in vivo (Rabbit, 1 hrs): Category 1EU

Respiratory or Skin Sensitization Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity Product Based on available data, the classification criteria are not met.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		12/46

Carcinogenicity	
Product	Based on available data, the classification criteria are not met.
Reproductive toxicity	
Product	Based on available data, the classification criteria are not met.
Specific Target Organ Toxicity - Single Exposure	
Product	Based on available data, the classification criteria are not met.
Hydrogen chloride	Severe corrosion to the respiratory tract at high concentrations.
Specific Target Organ Toxicity - Repeated Exposure	
Product	Based on available data, the classification criteria are not met.
Aspiration Hazard	
Product	Not applicable to gases and gas mixtures..

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity	
Product	No ecological damage caused by this product.
Acute toxicity - Fish	
Hydrogen chloride	EC 50 (Fish, 96 h): 3,25 - 3,5 mg/l
Acute toxicity - Aquatic Invertebrates	
Hydrogen chloride	EC 50 (Water flea (Daphnia magna), 48 h): 4,92 mg/l
Toxicity to Aquatic Plants	
Hydrogen chloride	EC 50 (Alga, 72 h): 4,7 mg/l

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		13/46

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Results of PBT and vPvB assessment

Product Not classified as PBT or vPvB.

12.6 Other adverse effects:

Other Ecological Information

May cause pH changes in aqueous ecological systems.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Must not be discharged to atmosphere. Consult supplier for specific recommendations.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information

ADR

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name:	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
Hazard No. (ADR):	268
Tunnel restriction code:	(C/D)
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		14/46

RID

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.3, 8
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-

IMDG

14.1 UN Number:	UN 1050
14.2 UN Proper Shipping Name:	HYDROGEN CHLORIDE, ANHYDROUS
14.3 Transport Hazard Class(es)	
Class:	2.3
Label(s):	2.3, 8
EmS No.:	F-C, S-U
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-

IATA

14.1 UN Number:	UN 1050
14.2 Proper Shipping Name:	Hydrogen chloride, anhydrous
14.3 Transport Hazard Class(es):	
Class:	2.3
Label(s):	-
14.4 Packing Group:	-
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Forbidden.
Cargo aircraft only:	Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 15/46

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, as amended.:

Chemical	CAS-No.	Lower-tier Requirements	Upper-tier Requirements
Hydrogen chloride	7647-01-0	25.000 kg	250.000 kg

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen chloride	7647-01-0	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
 This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013 Version: 3.1 SDS No.: 000010021725
 Last revised date: 23.02.2022 16/46

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
 Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
 European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
 European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
 European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.
 International Programme on Chemical Safety (<http://www.inchem.org/>)
 ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
 Matheson Gas Data Book, 7th Edition.
 National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
 The ESIS (European chemical Substances Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
 The European Chemical Industry Council (CEFIC) ERICards.
 United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
 Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
 Substance specific information from suppliers.
 Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Training information: Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Acute Tox. 3, H331
 Skin Corr. 1A, H314
 Eye Dam. 1, H318
 Press. Gas Liq. Gas, H280



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021725
Last revised date:	23.02.2022		17/46

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 23.02.2022

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 18/46

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1)	Industrial use, Formulation & (re)packing of substances and mixtures
Exposure Scenario 2)	Industrial use, Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.
Exposure Scenario 3)	Industrial use, Using gas for metal treatment.
Exposure Scenario 4)	Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

Exposure Scenario 1)

Exposure Scenario worker

1. Industrial use, Formulation & (re)packing of substances and mixtures	
List of use descriptors	
Sector(s) of use	
Product categories [PC]:	
Name of contributing environmental scenario and corresponding ERC	<p><u>Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:</u> ERC2: Formulation into mixture</p>
Contributing Scenarios	<p><u>Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions</p> <p>PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities</p>
2.1. Contributing exposure scenario controlling environmental exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.	
Product characteristics	



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 19/46

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
20/46

	Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 21/46

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
 Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1
Hours per shift	<= 4 h	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 22/46

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
23/46

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

ERC2:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

ERC2:

Compartment	PEC	RCR	Method	Remarks
Water		< 1	Qualitative approach used to conclude safe use.	May cause pH changes in aqueous ecological systems.

Health:

Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, without local	0,03 mg/m ³	0,002		none



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 24/46

	exhaust ventilation				
--	---------------------	--	--	--	--

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, without local exhaust ventilation	0,015 mg/m ³	0,002		none

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, with local exhaust	13,69 mg/m ³	0,913		none



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
25/46

	ventilation				
--	-------------	--	--	--	--

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, with local exhaust ventilation	4,11 mg/m ³	0,514		none

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 2)



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 26/46

Exposure Scenario worker

1. Industrial use, Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.

List of use descriptors	
Sector(s) of use	SU9: Manufacture of fine chemicals
Product categories [PC]:	PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Using gas as feedstock in chemical processes.:</u> ERC6a: Use of intermediate
---	---

Contributing Scenarios	<u>Using gas as feedstock in chemical processes.:</u> PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 27/46

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
28/46

Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
29/46

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1
Hours per shift	<= 4 h	5 days per week	PROC8b

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general				Chemical production or refinery in closed process



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 30/46

ventilation (1 to 3 air changes per hour).				without likelihood of exposure or processes with equivalent containment conditions
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at dedicated facilities

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
31/46

3. Exposure estimation

Environment:

Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.:

ERC6a:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

ERC6a:

Compartment	PEC	RCR	Method	Remarks
Water		< 1	Qualitative approach used to conclude safe use.	May cause pH changes in aqueous ecological systems.

Health:

Using gas as feedstock in chemical processes., Use of gas to manufacture pharmaceutical products., Use gas as catalyst regenerator.:

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, without local exhaust ventilation	0,03 mg/m ³	0,002		none

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, without local exhaust ventilation	0,015 mg/m ³	0,002		none

PROC1:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 32/46

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC1:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation	13,69 mg/m ³	0,913		none

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, with local exhaust ventilation	4,11 mg/m ³	0,514		none

PROC8b:

Route of Exposure	Specific	Exposure	RCR	Method	Remarks
-------------------	----------	----------	-----	--------	---------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 33/46

	condition	level			
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC8b:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency. Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 3)

Exposure Scenario worker

1. Industrial use, Using gas for metal treatment.

List of use descriptors	
Sector(s) of use	SU14: Manufacture of basic metals, including alloys SU15: Manufacture of fabricated metal products, except machinery and equipment
Product categories [PC]:	PC14: Metal surface treatment products



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 34/46

Name of contributing environmental scenario and corresponding ERC	<p><u>Using gas for metal treatment.:</u> ERC6a: Use of intermediate</p> <p>ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)</p>
---	---

Contributing Scenarios	<p><u>Using gas for metal treatment.:</u> PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature</p>
------------------------	---

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas for metal treatment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product	See section 9 of the SDS.
------------------------------	---------------------------

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 35/46

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 36/46

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
 Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas for metal treatment.

Process Categories:	PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature
---------------------	--

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 37/46

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC22

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions: . See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Manufacturing and processing of minerals and/or metals at substantially elevated temperature
Local exhaust ventilation				Manufacturing and processing of minerals and/or metals at substantially elevated temperature

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
38/46

				exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:
Using gas for metal treatment.:
ERC6a, ERC6b:

Compartment	PEC	RCR	Method	Remarks
Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.

ERC6a, ERC6b:

Compartment	PEC	RCR	Method	Remarks
Water		< 1	Qualitative approach used to conclude safe use.	May cause pH changes in aqueous ecological systems.

Health:



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
39/46

Using gas for metal treatment.:

PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

PROC22:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 40/46

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>

Exposure Scenario 4)

Exposure Scenario worker

1. Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

List of use descriptors	
Sector(s) of use	SU24: Scientific research and development
Product categories [PC]:	PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
---	---

Contributing Scenarios	<u>Using gas alone or in mixtures for the calibration of analysis equipment.:</u> PROC15: Use as laboratory reagent
------------------------	--

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 41/46

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release
------------------------	--

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Air	Handle substance within a closed system. Effectiveness: 100 %.
Soil	Soil emission controls are not applicable as there is no direct release to soil.
Water	Neutralisation. Effectiveness: 100 %.
Sediment:	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
42/46

Conditions and measures related to sewage treatment plant

type:	Onsite Sewage Treatment Plant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Substance will dissociate upon contact with water, the only effect is the pH effect, therefore after passing through the sewage treatment plant exposure is considered negligible and with no risk.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH Chemical Safety Report

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.
Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Process Categories: PROC15: Use as laboratory reagent

Product characteristics



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 43/46

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
--	---

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	4260 kPa
Process temperature:	>= 20 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.
--	-----------------------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See section 8 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a good standard of				Use as laboratory reagent



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
44/46

controlled ventilation (10 to 15 air changes per hour).				
Local exhaust ventilation				Use as laboratory reagent

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				Ensure operatives are trained to minimise exposures.
				Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH Chemical Safety Report

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:
Using gas alone or in mixtures for the calibration of analysis equipment.:
ERC8b:

Compartment	PEC	RCR	Method	Remarks
-------------	-----	-----	--------	---------



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
45/46

Air		< 1	Qualitative approach used to conclude safe use.	Not classified as PBT or vPvB. As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.
-----	--	-----	---	--

ERC8b:

Compartment	PEC	RCR	Method	Remarks
Water		< 1	Qualitative approach used to conclude safe use.	May cause pH changes in aqueous ecological systems.

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, short-term, local, (acute)	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
inhalative, long-term, local	Indoor use, with local exhaust ventilation	mg/m ³	< 1		No exposure assessment presented for human health.

PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, short-term, systemic, (acute)			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen chloride, anhydrous

Issue Date: 16.01.2013
 Last revised date: 23.02.2022

Version: 3.1

SDS No.: 000010021725
 46/46

					exposure is not assessed in this exposure scenario
--	--	--	--	--	--

PROC15:

Route of Exposure	Specific condition	Exposure level	RCR	Method	Remarks
dermal, long-term, systemic			< 1		Since the product has corrosive properties, dermal exposure has to be minimised as far as technically feasible. A DNEL for dermal effects has not been derived. Thus, dermal exposure is not assessed in this exposure scenario

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see <http://www.ecetoc.org/tra>