

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
1/16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: H2 1 %;HCl 5 %;Ne 94 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273**E-mail:** office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.

T; R23 C; R35

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure	Compressed gas	H280: Contains gas under pressure; may explode if heated.
----------------------	----------------	---

Health Hazards

Skin corrosion	Category 1A	H314: Causes severe skin burns and eye damage.
Serious eye damage	Category 1	H318: Causes serious eye damage.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
 Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
 2/16

2.2 Label Elements

Contains: Hydrogen chloride



Signal Words: Danger

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.
 H314: Causes severe skin burns and eye damage.

Precautionary Statement

Prevention: P260: Do not breathe gas/vapors.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P303+P361+P353+P315: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Get immediate medical advice/attention.
 P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
 P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

EUH071: Corrosive to the respiratory tract.

2.3 Other hazards: None.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	Notes
Hydrogen	H2	1%	1333-74-0	215-605-7	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
3/16

Hydrogen chloride	HCl	5%	7647-01-0	231-595-7	01-2119484862-27	#
Neon	Ne	94%	7440-01-9	231-110-9	Listed in Annex IV/V of Regulation (EC) No 1907/2006 (REACH), exempted from registration.	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

This substance has workplace exposure limit(s).

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Classification		Notes
Hydrogen	DSD:	F+; R12	
	CLP:	Press. Gas Compr. Gas;H280, Flam. Gas 1;H220	Note U
Hydrogen chloride	DSD:	C; R35 T; R23	Nota 5
	CLP:	Press. Gas Liquef. Gas;H280, Skin Corr. 1A;H314, Acute Tox. 3;H331, Eye Dam. 1;H318	
Neon	DSD:	none	
	CLP:	Press. Gas Compr. Gas;H280	

DSD: Directive 67/548/EEC.

Nota 5: The concentration limits for gaseous preparations are expressed as volume per volume percentage.

CLP: Regulation No. 1272/2008.

Note U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

The full text for all R-phrases and H-statements is displayed in section 16.

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Make sure to remove any contact lenses from the eyes before rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
 Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
 4/16

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Causes severe skin burns and eye damage. May be harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Causes severe skin burns and eye damage. May be harmful if inhaled.

Treatment: None.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water. Dry powder. Foam. Carbon Dioxide.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products.

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
 Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
5/16

- 6.2 Environmental Precautions:** Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.
- 6.3 Methods and material for containment and cleaning up:** Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.
- 6.4 Reference to other sections:** Refer to sections 8 and 13.

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
- 7.2 Conditions for safe storage, including any incompatibilities:** Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.
- 7.3 Specific end use(s):** None.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
 Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
 6/16

SECTION 8: Exposure controls/personal protection
8.1 Control Parameters
Occupational Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Hydrogen chloride	TWA	5 ppm 8 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	STEL	10 ppm 15 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	MAK	5 ppm 8 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	10 ppm 15 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

DNEL-Values

Critical component	type	Value	Remarks
Hydrogen chloride	Worker - inhalative, short-term - local	15	-
	Worker - inhalative, long-term - local	8	-

PNEC-Values

Critical component	type	Value	Remarks
Hydrogen chloride	Aquatic (marine water)	36 µg/l	-
	Sewage treatment plant	36 µg/l	-
	Aquatic (intermit. releases)	45 µg/l	-
	Aquatic (freshwater)	36 µg/l	-

8.2 Exposure controls
Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
7/16**Individual protection measures, such as personal protective equipment**

General information:	A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
Eye/face protection:	Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
Skin protection	
Hand Protection:	Wear working gloves while handling containers Guideline: EN 388 Protective gloves against mechanical risks. Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
Body protection:	No special precautions.
Other:	Wear safety shoes while handling containers Guideline: ISO 20345 Personal protective equipment - Safety footwear.
Respiratory Protection:	Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
 Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
 8/16

SECTION 9: Physical and chemical properties
--

9.1 Information on basic physical and chemical properties**Appearance**

Physical state:	Gas
Form:	Compressed gas
Color:	H2: Colorless HCl: Colorless to slight yellow Ne: Colorless
Odor:	H2: Odorless HCl: Pungent Ne: Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	not applicable.
Melting Point:	No data available.
Boiling Point:	No data available.
Sublimation Point:	not applicable.
Critical Temp. (°C):	No data available.
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	This product is not flammable.
Flammability Limit - Upper (%):	not applicable.
Flammability Limit - Lower (%):	not applicable.
Vapor pressure:	No reliable data available.
Vapor density (air=1):	0,73 (calculated) (15 °C)
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	No data available.
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	No data available.
Explosive properties:	Not applicable.
Oxidizing properties:	not applicable.

9.2 Other information: None.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
 Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
 9/16

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	No data available.
10.4 Conditions to avoid:	Avoid moisture in the installation.
10.5 Incompatible Materials:	Moisture. For material compatibility see latest version of ISO-11114.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral Product	Based on available data, the classification criteria are not met.
Acute toxicity - Dermal Product	Based on available data, the classification criteria are not met.
Acute toxicity - Inhalation Product	ATEmix (4 h): > 20000 ppm Based on available data, the classification criteria are not met.
Component Information Hydrogen chloride	LC 50 (Rat, 4 h): 1405 ppm LC 50 (Rat, 1 h): 2810 ppm Remarks: Delayed fatal pulmonary oedema possible.
Repeated dose toxicity Component Information Hydrogen chloride	NOAEL (Rat(Female, Male), Inhalation, 4 - 91 d): 10 ppm(m) Inhalation Experimental result, Key study
Skin Corrosion/Irritation Product	Causes severe burns.

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
10/16**Serious Eye Damage/Eye Irritation****Product** Causes serious eye damage.**Component Information**

Hydrogen chloride in vivo (Rabbit, 4 - 96 hrs): Risk of serious damage to eyes.83/467/EEC

Respiratory or Skin Sensitization**Product** Based on available data, the classification criteria are not met.**Germ Cell Mutagenicity****Product** Based on available data, the classification criteria are not met.**Carcinogenicity****Product** Based on available data, the classification criteria are not met.**Reproductive toxicity****Product** Based on available data, the classification criteria are not met.**Specific Target Organ Toxicity - Single Exposure****Product** May cause respiratory irritation.**Component Information**

Hydrogen chloride Severe corrosion to the respiratory tract at high concentrations.

Specific Target Organ Toxicity - Repeated Exposure**Product** Based on available data, the classification criteria are not met.**Aspiration Hazard****Product** Not applicable to gases and gas mixtures..**SECTION 12: Ecological information****12.1 Toxicity****Acute toxicity****Product** No ecological damage caused by this product.**Acute toxicity - Fish****Component Information**

Hydrogen chloride EC 50 (Fish, 96 h): 3,25 - 3,5 mg/l

Acute toxicity - Aquatic Invertebrates**Component Information**

Hydrogen chloride EC 50 (Water flea (Daphnia magna), 48 h): 4,92 mg/l

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
11/16**Toxicity to microorganisms
Component Information****Toxicity to Aquatic Plants
Component Information**

Hydrogen chloride EC 50 (Alga, 72 h): 4,7 mg/l

**12.2 Persistence and Degradability
Product**

Not applicable to gases and gas mixtures..

**12.3 Bioaccumulative Potential
Product**

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in Soil
Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB
assessment
Product**

Not classified as PBT or vPvB.

12.6 Other Adverse Effects:

No ecological damage caused by this product.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****General information:**

Avoid discharges to atmosphere. Consult supplier for specific recommendations.

Disposal methods:Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.**European Waste Codes****Container:**

16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
12/16**SECTION 14: Transport information****ADR**

14.1 UN Number: UN 1956
14.2 UN Proper Shipping Name: COMPRESSED GAS, N.O.S.(Neon, Hydrogen chloride)
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.2
Hazard No. (ADR): 20
Tunnel restriction code: (E)
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1956
14.2 UN Proper Shipping Name: COMPRESSED GAS, N.O.S.(Neon, Hydrogen chloride)
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.2
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 1956
14.2 UN Proper Shipping Name: COMPRESSED GAS, N.O.S.(Neon, Hydrogen chloride)
14.3 Transport Hazard Class(es)
Class: 2.2
Label(s): 2.2
EmS No.: F-C, S-V
14.3 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
13/16

IATA

14.1 UN Number:	UN 1956
14.2 Proper Shipping Name:	COMPRESSED GAS, N.O.S.(Neon, Hydrogen chloride)
14.3 Transport Hazard Class(es):	
Class:	2.2
Label(s):	2.2
14.4 Packing Group:	-
14.5 Environmental hazards:	not applicable
14.6 Special precautions for user:	-
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	1,0 - 10%

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Hydrogen chloride	7647-01-0	1,0 - 10%

Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	1,0 - 10%

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**

Issue Date: 20.12.2012

Version: 1.1

SDS No.: 000010007916

Last revised date: 26.01.2017

14/16

Hydrogen chloride	7647-01-0	1,0 - 10%
-------------------	-----------	-----------

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen	1333-74-0	1,0 - 10%
Hydrogen chloride	7647-01-0	1,0 - 10%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 453/2010.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

SAFETY DATA SHEET

H2 1 %;HCl 5 %;Ne 94 %

Issue Date: 20.12.2012
Last revised date: 26.01.2017

Version: 1.1

SDS No.: 000010007916
15/16

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the R-phrases and H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
R12	Extremely flammable.
R23	Toxic by inhalation.
R35	Causes severe burns.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Skin Corr. 1A, H314
Eye Dam. 1, H318
STOT SE 3, H335
Press. Gas Compr. Gas, H280

SAFETY DATA SHEET**H2 1 %;HCl 5 %;Ne 94 %**

Issue Date: 20.12.2012

Version: 1.1

SDS No.: 000010007916

Last revised date: 26.01.2017

16/16

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date:

26.01.2017

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.