

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
1/14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Product name: Isobutane
Trade name: Gasart 431 Isobutan 2.5, Isobutan 3.5, R600A
Other Name: R600a

Additional identification

Chemical name: Isobutane
Chemical formula: C₄H₁₀
INDEX No. 601-004-00-0
CAS-No. 75-28-5
EC No. 200-857-2
REACH Registration No. 01-2119485395-27

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Aerosol propellant. Foaming agent in personal care products. Refrigerant.
Transfilling gas or liquid, Use as a fuel Use as an Intermediate (transported, on-site isolated). Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical processes. Formulation of mixtures with gas in pressure receptacles.
Consumer use.

Uses advised against Foaming agent in personal care products. Aerosol propellant. Use as a fuel
Uses other than those listed above are not supported. Contact supplier for more information on uses.

1.3 Details of the supplier of the safety data sheet**Supplier**

Linde Gas GmbH
Carl-von-Linde-Platz 1
A-4651 Stadl-Paura

Telephone: +43 50 4273**E-mail:** office@at.linde-gas.com

1.4 Emergency telephone number: Emergency number Linde: + 43 50 4273 (during business hours), Poisoning Information Center: +43 1 406 43 43

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
2/14

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1	H220: Extremely flammable gas.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements

Signal Words: Danger

Hazard Statement(s): H220: Extremely flammable gas.
H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

2.3 Other hazards: Contact with evaporating liquid may cause frostbite or freezing of skin.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
3/14

SECTION 3: Composition/information on ingredients**3.1 Substances**

Chemical name Isobutane
INDEX No.: 601-004-00-0
CAS-No.: 75-28-5
EC No.: 200-857-2
REACH Registration No.: 01-2119485395-27
Purity: 100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.

Trade name: Gasart 431 Isobutan 2.5, Isobutan 3.5, R600A

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Get medical attention. Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical attention immediately.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
4/14

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water Spray or Fog. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide.

5.2 Special hazards arising from the substance or mixture: Heat may cause the containers to explode.

Hazardous Combustion Products: Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so. Prevent spillage entering a watercourse or sewer, contaminating soil or vegetation. If this is not possible notify police and appropriate authorities immediately.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
5/14

6.3 Methods and material for containment and cleaning up: Ventilate the area. Eliminate sources of ignition. Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (Ground free from frost).

6.4 Reference to other sections: Refer to sections 8 and 13.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

SAFETY DATA SHEET

Isobutane

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
6/14

7.2 Conditions for safe storage, including any incompatibilities:

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s):

None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Isobutane	MAK	800 ppm 1.900 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)
	MAK CEIL	1.600 ppm 3.800 mg/m ³	Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001 (09 2007)

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.

Eye/face protection:

Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
7/14

Skin protection**Hand Protection:**

Wear working gloves while handling containers
Guideline: EN 388 Protective gloves against mechanical risks.

Body protection:

Wear fire resistant or flame retardant clothing.
Guideline: EN 943 Protective clothing against liquid and gaseous chemicals, including liquid aerosols and solid particles.

Other:

Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection:

Respiratory Protective Equipment (RPE) is recommended when conducting operations according to exposure scenarios contained in the extended safety data sheet. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. In case of inadequate ventilation, use respiratory protection.

Material: Filter AX

Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.

Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.

Thermal hazards:

No precautionary measures are necessary.

Hygiene measures:

Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls:

For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance****Physical state:**

Gas

Form:

Liquefied gas

Color:

Colorless

Odor:

Gasoline-like or natural gas odor

Odor Threshold:

Odor threshold is subjective and is inadequate to warn of over exposure.

pH:

not applicable.

Melting Point:

-182,47 °C Experimental result, Key study

Boiling Point:

-11,73 °C (1.013 hPa) Experimental result, Key study

Sublimation Point:

not applicable.

Critical Temp. (°C):

135,0 °C

SAFETY DATA SHEET

Isobutane

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
8/14

Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Flammable Gas
Flammability Limit - Upper (%):	9,5 %(V) Experimental result, Key study
Flammability Limit - Lower (%):	1,5 %(V)
Vapor pressure:	347,97 kPa (25 °C)
Vapor density (air=1):	2,01 AIR=1
Relative density:	0,59
Solubility(ies)	
Solubility in Water:	54 mg/l
Partition coefficient (n-octanol/water):	2,76
Autoignition Temperature:	460 °C Experimental result, Key study
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,238 mPa.s (-10 °C)
Explosive properties:	Not applicable.
Oxidizing properties:	not applicable.

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

Molecular weight: 58,12 g/mol (C₄H₁₀)

SECTION 10: Stability and reactivity

10.1 Reactivity:	No reactivity hazard other than the effects described in sub-section below.
10.2 Chemical Stability:	Stable under normal conditions.
10.3 Possibility of hazardous reactions:	Can form a potentially explosive atmosphere in air. May react violently with oxidants.
10.4 Conditions to avoid:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
10.5 Incompatible Materials:	Air and oxidizers. For material compatibility see latest version of ISO-11114.
10.6 Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
9/14

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects**Acute toxicity - Oral
Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Dermal
Product**

Based on available data, the classification criteria are not met.

**Acute toxicity - Inhalation
Product**

Based on available data, the classification criteria are not met.

Isobutane

LC 50 (Rat, 10 min): > 800000 ppm Remarks: Inhalation Experimental result, Key study

**Repeated dose toxicity
Isobutane**

NOAEL (Rat(Female, Male), Inhalation, 13 Weeks): 10.000 ppm(m) Inhalation Read-across based on grouping of substances (category approach), Key study

**Skin Corrosion/Irritation
Product**

Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation
Product**

Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization
Product**

Based on available data, the classification criteria are not met.

**Germ Cell Mutagenicity
Product**

Based on available data, the classification criteria are not met.

**Carcinogenicity
Product**

Based on available data, the classification criteria are not met.

**Reproductive toxicity
Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure
Product**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure
Product**

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
10/14

**Aspiration Hazard
Product**

Not applicable to gases and gas mixtures..

SECTION 12: Ecological information**12.1 Toxicity****Acute toxicity
Product**

No ecological damage caused by this product.

**Acute toxicity - Fish
Isobutane**

LC 50 (Various, 96 h): 24,11 mg/l (QSAR) Remarks: QSAR QSAR, Key study

Acute toxicity - Aquatic Invertebrates

Isobutane

LC 50 (Daphnid, 48 h): 14,22 mg/l (QSAR) Remarks: QSAR QSAR, Key study

**12.2 Persistence and Degradability
Product**

Not applicable to gases and gas mixtures..

**Biodegradation
Isobutane**

100 % (385,5 h) Detected in water. Experimental result, Key study

**12.3 Bioaccumulative potential
Product**

The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

**12.4 Mobility in soil
Product**

Because of its high volatility, the product is unlikely to cause ground or water pollution.

**12.5 Results of PBT and vPvB
assessment
Product**

Not classified as PBT or vPvB.

12.6 Other adverse effects:**Global Warming Potential**

Global warming potential: 3
Contains greenhouse gas(es). When discharged in large quantities may contribute to the greenhouse effect.

Isobutane

EU. F-Gases Subject to Emission Limits/Reporting (Annexes I, II), Regulation 517/2014/EU on FGGs
- Global warming potential: 3 100-yr

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
11/14

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

General information: Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information**ADR**

14.1 UN Number: UN 1969
14.2 UN Proper Shipping Name: ISOBUTANE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.1
Hazard No. (ADR): 23
Tunnel restriction code: (B/D)
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1969
14.2 UN Proper Shipping Name: ISOBUTANE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.1
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
12/14

IMDG

14.1 UN Number: UN 1969
14.2 UN Proper Shipping Name: ISOBUTANE
14.3 Transport Hazard Class(es)
Class: 2.1
Label(s): 2.1
EmS No.: F-D, S-U
14.3 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -

IATA

14.1 UN Number: UN 1969
14.2 Proper Shipping Name: Isobutane
14.3 Transport Hazard Class(es):
Class: 2.1
Label(s): 2.1
14.4 Packing Group: -
14.5 Environmental hazards: not applicable
14.6 Special precautions for user: -
Other information
Passenger and cargo aircraft: Forbidden.
Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:****EU Regulations**

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
13/14

Chemical name	CAS-No.	Concentration
Isobutane	75-28-5	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)
(<http://www.atsdr.cdc.gov/>).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances

<http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (<http://www.inchem.org/>)

ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET**Isobutane**

Issue Date: 16.01.2013
Last revised date: 28.11.2018

Version: 1.1

SDS No.: 000010021773
14/14

Training information: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1, H220

Press. Gas Liq. Gas, H280

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 28.11.2018

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.